
Basic Applied Topology Subprograms

Brad Nelson

Aug 20, 2021

CONTENTS:

1	Why BATS?	3
1.1	Installation	3
1.2	Quick Start Guide	4
1.3	Tutorials	10
1.4	Examples	10
1.5	Library API	11
1.6	About BATS	235
2	Indices and tables	237
Index		239

The Basic Applied Topology Subprograms (BATS) are a C++ header-only library for applied algebraic topology. It includes functionality for

- Creation of simplicial, cubical, and cell complexes, as well as cellular maps
- Implementation of chain and homology functors
- Filtered complexes and persistent homology
- Diagrams of spaces and maps, and computation of zigzag homology
- Topological constructions such as Vietoris-Rips complexes, Witness complexes, Nerves of covers
- Sparse linear algebra over (finite) fields
- And more!

BATS attempts to balance performance with extensibility. The library uses template metaprogramming to make it easy to swap in and out different constructions while maintaining a consistent core functionality.

CHAPTER ONE

WHY BATS?

There are many very high-performance libraries for computing things like persistent homology that have been developed over the past decade. Unlike many of these libraries BATS is focused on functorality, and provides functionality to handle maps between topological spaces, chain maps, and induced maps on homology. The goal is to make it easier for researchers and practitioners to implement and explore the vast back catalog of algebraic topology while also providing applied functionality.

1.1 Installation

You can obtain BATS from GitHub:

```
$ git clone https://github.com/bnels/BATS.git
```

1.1.1 Dependencies

BATS is written in C++ and requires a compiler which is able to understand C++17 syntax. It has been run and tested on Linux (Ubuntu and Fedora distributions) using the gcc compiler.

BATS itself is header-only, and is built using STL data structures, meaning you don't need to find other headers.

To get the most out of BATS, you should compile with OpenMP.

```
$ g++ ...<other flags> -std=c++17 -fopenmp
```

1.1.2 Testing Installation

Once you have BATS on your computer, you can test your installation. from the root of your repository:

```
$ cd tests  
$ make test -j
```

1.2 Quick Start Guide

This guide will cover several basic use cases for BATS. More specialized functionality is covered in the tutorials and examples. Ultimately, you can use the API reference.

1.2.1 Simplicial Complexes and Homology

BATS offers two implementations of simplicial complexes: `SimplicialComplex` and `LightSimplicialComplex`. While the internal representations differ, they both have the same interface which can be used. When dealing with stand-alone simplices, BATS uses `std::vector<size_t>` to represent simplices, from which the vertex set and dimension of the simplex can be extracted.

Warning: Simplices in bats should generally be assumed to be *ordered*, meaning that $\{0, 1, 2\}$ is not the same as $\{1, 2, 0\}$. If you want to use *unordered* simplices, you can either add vertices in sorted order, or use a sorting algorithm before adding simplices to complexes.

The two main methods for adding simplices to simplicial complexes are `add`, which assumes you have already added the boundary of a simplex, and `add_recursive` which will add any faces that are not already present.

```
bats::SimplicialComplex X();
X.add_recursive({0,1,2});
X.add_recursive({2,3});
X.add({1,3});

X.print_summary();
```

The above code will create a `SimplicialComplex` with a single connected component and a single hole. The call to `X.print_summary()` will produce

```
SimplicialComplex, maxdim = 2
  dim 0 : 4 cells
  dim 1 : 5 cells
  dim 2 : 1 cells
10 total
```

Let's now compute homology.

```
using F2 = ModP<int, 2>;
auto R = bats::Reduce(X, F2());

R.print_summary();
```

The output of `bats::Reduce` will be a `ReducedChainComplex` with `F2` coefficients, which holds information used to compute homology. The output of `R.print_summary()` will be

```
ReducedChainComplex, maxdim = 2
  dim 0: 4, betti_0: 1
  dim 1: 5, betti_1: 1
  dim 2: 1, betti_2: 0
```

1.2.2 Persistent Homology

A filtration in BATS is a class which is templated over the type of the filtration values as well as the type of the underlying complex.

```
bats::Filtration<double>, bats::SimplicialComplex> F;
std::vector<size_t> spx;
spx = {0,1,2}; F.add_recursive(0.0, spx);
spx = {2,3};   F.add_recursive(1.0, spx);
spx = {1,3};   F.add(2.0, spx);

F.complex().print_summary();
```

The underlying SimplicialComplex is the same as in the previous example:

```
SimplicialComplex, maxdim = 2
  dim 0 : 4 cells
  dim 1 : 5 cells
  dim 2 : 1 cells
10 total
```

Again, we can use the Reduce function to compute homology. Because we are using a filtration as input, persistent homology will be computed, returning a ReducedFilteredChainComplex.

```
using F2 = ModP<int, 2>;
auto R = bats::Reduce(F, F2());

for (size_t k = 0; k < R.maxdim(); ++k) {
    std::cout << "\n" << k << "-dimensional barcode:\n";
    for (auto p : R.persistence_pairs(k)) {
        std::cout << p.str() << std::endl;
    }
}
```

The output will show one persistent 0-dimensional homology class as well as one persistent 1-dimensional homology class

```
0-dimensional barcode:
0 : (0,inf) <0,-1>
0 : (0,0) <1,0>
0 : (0,0) <2,1>
0 : (1,1) <3,3>

1-dimensional barcode:
1 : (0,0) <2,0>
1 : (2,inf) <4,-1>
```

The output of `R.persistence_pairs(k)` is a vector of PersistencePairs for k-dimensional persistent homology.

A PersistencePair includes 5 pieces of information: * The dimension of the homology class. * The birth and death parameters of the homology class. * The simplex indices responsible for birth and death.

1.2.3 Maps

BATS makes dealing with maps between topological spaces and associated chain maps and induced maps on homology easy. The relevant class is a CellularMap which keeps track of what cells in one complex map to what cells in another.

We'll just look at a wrapper for CellularMap, called SimplicialMap which can be used to extend a map on the vertex set of a SimplicialComplex to a map of simplices.

First, we'll build identical simplicial complexes X and Y which are both cycle graphs on four vertices.

```
bats::SimplicialComplex X;
X.add_recursive({0,1});
X.add_recursive({1,2});
X.add_recursive({2,3});
X.add_recursive({0,3});
bats::SimplicialComplex Y = X; // copy
```

We then build a simplicial map from X to Y which is extended from a reflection of the vertices.

```
std::vector<size_t> f0{2,1,0,3}; // reflection map
auto F = bats::SimplicialMap(X, Y, f0);
```

The map is extended by sending vertex i in X to vertex $f_0[i]$ in Y. Next, we can apply the chain functor. We'll use F3 coefficients.

```
// apply the chain functor
using F3 = ModP<int, 3>;
auto CX = bats::Chain(X, F3());
auto CY = bats::Chain(Y, F3());
auto CF = bats::Chain(F, F3());
```

Finally, we can compute homology of the chain complexes and the induced maps.

```
auto RX = bats::ReducedChainComplex(CX);
auto RY = bats::ReducedChainComplex(CY);
RX.print_summary();
RY.print_summary();

for (size_t k = 0; k < 2; k++) {
    std::cout << "\nInduced map in dimension " << k << std::endl;
    auto HF = bats::induced_map(CF, RX, RY, k);
    HF.print();
}
```

The following output will be produced:

```
ReducedChainComplex, maxdim = 1
dim 0: 4, betti_0: 1
dim 1: 4, betti_1: 1
ReducedChainComplex, maxdim = 1
dim 0: 4, betti_0: 1
dim 1: 4, betti_1: 1

Induced map in dimension 0
[0x7fff6f336460] : 1 x 1 ColumnMatrix
```

(continues on next page)

(continued from previous page)

```

1

Induced map in dimension 1
[0x7fff6f336460] : 1 x 1 ColumnMatrix
2

```

As expected, we see that X and Y both have 1-dimensional homology in dimensions 0 and 1. The induced map in dimension 0 is the identity, and the induced map in dimension 1 is multiplication by -1 (in mod-3 coefficients).

1.2.4 Zigzag Homology

We'll now compute a simple zigzag barcode, using the above example. We'll consider a diagram with two (identical) spaces, connected by a single edge which applies the reflection map in the above example.

```

bats::Diagram<bats::SimplicialComplex, bats::CellularMap> D(2,1);

bats::SimplicialComplex X;
X.add_recursive({0,1});
X.add_recursive({1,2});
X.add_recursive({2,3});
X.add_recursive({0,3});

std::vector<size_t> f0{2,1,0,3}; // reflection map
auto F = bats::SimplicialMap(X, X, f0);

D.set_node(0, X);
D.set_node(1, X);
D.set_edge(0, 0, 1, F); // edge 0: (0,1)

```

We can then apply the Chain and Hom functors, to obtain a diagram of homology spaces and maps between them

```

using F3 = ModP<int, 3>;
auto CD = bats::Chain(D, F3());
auto HD = bats::Hom(CD, (size_t) 1); // homology in dimension 1

```

Finally, we extract the barcode from the homology diagram

```

auto ps = barcode(HD, 1);
for (auto p : ps) {
    std::cout << p.str() << std::endl;
}

```

The output should look like: $1 : (0,1) <0,0>$. This indicates there is a 1-dimensional homology bar, which is born in the space with index 0 and survives until the space with index 1. The $<0,0>$ indicates which generators are associated with the homology class in the diagram.

1.2.5 Source Code

```

1 #include <vector>
2 #include <iostream>
3 #include <bats.hpp>
4
5 int main() {
6
7     // Simplicial complexes and Homology
8     {
9         bats::SimplicialComplex X;
10        X.add_recursive({0,1,2});
11        X.add_recursive({2,3});
12        X.add({1,3});
13
14        X.print_summary();
15
16        using F2 = ModP<int, 2>;
17        auto R = bats::Reduce(X, F2());
18
19        R.print_summary();
20    }
21
22    // Persistent homology
23    {
24        bats::Filtration<double, bats::SimplicialComplex> F;
25        std::vector<size_t> spx;
26        spx = {0,1,2}; F.add_recursive(0.0, spx);
27        spx = {2,3};   F.add_recursive(1.0, spx);
28        spx = {1,3};   F.add(2.0, spx);
29
30        F.complex().print_summary();
31
32        using F2 = ModP<int, 2>;
33        auto R = bats::Reduce(F, F2());
34
35        for (size_t k = 0; k < R.maxdim(); ++k) {
36            std::cout << "\n" << k << "-dimensional barcode:\n";
37            for (auto p : R.persistence_pairs(k)) {
38                std::cout << p.str() << std::endl;
39            }
40        }
41    }
42
43    // Maps
44    {
45        bats::SimplicialComplex X;
46        X.add_recursive({0,1});
47        X.add_recursive({1,2});
48        X.add_recursive({2,3});
49        X.add_recursive({0,3});
50        bats::SimplicialComplex Y = X; // copy
51

```

(continues on next page)

(continued from previous page)

```

52     X.print_summary();
53
54     std::vector<size_t> f0{2,1,0,3}; // reflection map
55     auto F = bats::SimplicialMap(X, Y, f0);
56
57     // apply the chain functor
58     using F3 = ModP<int, 3>;
59     auto CX = bats::Chain(X, F3());
60     auto CY = bats::Chain(Y, F3());
61     auto CF = bats::Chain(F, F3());
62
63     auto RX = bats::ReducedChainComplex(CX);
64     auto RY = bats::ReducedChainComplex(CY);
65     RX.print_summary();
66     RY.print_summary();
67
68     for (size_t k = 0; k < 2; k++) {
69         std::cout << "\nInduced map in dimension " << k << std::endl;
70         auto HF = bats::induced_map(CF, RX, RY, k);
71         HF.print();
72     }
73 }
74
75 // Zigzag homology
76 std::cout << "\nZigzag Example\n";
77 {
78     bats::Diagram<bats::SimplicialComplex, bats::CellularMap> D(2,1);
79
80     bats::SimplicialComplex X;
81     X.add_recursive({0,1});
82     X.add_recursive({1,2});
83     X.add_recursive({2,3});
84     X.add_recursive({0,3});
85
86     std::vector<size_t> f0{2,1,0,3}; // reflection map
87     auto F = bats::SimplicialMap(X, X, f0);
88
89     D.set_node(0, X);
90     D.set_node(1, X);
91     D.set_edge(0, 0, 1, F); // edge 0: (0,1)
92
93     using F3 = ModP<int, 3>;
94     auto CD = bats::Chain(D, F3());
95
96     auto HD = bats::Hom(CD, (size_t) 1); // homology in dimension 1
97
98     auto ps = bats::barcode(HD, 1);
99     for (auto p : ps) {
100         std::cout << p.str() << std::endl;
101     }
102
103 }
```

(continues on next page)

(continued from previous page)

```
104     }
105
106     return EXIT_SUCCESS;
107 }
108 }
```

1.3 Tutorials

1.3.1 Complexes

This tutorial will cover building and using complexes which represent topological spaces.

Interfaces

Chain Functor

There are several functions a complex should implement in order to be compatible with the chain functor.

Filtrations

Filtrations can be created from a complex as well as a list of filtration values. However, in order to construct filtrations incrementally the following methods should be implemented.

1.4 Examples

1.4.1 Zigzag Filtrations

A zigzag filtration allows cells to enter and exit a complex at specified parameters. Construction is similar to a filtration, but you need to specify entry as well as exit time. Zigzag filtration functionality is under the `bats::zigzag` namespace.

```
bats::zigzag::ZigzagFiltration<bats::SimplicialComplex> F;

std::vector<size_t> spx;
// create a cycle that persists for a while
spx = {0,1}; F.add_recursive(0.0, 10.0, spx);
spx = {0,2}; F.add_recursive(0.0, 10.0, spx);
spx = {1,2}; F.add_recursive(0.0, 10.0, spx);

// now block cycle for some period of time
spx = {0,1,2}; F.add(2.0, 4.0, spx);
```

You can compute a barcode using `bats::barcode`

```
using F2 = ModP<int, 2>;
auto ps = bats::zigzag::barcode(F, 1, F2(),
    bats::no_optimization_flag(),
```

(continues on next page)

(continued from previous page)

```
bats::standard_reduction_flag()
);

for (auto& pk : ps) {
    for (auto p : pk) {
        if (p.length() > 0)
            std::cout << p << std::endl;
    }
}
```

You should see the following output

```
0 : (0,10) <0(1),0(0)>
1 : (0,2) <2(1),0(1)>
1 : (4,10) <0(0),2(0)>
```

This indicates that there is a single connected component in the zigzag filtration. The two H1 classes correspond to the cycle, which isn't present when we put in the triangle between parameters 2 and 4.

1.5 Library API

1.5.1 Class Hierarchy

1.5.2 File Hierarchy

1.5.3 Full API

Namespaces

Namespace bats

Contents

- *Detailed Description*
- *Namespaces*
- *Classes*
- *Functions*
- *Typedefs*
- *Variables*

Detailed Description

We need to specify what is the conventional usage of permutation in bats!! [2, 0, 1] apply to [2.0 , 1.0 ,5.0] a) is [5.0, 2.0, 1.0] in matrix permutation notation b) is [1.0, 5.0 ,2.0] in traditioanl notation(in book From Mathematics to Generic Programming) We take the frist notation here, but notice that BATs, sometimes, will mix the two notations!!! Check before use!!! Since the above two notations are inverse to each other, inverse them if needed! Constructions on a grid Freudenthal triangulation

Namespaces

- *Namespace bats::detail*
- *Namespace bats::flags*
- *Namespace bats::future*
- *Namespace bats::rowmajor*
- *Namespace bats::util*
- *Namespace bats::zigzag*

Classes

- *Template Struct AbstractMetric*
- *Struct AngleDist*
- *Struct apparent_pairs_flag*
- *Struct bar*
- *Template Struct ChainComplex*
- *Template Struct ChainMap*
- *Struct clearing_flag*
- *Template Struct CochainComplex*
- *Struct compression_flag*
- *Struct compute_basis_flag*
- *Struct CosineDist*
- *Template Struct DataSet*
- *Template Struct DGLinearMap*
- *Template Struct DGVectorSpace*
- *Struct Diagram::Edge*
- *Struct divide_conquer_flag*
- *Struct Euclidean*
- *Struct extra_reduction_flag*
- *Template Struct filtered_edge*
- *Template Struct FilteredChainComplex*

- *Template Struct FilteredCochainComplex*
- *Struct L1Dist*
- *Struct LightSimplicialComplex::simplex_boundary_iterator*
- *Struct LInfDist*
- *Struct no_apparent_pairs_flag*
- *Struct no_optimization_flag*
- *Template Struct PersistencePair*
- *Template Struct ReducedDGVectorSpace*
- *Template Struct ReducedFilteredChainComplex*
- *Struct RPAngleDist*
- *Struct RPCosineDist*
- *Struct sparse_reduction_flag*
- *Struct standard_reduction_flag*
- *Template Struct tedge*
- *Struct triangle*
- *Template Struct Update_info*
- *Template Class BarcodePair*
- *Class CellComplex*
- *Class CellularMap*
- *Class CubicalComplex*
- *Template Class Diagram*
- *Template Class Filtration*
- *Template Class LightSimplicialComplex*
- *Template Class ReducedChainComplex*
- *Template Class ReducedCochainComplex*
- *Class SimplicialComplex*
- *Template Class SparseTrie*

Functions

- *Template Function bats::__ChainComplex(const CpxT&, T)*
- *Template Function bats::__ChainComplex(const CpxT&, const CpxT&, T)*
- *Template Function bats::__ChainFunctor*
- *Template Function bats::__CochainComplex*
- *Template Function bats::__FilteredChainComplex*
- *Template Function bats::__ReducedChainComplex*
- *Template Function bats::__ReducedCochainComplex*

- *Template Function bats::__ReducedFilteredChainComplex*
- *Template Function bats::add_dimension_recursive_flag(CpxT&, const NT&, const size_t, const size_t, const std::vector<size_t>&, std::vector<size_t>&)*
- *Template Function bats::add_dimension_recursive_flag(Filtration<T, CpxT>&, const NT&, const size_t, const size_t, const std::vector<size_t>&, std::vector<size_t>&, const T&)*
- *Template Function bats::add_dimension_recursive_flag(Filtration<T, CpxT>&, const NT&, const size_t, const size_t, const std::vector<size_t>&, std::vector<size_t>&, const T&, bool, const cell_ind&)*
- *Template Function bats::add_dimension_recursive_flag_extension*
- *Template Function bats::add_dimension_recursive_flag_unsafe*
- *Function bats::add_dimension_recursive_nerve*
- *Template Function bats::add_normal_noise(Matrix<T>&, const T, const T)*
- *Template Function bats::add_normal_noise(Matrix<T>&, unsigned, const T, const T)*
- *Template Function bats::add_normal_noise(DataSet<T>&, const T, const T)*
- *Template Function bats::add_normal_noise(DataSet<T>&, unsigned, const T, const T)*
- *Template Function bats::add_uniform_noise(Matrix<T>&, unsigned, const T, const T)*
- *Template Function bats::add_uniform_noise(Matrix<T>&, const T, const T)*
- *Template Function bats::add_uniform_noise(DataSet<T>&, const T, const T)*
- *Function bats::all_pairs*
- *Template Function bats::approx_center*
- *Template Function bats::assign_set_lower*
- *Template Function bats::assign_set_upper*
- *Template Function bats::barcode(const Diagram<NT, std::vector<TM>>&, Args ...)*
- *Template Function bats::barcode(const Diagram<NT, TM>&, size_t)*
- *Template Function bats::barcode(const Diagram<NT, TM>&, size_t, flags::divide_conquer)*
- *Template Function bats::barcode(const Diagram<NT, TM>&, size_t, flags::leftward)*
- *Template Function bats::barcode(const Diagram<NT, TM>&, size_t, flags::rightward)*
- *Template Function bats::barcode_equality*
- *Template Function bats::barcode_form_divide_conquer*
- *Template Function bats::barcode_form_leftright*
- *Template Function bats::barcode_form_rightleft*
- *Template Function bats::barcode_from_barcode_form*
- *Function bats::bars_to_pairs*
- *Function bats::bivariate_cover*
- *Template Function bats::Chain(const Diagram<CpxT, CellularMap>&, T)*
- *Template Function bats::Chain(const CpxT&, T)*
- *Template Function bats::Chain(const CpxT&, const CpxT&, T)*
- *Template Function bats::Chain(const CellularMap&, T)*

- *Template Function bats::Chain(const Filtration<FT, CpxT>&, T)*
- *Template Function bats::ChainFunctor(const DT&)*
- *Template Function bats::ChainFunctor(const DT&, TF)*
- *Template Function bats::circle*
- *Template Function bats::CompleteFlagFiltration*
- *Template Function bats::coordinate_projection*
- *Function bats::Cube(size_t, size_t)*
- *Function bats::Cube(size_t, size_t, size_t)*
- *Function bats::Cube(size_t, size_t, size_t, size_t, size_t, size_t, size_t, size_t)*
- *Function bats::CubicalMap*
- *Template Function bats::DGLinearFunctor*
- *Template Function bats::DiscreteMorozovZigzag*
- *Template Function bats::DiscreteMorozovZigzagSets*
- *Template Function bats::dowker_edge_param(const Matrix<T>&, const size_t, const size_t)*
- *Template Function bats::dowker_edge_param(const Matrix<T>&)*
- *Template Function bats::dowker_filtration_edges*
- *Template Function bats::DowkerFiltration(const Matrix<T>&, T, size_t)*
- *Template Function bats::DowkerFiltration(const DataSet<T>&, const DataSet<T>&, const M&, T, size_t)*
- *Template Function bats::DowkerFiltration(const Matrix<T>&, const bats::Cover&, T, size_t)*
- *Template Function bats::DowkerFiltration(const DataSet<T>&, const DataSet<T>&, const M&, const bats::Cover&, T, size_t)*
- *Template Function bats::EilenbergZilber(const CpxT&, const CpxT&, const size_t, T)*
- *Template Function bats::EilenbergZilber(const CpxT&, const CpxT&, const CpxT&, const CpxT&, const size_t, T)*
- *Template Function bats::enclosing_radius*
- *Template Function bats::euclidean*
- *Function bats::extension_perm*
- *Template Function bats::extract_basis_indices(const MT&, const std::vector<size_t>&)*
- *Template Function bats::extract_basis_indices(const MT&)*
- *Template Function bats::extract_dimension*
- *Function bats::filtration_iperm*
- *Template Function bats::filtration_sortperm(const std::vector<T>&)*
- *Template Function bats::filtration_sortperm(const std::vector<std::vector<T>>&)*
- *Template Function bats::find_perm_from_vector*
- *Template Function bats::flag_filtration_edges*
- *Template Function bats::FlagComplex*
- *Template Function bats::FlagFiltration*

- *Template Function bats::FlagFiltration_extension*
- *Template Function bats::force_repel_rp*
- *Template Function bats::Freudenthal(size_t, size_t)*
- *Template Function bats::Freudenthal(size_t, size_t, size_t)*
- *Template Function bats::Freudenthal(size_t, size_t, size_t, size_t, size_t, size_t, size_t, size_t, size_t)*
- *Template Function bats::Freudenthal(const CubicalComplex&, size_t, size_t, size_t)*
- *Function bats::gen_cylinder*
- *Function bats::get_clearing_inds*
- *Template Function bats::get_compression_inds*
- *Template Function bats::get_dM_ZZ_inds*
- *Template Function bats::get_m*
- *Template Function bats::get_subset*
- *Template Function bats::greedy_landmarks*
- *Template Function bats::greedy_landmarks_hausdorff(const DataSet<T>&, const M&, const size_t)*
- *Template Function bats::greedy_landmarks_hausdorff(const Matrix<T>&, const size_t)*
- *Template Function bats::hausdorff_landmarks*
- *Template Function bats::Hom(const Diagram<DGVectorSpace<TM>, DGLinearMap<TM>>&, size_t)*
- *Template Function bats::Hom(const Diagram<ChainComplex<TM>, ChainMap<TM>>&, size_t)*
- *Template Function bats::Hom(const Diagram<ChainComplex<TM>, ChainMap<TM>>&, bool)*
- *Function bats::identity_perm*
- *Template Function bats::increment_m*
- *Template Function bats::induced_map(const ChainMap<ColumnMatrix<TVec>>&, const ReducedChainComplex<ColumnMatrix<TVec>>&, const ReducedChainComplex<ColumnMatrix<TVec>>&, size_t)*
- *Template Function bats::induced_map(const ChainMap<ColumnMatrix<TVec>>&, const ReducedCochainComplex<ColumnMatrix<TVec>>&, const ReducedCochainComplex<ColumnMatrix<TVec>>&, size_t)*
- *Template Function bats::induced_map(const DGLinearMap<ColumnMatrix<TVec>>&, const ReducedDGVectorSpace<ColumnMatrix<TVec>>&, const ReducedDGVectorSpace<ColumnMatrix<TVec>>&, size_t)*
- *Template Function bats::interval*
- *Template Function bats::is_left_arrow*
- *Template Function bats::kdist*
- *Template Function bats::kron_chain_shift*
- *Template Function bats::kron_chains*
- *Template Function bats::kron_homology*
- *Template Function bats::kron_index*
- *Template Function bats::landmark_cover*
- *Template Function bats::landmark_eps_cover*

- *Function bats::linear_cover_intersection_diagram*
- *Function bats::linear_subset_union_diagram*
- *Template Function bats::LowerStarFiltration*
- *Template Function bats::make_edge*
- *Template Function bats::mayer_vietoris_boundary*
- *Template Function bats::neighborhood(const VectorView<T>&, const DataSet<T>&, const M&, const T)*
- *Template Function bats::neighborhood(const VectorView<T>&, const DataSet<T>&, const M&, const size_t)*
- *Template Function bats::neighborhoods(const DataSet<T>&, const DataSet<T>&, const M&, const T)*
- *Template Function bats::neighborhoods(const DataSet<T>&, const DataSet<T>&, const M&, const size_t)*
- *Template Function bats::neighborhoods(const Matrix<T>&, const T)*
- *Function bats::Nerve(const bats::Cover&, const size_t)*
- *Function bats::Nerve(const Diagram<bats::Cover, std::vector<size_t>>&, const size_t)*
- *Template Function bats::normalize_entries*
- *Template Function bats::operator<*
- *Template Function bats::operator<<*
- *Template Function bats::OscillatingRipsZigzagSets*
- *Template Function bats::pairwise_dist*
- *Template Function bats::partial_reduce_parallel(ColumnMatrix<TVec>&, const size_t)*
- *Template Function bats::partial_reduce_parallel(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t)*
- *Template Function bats::pass_L_left*
- *Template Function bats::pass_P_left*
- *Template Function bats::pass_P_right*
- *Template Function bats::pass_PL_left*
- *Template Function bats::pass_U_right*
- *Template Function bats::pass_UP_right*
- *Function bats::perm_to_the_end(const size_t&, const size_t&)*
- *Function bats::perm_to_the_end(const std::vector<size_t>&, const size_t&)*
- *Template Function bats::print_ID_vectors*
- *Template Function bats::print_2D_vectors*
- *Template Function bats::print_filtration_info*
- *Template Function bats::print_simplex*
- *Template Function bats::print_summary_of_filtration*
- *Function bats::prod_ind*
- *Template Function bats::product_paths(CpxT&, iT, const iT, iT, const iT, std::vector<size_t>&, const size_t)*
- *Template Function bats::product_paths(CpxT&, iT, const iT, iT, const iT, std::vector<size_t>&, const size_t, std::vector<cell_ind>&)*

- *Template Function bats::product_space*
- *Template Function bats::random_landmarks*
- *Template Function bats::read_point_cloud*
- *Template Function bats::Reduce(const Filtration<FT, CpxT>&, T, Args ...)*
- *Template Function bats::Reduce(const FilteredChainComplex<T, MT>&, Args ...)*
- *Template Function bats::Reduce(const CpxT&, T, Args ...)*
- *Template Function bats::Reduce(const ChainComplex<MT>&, Args ...)*
- *Template Function bats::reduce_block_dq(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, const size_t, const size_t)*
- *Template Function bats::reduce_block_dq(ColumnMatrix<TVec>&, const size_t, const size_t, const size_t, const size_t)*
- *Template Function bats::reduce_block_sequential(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, const size_t)*
- *Template Function bats::reduce_block_sequential(ColumnMatrix<TVec>&, const size_t, const size_t)*
- *Template Function bats::reduce_column_extra*
- *Template Function bats::reduce_column_sparsify*
- *Template Function bats::reduce_column_standard(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, std::unordered_map<size_t, size_t>&, typename TVec::tmp_type&)*
- *Template Function bats::reduce_column_standard(ColumnMatrix<TVec>&, const size_t, std::unordered_map<size_t, size_t>&, typename TVec::tmp_type&)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, divide_conquer_flag)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, divide_conquer_flag)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, bats::standard_reduction_flag)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, bats::extra_reduction_flag)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, bats::standard_reduction_flag)*
- *Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, bats::extra_reduction_flag)*
- *Template Function bats::reduce_matrix_clearing*
- *Template Function bats::reduce_matrix_compression(ColumnMatrix<TVec>&, const std::vector<bool>&, flag)*
- *Template Function bats::reduce_matrix_compression(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const std::vector<bool>&, flag)*
- *Template Function bats::reduce_matrix_extra(ColumnMatrix<TVec>&)*
- *Template Function bats::reduce_matrix_extra(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)*
- *Template Function bats::reduce_matrix_standard(ColumnMatrix<TVec>&)*

- *Template Function bats::reduce_matrix_standard(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)*
- *Template Function bats::remove_extra_cycles*
- *Template Function bats::Rips(const Diagram<std::set<size_t>, std::vector<size_t>>&, const DataSet<T>&, const M&, const T, const size_t)*
- *Template Function bats::Rips(const Diagram<std::set<size_t>, std::vector<size_t>>&, const DataSet<T>&, const M&, const std::vector<T>&, const size_t)*
- *Template Function bats::rips_edges(std::vector<T>&, std::vector<size_t>&, std::vector<T>&)*
- *Template Function bats::rips_edges(const DataSet<T>&, const M&, const T)*
- *Template Function bats::rips_edges(const Matrix<T>&, const T)*
- *Template Function bats::rips_filtration_edges(const DataSet<T>&, const M&, const T)*
- *Template Function bats::rips_filtration_edges(const Matrix<T>&, const T)*
- *Template Function bats::rips_filtration_edges(const DataSet<T>&, const bats::Cover&, const M&, const T)*
- *Template Function bats::RipsComplex(const DataSet<T>&, const M&, T, size_t)*
- *Template Function bats::RipsComplex(const Matrix<T>&, T, size_t)*
- *Template Function bats::RipsFiltration(const DataSet<T>&, const M&, T, size_t)*
- *Template Function bats::RipsFiltration(const Matrix<T>&, T, size_t)*
- *Template Function bats::RipsFiltration(const DataSet<T>&, const bats::Cover&, const M&, T, size_t)*
- *Template Function bats::RipsFiltration_extension(const DataSet<T>&, const M&, T, size_t)*
- *Template Function bats::RipsFiltration_extension(const Matrix<T>&, T, size_t)*
- *Template Function bats::RipsHom*
- *Template Function bats::sample_cube(const size_t, const size_t)*
- *Template Function bats::sample_cube(const size_t, const size_t, unsigned)*
- *Template Function bats::sample_sphere*
- *Function bats::serpinski_diagram*
- *Template Function bats::SimplicialMap(const CpxT&, const CpxT&)*
- *Template Function bats::SimplicialMap(const CpxT&, const CpxT&, const std::vector<size_t>&)*
- *Template Function bats::sort_edges*
- *Template Function bats::sort_indexes*
- *Template Function bats::sparsify_basis(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, std::map<F, size_t>&, typename TVec::tmp_type&)*
- *Template Function bats::sparsify_basis(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)*
- *Template Function bats::StrictWitnessComplex*
- *Template Function bats::test_reduce_result*
- *Template Function bats::TriangulatedProduct(const CpxT&, const CpxT&, const size_t, const size_t)*
- *Template Function bats::TriangulatedProduct(const CpxT&, const CpxT&, const CpxT&)*
- *Template Function bats::TriangulatedProduct(const CpxT&, const CpxT&, const size_t)*
- *Template Function bats::type_A_dq_common*

Basic Applied Topology Subprograms

- *Template Function bats::type_A_dq_EL*
- *Template Function bats::type_A_dq_EU*
- *Template Function bats::type_A_leftright_sweep1*
- *Template Function bats::type_A_leftright_sweep2*
- *Template Function bats::type_A_rightleft_sweep1*
- *Template Function bats::type_A_rightleft_sweep2*
- *Template Function bats::uniform_interval_cover*
- *Template Function bats::vertex_inclusion_map*
- *Template Function bats::witness_edge_param*
- *Template Function bats::witness_edges(const DataSet<T>&, const DataSet<T>&, const M&)*
- *Template Function bats::witness_edges(const DataSet<T>&, const DataSet<T>&, const M&, const T)*
- *Template Function bats::witness_neighborhoods*
- *Template Function bats::WitnessComplex(const DataSet<T>&, const DataSet<T>&, const M&, const size_t)*
- *Template Function bats::WitnessComplex(const DataSet<T>&, const DataSet<T>&, const M&, const size_t, const T, const size_t)*
- *Template Function bats::WitnessFiltration*
- *Template Function bats::zigzag_levelsets*
- *Template Function bats::zigzag_toplex*

TypeDefs

- *Typedef bats::Cover*
- *Typedef bats::Matrix*

Variables

- *Variable bats::NO_IND*

Namespace bats::detail

Contents

- *Functions*

Functions

- *Template Function bats::detail::pivot_coeff*

Namespace bats::flags

Contents

- *Classes*

Classes

- *Struct divide_conquer*
- *Struct leftward*
- *Struct rightward*

Namespace bats::future

Contents

- *Classes*
- *Functions*

Classes

- *Struct ColumnMajor*
- *Struct ElementaryPermutation*
- *Template Struct LUFact*
- *Struct RowMajor*
- *Template Struct SimilarityTransform*
- *Class CompositePermutation*
- *Template Class const_strided_iterator*
- *Template Class Matrix*
- *Template Class MatrixView*
- *Class Permutation*
- *Template Class range*
- *Class range::const_iterator*
- *Template Class Span*

- *Template Class strided_iterator*
- *Template Class VectorView*

Functions

- *Template Function bats::future::find_pivot_complete*
- *Template Function bats::future::find_pivot_high(const RandomAccessIterator&, ssize_t, ssize_t)*
- *Template Function bats::future::find_pivot_high(const RandomAccessIterator&, ssize_t)*
- *Template Function bats::future::gemm*
- *Template Function bats::future::gemv(const MT&, const VT&)*
- *Template Function bats::future::gemv(const MT&, const VT1&, VT2&&)*
- *Template Function bats::future::l_residual(const MT&&, I1&&)*
- *Template Function bats::future::l_residual(const MT&, I1&)*
- *Template Function bats::future::l_solve(const MT1&, const MT2&, I1&, I2&)*
- *Template Function bats::future::l_solve(const MT&, I1&, I2&)*
- *Template Function bats::future::LU*
- *Function bats::future::operator<<(std::ostream&, const ElementaryPermutation&)*
- *Function bats::future::operator<<(std::ostream&, const CompositePermutation&)*
- *Template Function bats::future::unit_lower*
- *Template Function bats::future::upper*

Namespace bats::rowmajor

Contents

- *Functions*

Functions

- *Template Function bats::rowmajor::get_idx(T, T, T)*
- *Template Function bats::rowmajor::get_idx(T, T, T, T, T)*

Namespace bats::util

Contents

- *Namespaces*
- *Classes*
- *Functions*

Namespaces

- *Namespace bats::util::io*

Classes

- *Struct SimplexHasher*
- *Class SimplexContainer*

Functions

- *Template Function bats::util::apply_iperm_swap*
- *Template Function bats::util::apply_perm(T , std::vector< $T2$ >&, const std::vector< $size_t$ >&)*
- *Template Function bats::util::apply_perm(T *, const std::vector< $size_t$ >&)*
- *Template Function bats::util::apply_perm(std::vector< T >&, const std::vector< $size_t$ >&)*
- *Template Function bats::util::apply_perm_swap*
- *Function bats::util::fill_partial_sortperm*
- *Template Function bats::util::fill_sortperm(const std::vector< T >&, std::vector< $size_t$ >&)*
- *Template Function bats::util::fill_sortperm(const T &, const T &, std::vector< $size_t$ >&)*
- *Template Function bats::util::find_sorted_lt*
- *Template Function bats::util::firstk*
- *Template Function bats::util::has_intersect_sorted*
- *Template Function bats::util::has_intersect_sorted_lt*
- *Template Function bats::util::intersect_sorted(const $C1$ &, const $C2$ &, std::vector< T >&)*
- *Template Function bats::util::intersect_sorted(const $C1$ &, const $C2$ &, std::set< T >&)*
- *Template Function bats::util::intersect_sorted_lt*
- *Function bats::util::inv_perm*
- *Template Function bats::util::is_degenerate*
- *Function bats::util::partial_perm*
- *Template Function bats::util::perm_inversions*

- *Template Function bats::util::perm_sign*
- *Function bats::util::rand_perm*
- *Function bats::util::random_subset*
- *Template Function bats::util::read_simplex*
- *Template Function bats::util::set_intersection*
- *Template Function bats::util::set_union*
- *Template Function bats::util::simplex_sign*
- *Function bats::util::sort_ind_by_perm*
- *Function bats::util::sort_ind_pair_by_perm*
- *Template Function bats::util::sort_into*
- *Template Function bats::util::sort_sum_reduce*
- *Template Function bats::util::sorted_complement*
- *Template Function bats::util::sortperm(const std::vector<T>&)*
- *Template Function bats::util::sortperm(const TI&, const TI&)*
- *Template Function bats::util::sortperm(RAI, RAI, Compare)*
- *Template Function bats::util::sortperm(const size_t, const size_t, Compare)*
- *Template Function bats::util::stable_sortperm*
- *Template Function bats::util::to_set*
- *Template Function bats::util::top_k*
- *Template Function bats::util::top_p*
- *Template Function bats::util::write_simplex(IO&, std::vector<T>&)*
- *Template Function bats::util::write_simplex(IO&, TI&&, TI&&)*

Namespace bats::util::io

Contents

- *Functions*

Functions

- *Template Function bats::util::io::parse_argv(const int, char **, const std::string&&, const T)*
- *Function bats::util::io::parse_argv(const int, char **, const std::string&&, const std::string)*

Namespace bats::zigzag

Contents

- *Namespaces*
- *Classes*
- *Functions*

Namespaces

- *Namespace bats::zigzag::detail*

Classes

- *Template Struct rfilt_val*
- *Template Struct ZigzagChainComplex*
- *Template Struct ZigzagPair*
- *Template Class ZigzagFiltration*

Functions

- *Template Function bats::zigzag::barcode*
- *Template Function bats::zigzag::extend_levelset*
- *Template Function bats::zigzag::extend_zigzag_filtration(const std::vector<T>&, const CubicalComplex&, const T, const size_t)*
- *Template Function bats::zigzag::extend_zigzag_filtration(const std::vector<T>&, const CpxT&, const T)*
- *Template Function bats::zigzag::extra_col_reduction*
- *Template Function bats::zigzag::prepare_ChainComplex(const ZigzagFiltration<CpxT, T>&, FT)*
- *Template Function bats::zigzag::prepare_ChainComplex(const ZigzagFiltration<bats::SimplicialComplex, T>&, FT)*
- *Template Function bats::zigzag::reduce_column(size_t, ColumnMatrix<VecT>&, ColumnMatrix<VecT>&, std::vector<size_t>&, typename VecT::tmp_type&, bats::extra_reduction_flag)*
- *Template Function bats::zigzag::reduce_column(size_t, ColumnMatrix<VecT>&, ColumnMatrix<VecT>&, std::vector<size_t>&, typename VecT::tmp_type&, reduction_flag)*
- *Template Function bats::zigzag::zigzag_barcode_reduction*

Namespace bats::zigzag::detail

Contents

- *Functions*

Functions

- *Template Function bats::zigzag::detail::apply_basis*
- *Template Function bats::zigzag::detail::boundary_insertion_map*
- *Template Function bats::zigzag::detail::cube_extrema*
- *Template Function bats::zigzag::detail::cube_val*
- *Template Function bats::zigzag::detail::cycle_insertion_map*
- *Function bats::zigzag::detail::lex_cmp*
- *Function bats::zigzag::detail::rlex_cmp*
- *Template Function bats::zigzag::detail::simplex_extrema*
- *Template Function bats::zigzag::detail::update_bars*

Classes and Structs

Template Struct A

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Type

- `public MAT` (*Struct MAT*)

Derived Types

- `public E< Impl >` (*Template Struct E*)
- `public T< Impl >` (*Template Struct T*)

Struct Documentation

```
template<typename Impl>
struct A : public MAT
    Subclassed by E< Impl >, T< Impl >
```

Template Struct AbstractMetric

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Struct Documentation

```
template<class D>
struct bats::AbstractMetric
```

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const

template<typename T>
inline T operator()(const VectorView<T> &x, const VectorView<T> &y) const

template<typename T>
inline std::vector<T> operator()(const VectorView<T> &x, const DataSet<T> &X) const

template<typename T>
inline Matrix<T> operator()(const DataSet<T> &X, const DataSet<T> &Y) const

template<typename T>
inline Matrix<T> operator()(const DataSet<T> &X) const
```

Struct AngleDist

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Inheritance Relationships

Base Type

- public bats::AbstractMetric< AngleDist > (*Template Struct AbstractMetric*)

Struct Documentation

struct bats::AngleDist : public bats::AbstractMetric<AngleDist>

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const
```

Struct apparent_pairs_flag

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

struct apparent_pairs_flag

Struct bar

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Struct Documentation

struct bats::bar

Public Functions

```
inline bar()
```

```
inline bar(size_t s, size_t si, size_t t, size_t ti)
```

Public Members

```
size_t start
size_t start_ind
size_t end
size_t end_ind
```

Template Struct ChainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_chain_complex.hpp

Struct Documentation

```
template<typename MT>
struct bats::ChainComplex
```

Public Functions

```
inline ChainComplex()
```

```
inline ChainComplex(size_t maxd)
```

```
inline ChainComplex(const std::vector<MT> &boundary)
```

```
template<typename CpxT>
inline ChainComplex(const CpxT &X)
```

```
template<typename CpxT>
inline ChainComplex(const CpxT &X, const CpxT &A)
```

```
inline size_t maxdim() const
```

```
inline size_t dim(size_t k) const
```

```
inline size_t dim() const
```

```
inline bool is_valid_complex() const
```

```
inline ChainComplex subcomplex(std::vector<std::vector<size_t>> &inds) const
```

```
inline ChainComplex relative_complex(std::vector<std::vector<size_t>> &inds) const
```

```
inline MT &operator[](size_t k)
    reference to k-dimensional boundary

Parameters k – dimension

inline const MT &operator[](size_t k) const

inline void permute_basis(size_t k, const std::vector<size_t> &perm)

inline void permute_basis(const std::vector<std::vector<size_t>> &perm)

inline void ipermute_basis(size_t k, const std::vector<size_t> &perm)

inline void ipermute_basis(const std::vector<std::vector<size_t>> &perm)

template<typename Information_type>
inline void update_basis_general(size_t k, const Information_type &UI)

template<typename Information_type>
inline void update_basis_general(const Information_type &UI_fast)

inline void clear_compress_apparent_pairs()
    A preprocessing step for computing homology using the reduction algorithm.
```

Warning: using this function will invalidate any basis used by a homology algorithm since no basis vector will be obtained for the cleared columns

Public Members

std::vector<*MT*> **boundary**

Friends

```
inline friend friend ChainComplex tensor_product (const ChainComplex &A,
                                                const ChainComplex &B, size_t dmax)

inline friend friend ChainComplex tensor_product (const ChainComplex &A,
                                                const ChainComplex &B)
```

Template Struct ChainMap

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_chain_map.hpp

Struct Documentation

```
template<typename TM>
struct bats::ChainMap
```

Public Functions

```
inline ChainMap()
```

```
inline ChainMap(const std::vector<TM> &map)
```

```
inline ChainMap(size_t d)
```

```
inline ChainMap(const CellularMap &f)
```

```
template<typename CpxT>
```

```
inline ChainMap(const CellularMap &f, const CpxT &X, const CpxT &A, const CpxT &Y, const CpxT &B)
```

```
inline ChainMap relative_map(std::vector<std::vector<size_t>> &inds1, std::vector<std::vector<size_t>>
&inds2) const
```

```
inline size_t maxdim() const
```

```
inline TM &operator[](size_t k)
```

```
inline const TM &operator[](size_t k) const
```

```
inline void permute_row_basis(size_t k, const std::vector<size_t> &p)
```

```
inline void permute_column_basis(size_t k, const std::vector<size_t> &p)
```

Public Members

```
std::vector<TM> map
```

Struct clearing_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

```
struct clearing_flag
```

Template Struct CochainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_cochain_complex.hpp

Struct Documentation

```
template<typename MT>
```

```
struct bats::CochainComplex
```

Public Functions

```
inline CochainComplex()
```

```
inline CochainComplex(const std::vector<size_t> &dim, const std::vector<MT> &coboundary)
```

```
template<typename CpxT>
```

```
inline CochainComplex(const CpxT &X)
```

```
inline size_t maxdim() const
```

```
inline MT &operator[](size_t k)
```

```
inline void permute_basis(size_t k, const std::vector<size_t> &perm)
```

```
inline void permute_basis(const std::vector<std::vector<size_t>> &perm)
```

```
inline void ipermute_basis(size_t k, const std::vector<size_t> &perm)
```

Public Members

```
std::vector<size_t> dim  
std::vector<MT> coboundary
```

Struct compression_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

```
struct compression_flag
```

Struct compute_basis_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_basis.hpp

Struct Documentation

```
struct compute_basis_flag
```

Struct CosineDist

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Inheritance Relationships

Base Type

- public bats::AbstractMetric< CosineDist > (*Template Struct AbstractMetric*)

Struct Documentation

```
struct bats::CosineDist : public bats::AbstractMetric<CosineDist>
```

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const
```

Template Struct DataSet

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data.hpp

Struct Documentation

```
template<typename T>
struct bats::DataSet
```

Public Functions

```
inline DataSet()
```

```
inline DataSet(const Matrix<T> &d)
```

```
inline size_t size() const
```

```
inline size_t dim() const
```

```
inline Matrix<T> &get_data()
```

```
template<typename TI>
```

```
inline DataSet operator[](const TI &inds) const
```

```
inline VectorView<T> operator[](const int i)
```

```
inline const VectorView<T> operator[](const int i) const
```

```
inline VectorView<T> operator[](const size_t i)
```

```
inline const VectorView<T> operator[](const size_t i) const
```

```
inline T &operator()(const size_t i, const size_t j)
```

```
inline const T &operator()(const size_t i, const size_t j) const
```

Public Members

Matrix<*T*> **data**

Template Struct **DGLinearMap**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_dgvs_dgmap.hpp

Struct Documentation

template<typename **TM**>

struct **bats**::**DGLinearMap**

A class for a map between two DGVectorSpaces

The map should be between DGVectorspaces of the same degree and the map should commute with the differential.

If the DGVectorspaces are augmented, the map should be augmentation preserving.

Public Functions

inline **DGLinearMap**()

inline **DGLinearMap**(const std::vector<*TM*> &map)

inline **DGLinearMap**(size_t d)

inline **DGLinearMap**(const *CellularMap* &f, int deg = -1)

inline ssize_t **maxdim**() const

inline *TM* &**operator[]**(ssize_t k)

inline const *TM* &**operator[]**(ssize_t k) const

inline void **permute_row_basis**(ssize_t k, const std::vector<size_t> &p)

inline void **permute_column_basis**(ssize_t k, const std::vector<size_t> &p)

Public Members

std::vector<*TM*> **map**

Template Struct DGVectorSpace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_dgvs_dgvs.hpp

Struct Documentation

template<typename **MT**>

struct **bats** : **DGVectorSpace**

a class for a differential graded vector space.

This encapsulates both chain and cochain complex constructions

degree is the degree of the differential: -1 for chain complexes (default) +1 for cochain complexes

differential holds the differential maps

We store maps starting on the edge (-1,0) (-1) (0) (1) (2) ... This map is 0 in the case of standard chain/cochain complexes but can be non-zero for augmented chain/cochain complexes

TODO: need to handle +1 boundary in maxdim

Public Functions

inline *MT* &**operator[]**(ssize_t k)

Access maps in various dimensions

if degree is +1 (cohomological type), then lowest map index is -1 -[-1]-> * -[0]-> * -[1]-> ...

if degree is -1 (homological type) then lowest map index is 0 <-[0]- * <-[1]- * <-[2]- ...

inline const *MT* &**operator[]**(ssize_t k) const

inline **DGVectorSpace**()

inline **DGVectorSpace**(size_t maxd, int deg = -1)

Construct a DGVector space with maxd dimensions

inline **DGVectorSpace**(const std::vector<*MT*> &diff, int deg = -1)

Construct a DGVector space explicitly from differentials

template<typename **CpxT**>

inline **DGVectorSpace**(const *CpxT* &X, const int deg = -1, const bool augmented = false)

inline ssize_t **maxdim**() const

inline size_t **dim**(ssize_t k) const

Public Members

```
int degree
std::vector<MT> differential
```

Struct Diagram::Edge

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_diagram.hpp

Nested Relationships

This struct is a nested type of *Template Class Diagram*.

Struct Documentation

```
struct bats::Diagram::Edge
```

Public Functions

```
inline Edge()
inline Edge(size_t s, size_t t)
```

Public Members

```
size_t src
size_t targ
```

Struct divide_conquer_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Struct Documentation

```
struct divide_conquer_flag
```

Struct Euclidean

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Inheritance Relationships

Base Type

- public bats::AbstractMetric< Euclidean > (*Template Struct AbstractMetric*)

Struct Documentation

```
struct bats::Euclidean : public bats::AbstractMetric<Euclidean>
```

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const
```

Struct extra_reduction_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

```
struct extra_reduction_flag
```

Template Struct filtered_edge

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Struct Documentation

```
template<typename T>
struct bats::filtered_edge
```

Public Functions

```
inline filtered_edge()  
  
inline filtered_edge(const size_t &s, const size_t &t, const T &r)  
  
inline bool operator<(const filtered_edge &other) const
```

Public Members

```
size_t s  
size_t t  
T r
```

Template Struct FilteredChainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_filtered_chain_complex.h

Struct Documentation

```
template<typename FT, typename MT>  
struct bats::FilteredChainComplex
```

Public Functions

```
inline FilteredChainComplex()  
  
template<typename CpxT>  
inline FilteredChainComplex(const Filtration<FT, CpxT> &F)  
  
inline size_t dim(const size_t k)  
  
inline const ChainComplex<MT> &complex() const  
  
inline const std::vector<std::vector<FT>> &vals() const  
  
inline void update_filtration(const std::vector<std::vector<FT>> newval)  
  
template<typename I>  
inline void update_filtration_general(const I &updating_information)
```

Public Members

```
std::vector<std::vector<FT>> val
ChainComplex<MT> C
std::vector<std::vector<size_t>> perm
```

Template Struct *FilteredCochainComplex*

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_filtered_cochain_complex.h

Struct Documentation

```
template<typename FT, typename MT>
struct bats::FilteredCochainComplex
```

Public Functions

```
inline FilteredCochainComplex()
template<typename CpxT>
inline FilteredCochainComplex(const Filtration<FT, CpxT> &F)

inline size_t dim(const size_t k)

inline const CochainComplex<MT> &complex() const

inline const std::vector<std::vector<FT>> &vals() const

inline void update_filtration(const std::vector<std::vector<FT>> newval)

template<typename I>
inline void update_filtration_general(const I &updating_information)
```

Public Members

```
std::vector<std::vector<FT>> val
CochainComplex<MT> C
std::vector<std::vector<size_t>> perm
```

Struct divide_conquer

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Struct Documentation

```
struct divide_conquer
    Flag to choose a divide and conquer algorithm
```

Struct leftward

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Struct Documentation

```
struct leftward
    Flag to choose leftward algorithm
```

Struct rightward

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Struct Documentation

```
struct rightward
    Flag to choose rightward algorithm
```

Struct ColumnMajor

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Struct Documentation

```
struct ColumnMajor
```

Struct ElementaryPermutation

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_permutation.hpp

Struct Documentation

```
struct bats::future::ElementaryPermutation
```

Public Functions

```
inline ElementaryPermutation()
```

```
inline ElementaryPermutation(size_t i, size_t j)
```

```
template<typename T>
inline T &operator()(T &a) const
```

```
template<typename T>
inline T &operator()(T &&a) const
```

```
inline CompositePermutation &operator()(CompositePermutation &a) const
```

Public Members

```
size_t i
```

```
size_t j
```

Friends

```
friend std::ostream & operator<< (std::ostream &os,
const ElementaryPermutation &p)
```

Template Struct LUFact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Struct Documentation

```
template<typename MT>
struct bats::future::LUFact
```

Public Types

```
using val_type = typename MT::value_type
```

Public Functions

```
inline LUFact(MT &&P, MT &&L, MT &&U, MT &&Q)
```

```
inline MT prod() const
```

```
inline void print_info() const
```

```
inline void print() const
```

Public Members

```
MT P
```

```
MT L
```

```
MT U
```

```
MT Q
```

Struct RowMajor

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Struct Documentation

```
struct RowMajor
```

Template Struct SimilarityTransform

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_similarity.hpp

Struct Documentation

```
template<typename T>
struct bats::future::SimilarityTransform
```

Public Functions

```
inline SimilarityTransform(const Matrix<T> &A0)
```

```
inline size_t size() const
```

```
inline T operator()(size_t i, size_t j) const
```

```
inline void print_info() const
```

```
inline void print() const
```

```
inline Matrix<T> prod() const
```

```
inline void swap_rows(size_t i0, size_t i1)
```

```
inline void swap_columns(size_t j0, size_t j1)
```

```
inline void add_row(T a, size_t i1, size_t i0)
```

```
inline void scale_row(T a, size_t i)
```

```
inline void scale_column(T a, size_t i)
```

Public Members

```
Matrix<T> S
```

```
Matrix<T> A
```

```
Matrix<T> Sinv
```

Struct L1Dist

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Inheritance Relationships

Base Type

- `public bats::AbstractMetric< L1Dist >` (*Template Struct AbstractMetric*)

Struct Documentation

```
struct bats::L1Dist : public bats::AbstractMetric<L1Dist>
```

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const
```

Struct LightSimplicialComplex::simplex_boundary_iterator

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_light_simplicial_complex.hpp

Nested Relationships

This struct is a nested type of *Template Class LightSimplicialComplex*.

Struct Documentation

```
struct bats::LightSimplicialComplex::simplex_boundary_iterator
```

Public Functions

```
inline simplex_boundary_iterator(index_type s, size_t dim, const LightSimplicialComplex *p)

inline simplex_boundary_iterator(index_type s, size_t dim, const LightSimplicialComplex *p, int i)

inline simplex_boundary_iterator(int i)

inline std::tuple<index_type, int> next()
```

Basic Applied Topology Subprograms

```
inline index_type operator*() const  
  
inline simplex_boundary_iterator &operator++()  
  
inline simplex_boundary_iterator &operator--()  
  
inline bool operator!=(const simplex_boundary_iterator &other)  
  
inline bool operator==(const simplex_boundary_iterator &other)  
  
inline operator bool() const
```

Public Members

```
const LightSimplicialComplex *p  
size_t dim  
int c  
int i  
index_type before  
index_type after
```

Struct LInfDist

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Inheritance Relationships

Base Type

- public bats::AbstractMetric< LInfDist > (*Template Struct AbstractMetric*)

Struct Documentation

```
struct bats::LInfDist : public bats::AbstractMetric<LInfDist>
```

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const
```

Struct no_apparent_pairs_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

```
struct no_apparent_pairs_flag
```

Struct no_optimization_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

```
struct no_optimization_flag
```

Template Struct PersistencePair

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_barcode.hpp

Struct Documentation

```
template<typename T>
struct bats::PersistencePair
```

Public Functions

```
inline PersistencePair()
```

```
inline PersistencePair(const size_t dim, const size_t birth_ind, const size_t death_ind, const T birth, const  
  T death)
```

```
inline bool operator==(const PersistencePair &other) const
```

```
inline bool operator!=(const PersistencePair &other) const
```

```
inline size_t get_dim() const  
  
inline size_t get_birth_ind() const  
  
inline size_t get_death_ind() const  
  
inline T get_birth() const  
  
inline T get_death() const  
  
inline T length() const  
  
inline T mid() const  
  
inline std::string str()
```

Public Members

```
size_t dim  
size_t birth_ind  
size_t death_ind  
T birth  
T death
```

Template Struct ReducedDGVectorSpace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_dgbasis.hpp

Struct Documentation

```
template<typename MT>  
struct bats::ReducedDGVectorSpace
```

Public Types

```
using vect_type = typename MT::col_type
```

Public Functions

```
inline size_t hdim(size_t k) const
```

```
inline size_t betti(size_t k) const
```

```
inline size_t maxdim() const
```

```
inline size_t dim(size_t k) const
```

```
inline MT &operator[](size_t k)
```

```
inline void initialize(const DGVectorSpace<MT> &C)
    initialize with chain complex C, but do not do reduction
```

```
inline void set_indices()
```

```
inline ReducedDGVectorSpace()
```

```
inline ReducedDGVectorSpace(const DGVectorSpace<MT> &C)
```

```
template<typename TV>
```

```
inline TV to_hom_basis(const TV &v, size_t k) const
    put vector/matrix in homology-revealing basis in dimension k
```

```
template<typename TV>
```

```
inline TV from_hom_basis(const TV &v, size_t k) const
    put vector/matrix back in original basis in dimension k
```

```
inline vect_type get_preferredRepresentative(const size_t j, const size_t k) const
```

```
inline void find_preferredRepresentative(vect_type &y, size_t k) const
```

```
inline vect_type chain_preferredRepresentative(const vect_type &c, size_t k) const
```

```
inline void print_summary(bool print_nnz = false) const
```

Public Members

```
int degree
std::vector<MT> U
std::vector<MT> R
std::vector<std::vector<size_t>> I
std::vector<std::vector<size_t>> p2c
```

Template Struct ReducedFilteredChainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtered_basis.h

Struct Documentation

```
template<typename T, typename MT>
struct bats::ReducedFilteredChainComplex
```

Public Functions

```
inline ReducedFilteredChainComplex()
```

```
template<typename ...Args>
inline ReducedFilteredChainComplex(const FilteredChainComplex<T, MT> &C, Args... args)
```

```
inline size_t maxdim() const
```

```
inline size_t dim(const size_t k) const
```

```
inline size_t hdim(const size_t k) const
```

```
inline std::vector<PersistencePair<T>> persistence_pairs(const size_t k, const bool permuted = false)
                                         const
                                         persistence pairs in dimension k
```

Parameters

- k** – homology dimension
- permuted** – set to true to return critical indices permuted by filtration parameter set to false to return with indices in original order. Default: false

```
inline auto representative(const PersistencePair<T> &p, const bool permuted = false) const
                           returns representative for homology class corresponding to persistence pair
```

if permuted is false, it is assumed the birth index is also not in permutation order.

Parameters

- **p** – persistence pair obtained from persistence_pairs
- **permuted** – set to true to return indices permuted by filtration parameter set to false to return with indices in original order. Default: false

```

std::vector<T> barcode(const size_t k)

std::vector<size_t> critical_cells(const size_t k)

inline void update_filtration(const std::vector<std::vector<T>> newval)

template<typename Information_type, typename ...Args>
inline void update_filtration_general(const Information_type &updating_information, Args... args)

inline std::vector<size_t> get_nnz_U()

inline std::vector<size_t> get_nnz_R()

inline void sparsify_basis()
    greedily introduce sparsity into basis

inline void remove_extra_cycles()
    remove extra cycles from U[k]

ReducedFilteredChainComplex get_subcomplex() const

inline void print_summary(bool print_nnz = false) const

```

Public Members

```

ReducedChainComplex<MT> RC

std::vector<std::vector<T>> val

std::vector<std::vector<size_t>> perm

```

Struct RPAngleDist

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Inheritance Relationships

Base Type

- public bats::AbstractMetric< RPAngleDist > (*Template Struct AbstractMetric*)

Struct Documentation

struct bats::RPAngleDist : public bats::AbstractMetric<RPAngleDist>

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const
```

Struct RPCosineDist

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Inheritance Relationships

Base Type

- public bats::AbstractMetric< CosineDist > (*Template Struct AbstractMetric*)

Struct Documentation

struct bats::RPCosineDist : public bats::AbstractMetric<CosineDist>

Public Functions

```
template<typename T>
inline T dist(const VectorView<T> &x, const VectorView<T> &y) const
```

Struct sparse_reduction_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

```
struct sparse_reduction_flag
```

Struct standard_reduction_flag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Struct Documentation

```
struct standard_reduction_flag
```

Template Struct tedge

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Struct Documentation

```
template<typename TF, typename TI>
```

```
struct bats::tedge
```

Public Functions

```
inline tedge()
```

```
inline tedge(TF v, TI s, TI t)
```

Public Members

```
TF v
```

```
TI s
```

```
TI t
```

Struct triangle

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_extras.hpp

Struct Documentation

```
struct bats::triangle
```

Public Functions

```
inline triangle()
```

```
inline triangle(size_t a, size_t b, size_t c)
```

Public Members

```
size_t a
```

```
size_t b
```

```
size_t c
```

```
size_t ab
```

```
size_t bc
```

```
size_t ca
```

Template Struct Update_info

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_update_information.hpp

Struct Documentation

```
template<class FiltrationType>
```

```
struct bats::Update_info
```

Public Functions

```
inline Update_info(const FiltrationType &F_X, const FiltrationType &F_Y)
```

```
inline void filtered_info(const std::vector<std::vector<size_t>> &perms_X)
```

```
inline std::vector<size_t> permutation_deletion_end(size_t i)
```

```
inline void print_summary()  
  
inline void print_detail()
```

Public Members

```
std::vector<std::vector<size_t>> addition_indices  
std::vector<std::vector<std::vector<size_t>>> boundary_indices  
std::vector<std::vector<size_t>> deletion_indices  
std::vector<std::vector<size_t>> permutations  
std::vector<std::vector<size_t>> intersection_indices_Y  
std::vector<std::vector<size_t>> intersection_indices_X  
size_t max_dim  
std::vector<std::vector<double>> F_X_vals  
std::vector<std::vector<size_t>> F_X_perms  
std::vector<std::vector<size_t>> perms_X_inv  
std::vector<std::vector<double>> F_Y_vals  
std::vector<std::vector<size_t>> F_Y_perms  
std::vector<std::vector<size_t>> perms_Y_inv  
FiltrationType F_old  
FiltrationType F_new  
bool filtered_boolean = false
```

Struct SimplexHasher

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_simplex.hpp

Struct Documentation

```
struct bats::util::SimplexHasher
```

Public Functions

```
inline std::size_t operator()(const std::vector<size_t> &k) const
```

Template Struct `rfilt_val`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Struct Documentation

```
template<typename T>
struct bats::zigzag::rfilt_val
    A struct that packages information about entries and exits in a right filtration
```

Public Functions

```
inline rfilt_val()
```

```
inline rfilt_val(size_t dim, size_t ind, size_t cind, T val, bool entry)
```

Public Members

```
size_t dim
```

```
size_t ind
```

```
size_t cind
```

```
T val
```

```
bool entry
```

Friends

```
inline friend friend std::ostream &operator<< (std::ostream &os,
const rfilt_val &v)
```

Template Struct ZigzagChainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_zigzag_filtration.hpp

Struct Documentation

```
template<typename MT, typename T = double>
struct bats::zigzag::ZigzagChainComplex
    A class that wraps a chain complex with a zigzag filtration.
```

A class that wraps a chain complex with a zigzag filtration. Unlike a Zigzag filtration, every chain has a unique entry and removal time.

Public Functions

```
inline void _correct_indices(size_t k, size_t j, const std::vector<std::vector<size_t>> extra_cells)
    correct the indices in column j in dimension k
    assumes column j hasn't already been corrected assumes val[k][j] has been set, as well as val[k-1] extra_cells
    maps to duplicate cells

inline ZigzagChainComplex()
```

```
template<typename CpxT>
inline ZigzagChainComplex(const ZigzagFiltration<CpxT, T> &X)
    Construct a zigzag chain complex from a zigzag filtration
    constructs a distinct column for every time a cell enters

inline size_t maxdim() const
    return maximum dimension of cells

inline size_t dim(const size_t k) const
    return number of cells in specified dimension
```

Parameters **dim** – dimension

```
inline size_t dim() const
```

```
inline const std::vector<std::vector<std::pair<T, T>>> &vals() const
    return const reference to right filtration values

inline const std::vector<std::pair<T, T>> &vals(const size_t k) const
    return const reference to right filtration values
```

Parameters **k** – dimension of values to return

Public Members

```
ChainComplex<MT> C  
std::vector<std::vector<std::pair<T, T>>> val  
std::vector<std::vector<size_t>> cind
```

Template Struct ZigzagPair

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Struct Documentation

```
template<typename T>  
struct bats::zigzag::ZigzagPair
```

Public Functions

```
inline ZigzagPair()
```

```
inline ZigzagPair(const size_t dim, const size_t birth_ind, const size_t death_ind, const T birth, const T  
death, const bool birth_is_entry, const bool death_is_entry)
```

```
inline bool operator==(const ZigzagPair &other) const
```

```
inline bool operator!=(const ZigzagPair &other) const
```

```
inline size_t get_dim() const
```

```
inline size_t get_birth_ind() const
```

```
inline size_t get_death_ind() const
```

```
inline T get_birth() const
```

```
inline T get_death() const
```

```
inline T length() const
```

```
inline T mid() const
```

```
inline std::string str()
```

Public Members

```
size_t dim  
size_t birth_ind  
size_t death_ind  
T birth  
T death  
bool birth_is_entry  
bool death_is_entry
```

Friends

```
inline friend friend std::ostream & operator<< (std::ostream &os,  
const ZigzagPair &p)
```

Struct cell_ind

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_abstract_complex

Struct Documentation

```
struct cell_ind
```

Public Functions

```
inline cell_ind()
```

```
inline cell_ind(size_t dim, size_t ind)
```

```
inline std::string str()
```

Public Members

```
size_t dim  
size_t ind
```

Template Struct D

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Types

- public E< Impl > (*Template Struct E*)
- public L< Impl > (*Template Struct L*)
- public U< Impl > (*Template Struct U*)

Struct Documentation

```
template<typename Impl>
struct D : public E<Impl>, public L<Impl>, public U<Impl>
```

Template Struct E

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Type

- public A< Impl > (*Template Struct A*)

Derived Types

- public D< Impl > (*Template Struct D*)
- public EL< Impl > (*Template Struct EL*)
- public ELH< Impl > (*Template Struct ELH*)
- public EU< Impl > (*Template Struct EU*)
- public EUH< Impl > (*Template Struct EUH*)
- public P< Impl > (*Template Struct P*)

Struct Documentation

```
template<typename Impl>
struct E : public A<Impl>
    Subclassed by D<Impl>, EL<Impl>, ELH<Impl>, EU<Impl>, EUH<Impl>, P<Impl>
```

Template Struct EL

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Types

- public [*E<Impl>*](#) (*Template Struct E*)
- public [*L<Impl>*](#) (*Template Struct L*)

Struct Documentation

```
template<typename Impl>
struct EL : public E<Impl>, public L<Impl>
```

Template Struct ELH

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Types

- public [*E<Impl>*](#) (*Template Struct E*)
- public [*L<Impl>*](#) (*Template Struct L*)

Struct Documentation

```
template<typename Impl>
struct ELH : public E<Impl>, public L<Impl>
```

Template Struct EU

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Types

- public E< *Impl* > (*Template Struct E*)
- public U< *Impl* > (*Template Struct U*)

Struct Documentation

```
template<typename Impl>
struct EU : public E<Impl>, public U<Impl>
```

Template Struct EUH

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Types

- public E< *Impl* > (*Template Struct E*)
- public U< *Impl* > (*Template Struct U*)

Struct Documentation

```
template<typename Impl>
struct EUH : public E<Impl>, public U<Impl>
```

Template Struct is_UnivariatePolynomial

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_polynomial.hpp

Inheritance Relationships

Base Type

- public false_type

Struct Documentation

```
template<typename T>
struct is_UnivariatePolynomial : public false_type
```

Template Struct **is_UnivariatePolynomial**< *UnivariatePolynomial*< T > >

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_polynomial.hpp

Inheritance Relationships

Base Type

- public true_type

Struct Documentation

```
template<typename T>
struct is_UnivariatePolynomial<UnivariatePolynomial<T>> : public true_type
```

Template Struct L

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Type

- public T< Impl > (*Template Struct T*)

Derived Types

- `public D< Impl >` (*Template Struct D*)
- `public EL< Impl >` (*Template Struct EL*)
- `public ELH< Impl >` (*Template Struct ELH*)

Struct Documentation

```
template<typename Impl>
struct L : public T<Impl>
    Subclassed by D< Impl >, EL< Impl >, ELH< Impl >
```

Struct MAT

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Derived Types

- `public A< Impl >` (*Template Struct A*)
- `public A< T >` (*Template Struct A*)

Struct Documentation

```
struct MAT
    Subclassed by A< Impl >, A< T >
```

Struct MultiGraph::Edge

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_multigraph.hpp

Nested Relationships

This struct is a nested type of *Template Class MultiGraph*.

Struct Documentation

```
struct MultiGraph::Edge
```

Public Functions

```
inline Edge(Node &sin, Node &tin, ET &x)
```

```
inline ET *get_data()
```

```
inline void print()
```

Public Members

```
ET *data
```

```
Node *src
```

```
Node *targ
```

Struct MultiGraph::Node

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_multigraph.hpp

Nested Relationships

This struct is a nested type of *Template Class MultiGraph*.

Struct Documentation

```
struct MultiGraph::Node
```

Public Functions

```
inline Node(NT &x)
```

```
inline Node(NT *x)
```

```
inline void add_input(Edge *in)
```

```
inline void add_output(Edge *out)
```

```
inline NT *get_data()  
  
inline void print()
```

Public Members

```
NT *data  
std::vector<Edge*> input  
std::vector<Edge*> output
```

Template Struct nzpair

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_abstract_vector.hpp

Struct Documentation

```
template<typename TI, typename TV>  
struct nzpair
```

Public Functions

```
inline nzpair()  
  
inline nzpair(const TI ind)  
  
inline nzpair(const TI ind, const TV val)  
  
inline nzpair(std::string &str)  
  
inline bool operator==(const nzpair &other) const  
  
inline bool operator!=(const nzpair &other) const
```

Public Members

TI **ind**

TV **val**

Template Struct P

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Type

- public **E< Impl >** (*Template Struct E*)

Struct Documentation

```
template<typename Impl>
```

```
struct P : public E<Impl>
```

Struct SI

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Struct Documentation

```
struct SI
```

Template Struct SmithFact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_pid.hpp

Struct Documentation

```
template<class TC>
```

```
struct SmithFact
```

Public Functions

inline *ColumnMatrix<TC>* **prod()** const

Public Members

ColumnMatrix<TC> **R**

ColumnMatrix<TC> **S**

ColumnMatrix<TC> **C**

Template Struct SparseFact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Struct Documentation

template<class TC>

struct **SparseFact**

Public Functions

inline *ColumnMatrix<TC>* **LEUP_prod()** const

inline *ColumnMatrix<TC>* **PLEU_prod()** const

inline *ColumnMatrix<TC>* **UELP_prod()** const

inline *ColumnMatrix<TC>* **PUEL_prod()** const

inline *ColumnMatrix<TC>* **LQU_prod()** const

inline *ColumnMatrix<TC>* **UQL_prod()** const

Public Members

ColumnMatrix<TC> **L**

ColumnMatrix<TC> **E**

ColumnMatrix<TC> **U**

ColumnMatrix<TC> **P**

Template Struct T

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Type

- public A< Impl > (*Template Struct A*)

Derived Types

- public L< Impl > (*Template Struct L*)
- public U< Impl > (*Template Struct U*)

Struct Documentation

```
template<typename Impl>
struct T : public A<Impl>
    Subclassed by L<Impl>, U<Impl>
```

Template Struct U

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Inheritance Relationships

Base Type

- public T< Impl > (*Template Struct T*)

Derived Types

- public D< Impl > (*Template Struct D*)
- public EU< Impl > (*Template Struct EU*)
- public EUH< Impl > (*Template Struct EUH*)

Struct Documentation

```
template<typename Impl>
struct U : public T<Impl>
    Subclassed by D<Impl>, EU<Impl>, EUH<Impl>
```

Template Class AbstractField

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_field.hpp

Class Documentation

```
template<class Derived>
class AbstractField
```

Public Functions

```
inline Derived operator+(const Derived &b)
```

```
inline Derived operator-(const Derived &b)
```

```
inline Derived operator-()
```

```
inline Derived operator*(const Derived &b)
```

```
inline Derived operator/(const Derived &b)
```

```
inline Derived inv()
```

```
inline Derived operator==(const Derived &b)
```

```
inline Derived operator==(const int b)
```

```
inline void print()
```

```
inline std::string str()
```

Friends

```
inline friend friend std::ostream & operator<< (std::ostream &os, AbstractField &x)
```

Class AbstractMatrix

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_abstract_matrix.hpp

Inheritance Relationships

Derived Types

- public ColumnMatrix< TC > (*Template Class ColumnMatrix*)
- public CSCMatrix< TV, TI > (*Template Class CSCMatrix*)

Class Documentation

```
class AbstractMatrix
    Subclassed by ColumnMatrix< TC >, CSCMatrix< TV, TI >
```

Template Class BarcodePair

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_barcode.hpp

Class Documentation

```
template<typename T>
class bats::BarcodePair
```

Public Functions

```
inline BarcodePair()
```

```
inline BarcodePair(T b)
```

```
inline BarcodePair(T b, T d)
```

```
inline void print()
```

Public Members

`T birth`

`T death`

Class CellComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_cell_complex.hpp

Class Documentation

```
class bats::CellComplex
```

Public Functions

inline `CellComplex()`

inline `CellComplex(size_t maxdim)`

inline `size_t maxdim() const`

inline `size_t ncells(size_t k) const`

inline `size_t ncells() const`

inline `size_t add(const std::vector<size_t> &b, const std::vector<int> &c, size_t k)`

inline `size_t add_vertex()`

inline `size_t add_vertices(size_t k)`

inline `CSCMatrix<int, size_t> boundary_csc(size_t dim) const`

inline `ColumnMatrix<SparseVector<int, size_t>> boundary(size_t dim)`

void `boundary(size_t k, std::vector<size_t> row, std::vector<size_t> col)`

Class CellularMap

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_cell_map.hpp

Class Documentation

```
class bats::CellularMap
```

Public Functions

```
inline CellularMap()
```

```
inline CellularMap(size_t dim)
```

```
inline CellularMap(std::string &fname)
```

```
template<typename CpxT>
```

```
inline CellularMap(const CpxT &X, const CpxT &Y)  
    Construct inclusion map
```

Should work for both *SimplicialComplex* and *CubicalComplex*

```
inline size_t maxdim() const
```

```
inline map_type &operator[](size_t k)
```

```
inline const map_type &operator[](size_t k) const
```

```
inline void save(std::string &fname) const
```

Public Static Functions

```
template<typename CpxT>
```

```
static inline CellularMap identity(const CpxT &X)
```

Class CubicalComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_cubical_complex.hpp

Class Documentation

```
class bats::CubicalComplex
```

Public Functions

```
inline CubicalComplex()
```

```
inline CubicalComplex(size_t maxdim)
```

```
inline CubicalComplex(size_t n, size_t maxdim)
```

```
inline size_t find_idx(const std::vector<size_t> &s)
```

```
inline size_t find_idx(const std::vector<size_t> &s) const
```

```
inline size_t maxdim() const
```

```
inline size_t ncells(const size_t k) const
```

```
inline size_t ncells() const
```

```
inline void set_dimension(size_t maxdim)
```

```
inline void print_summary() const
```

```
inline cell_ind add(std::vector<size_t> &s)
```

```
inline cell_ind add(std::vector<size_t> &&s)
```

```
inline std::vector<cell_ind> add_recursive(const std::vector<size_t> &s)
```

```
inline std::vector<cell_ind> add_recursive(const std::vector<size_t> &&s)
```

```
inline auto faces_begin(const size_t dim, const size_t i) const
```

```
inline auto faces_begin(const cell_ind &ci) const
```

```
inline auto faces_end(const size_t dim, const size_t i) const
```

```
inline auto faces_end(const cell_ind &ci) const
```

```
inline auto cell_begin(const size_t dim, const size_t i) const  
  
inline auto cell_end(const size_t dim, const size_t i) const  
  
inline void get_cube(size_t dim, size_t i, std::vector<size_t> &s) const  
  
inline std::vector<size_t> get_cube(size_t dim, size_t i) const  
  
inline auto get_cell(size_t dim, size_t i, std::vector<size_t> &s) const  
  
inline auto get_cell(size_t dim, size_t i) const  
  
inline std::vector<std::vector<size_t>> get_cubes(const size_t dim) const  
  
inline CubicalComplex skeleton(const size_t k) const  
  
inline std::vector<std::vector<size_t>> get_cubes() const  
  
inline CSCMatrix<int, size_t> boundary_csc(const size_t dim) const  
  
inline void load_cubes(std::string &fname)
```

Public Static Functions

```
static inline CubicalComplex generate_cube(const size_t n)  
    generate a discretized cube on n^3 vertices
```

Parameters **n** – number of vertex locations along each dimension

Template Class Diagram

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_diagram.hpp

Nested Relationships

Nested Types

- Struct Diagram::Edge*

Class Documentation

```
template<typename NT, typename ET>
class bats::Diagram
```

Public Functions

```
inline Diagram()
```

```
inline Diagram(size_t n, size_t m)
```

```
inline size_t nnode() const
```

```
inline size_t nedge() const
```

```
inline NT &node_data(size_t i)
```

```
inline const NT &node_data(size_t i) const
```

```
inline ET &edge_data(size_t j)
```

```
inline const ET &edge_data(size_t j) const
```

```
inline size_t edge_source(size_t j) const
```

```
inline size_t edge_target(size_t j) const
```

```
inline size_t add_node(NT &a)
```

```
inline size_t add_node(NT &&a)
```

```
inline void set_node(size_t i, NT &a)
```

```
inline void set_node(size_t i, NT &&a)
```

```
inline size_t add_edge(size_t i, size_t j, ET &data)
```

```
inline size_t add_edge(size_t i, size_t j, ET &&data)
```

```
inline void set_edge(size_t i, size_t s, size_t t, const ET &data)
```

```
inline void save_metadata(std::string &fname) const
```

```
inline void save(std::string &dbname) const
```

Public Members

```
std::vector<NT> node
std::vector<ET> edata
std::vector<Edge> elist
struct Edge
```

Public Functions

```
inline Edge()
inline Edge(size_t s, size_t t)
```

Public Members

```
size_t src
size_t targ
```

Template Class Filtration

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration.hpp

Class Documentation

```
template<typename TF, class CpxTFiltration
    A filtration which can be used to wrap a simplicial/cubical/cell complex.
    A filtration class, templated over the type of the filtration parameter, and the type of the underlying complex
```

Public Functions

```
inline Filtration()
inline Filtration(const CpxT &C)
template<class ...Ts>
inline Filtration(const Ts (&... args))
    Initialization which passes arguments to initialize the underlying complex
```

Parameters `args...` – passed to complex initialization

```
inline Filtration(const CpxT &C, const std::vector<std::vector<TF>> &vals)  
    Initialization which passes arguments to initialize the underlying complex
```

Parameters

- `C` – complex
- `vals` – filtration values for every cell in `C`

```
inline const CpxT &complex() const  
    return const reference to underlying complex
```

```
inline const std::vector<std::vector<TF>> &vals() const  
    return const reference to filtration values
```

```
inline const std::vector<TF> &vals(const size_t k) const  
    return const reference to filtration values
```

Parameters `k` – dimension of values to return

```
inline size_t maxdim() const  
    return maximum dimension of cells
```

```
inline size_t ncells(const size_t dim) const  
    return number of cells in specified dimension
```

Parameters `dim` – dimension

```
template<class ...Ts>  
inline cell_ind add(TF t, Ts (&... args))  
    add cell to filtration
```

Parameters

- `t` – filtration parameter
- `...args` – passed to add method of underlying complex

```
template<class ...Ts>  
inline std::vector<cell_ind> add_recursive(TF t, Ts (&... args))  
    Add recursively to filtration. Any cells added will take filtration value t.
```

Parameters

- `t` – filtration parameter
- `...args` – passed to add_recursive method of underlying complex

```
inline std::vector<size_t> sortperm(size_t dim) const
```

```
inline std::vector<std::vector<size_t>> sortperm() const
```

```
inline CpxT sublevelset(const TF a) const  
    Get sub-levelset of filtration (-inf, a]
```

Parameters `a` – upper bound of levelset

Class CompositePermutation

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_permutation.hpp

Class Documentation

```
class bats::future::CompositePermutation
```

Public Functions

```
inline CompositePermutation()
```

```
inline void append(const ElementaryPermutation &p)
```

```
inline void swap(size_t i, size_t j)
```

```
template<typename T>
inline T &operator()(T &a) const
```

```
template<typename T>
inline T &operator()(T &&a) const
```

```
inline CompositePermutation &operator()(const ElementaryPermutation &p)
```

Friends

```
friend std::ostream & operator<< (std::ostream &os,
const CompositePermutation &p)
```

Template Class const_strided_iterator

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Inheritance Relationships

Base Type

- public std::iterator< std::random_access_iterator_tag, T >

Class Documentation

```
template<typename T>
class bats::future::const_strided_iterator : public std::iterator<std::random_access_iterator_tag, T>
```

Public Functions

```
inline const_strided_iterator()
```

```
inline const_strided_iterator(const T *v, ssize_t s)
```

```
inline ~const_strided_iterator()
```

```
inline iterator operator++(int)
```

```
inline iterator &operator++()
```

```
inline iterator operator--(int)
```

```
inline iterator &operator--()
```

```
inline reference operator*() const
```

```
inline pointer operator->() const
```

```
inline bool operator==(const iterator &rhs) const
```

```
inline bool operator!=(const iterator &rhs) const
```

```
inline iterator operator+(size_t i) const
```

```
inline reference operator[](size_t i) const
```

Template Class Matrix

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Class Documentation

```
template<typename T>
class bats::future::Matrix
```

Public Types

```
typedef T value_type
```

Public Functions

```
inline size_t len() const
```

```
inline void fill(T a)
```

```
inline Matrix()
```

```
inline Matrix(size_t m, size_t n, RowMajor)
```

```
inline Matrix(size_t m, size_t n, ColumnMajor)
```

```
inline Matrix(size_t m, size_t n)
```

```
inline Matrix(size_t m, size_t n, T a)
```

```
template<typename Major>
```

```
inline Matrix(size_t m, size_t n, T a, Major &ms)
```

```
inline Matrix(Matrix &other, ColumnMajor)
```

```
inline T *data()
```

```
inline const T *data() const
```

```
inline size_t nrow() const
```

```
inline size_t ncol() const
```

```
inline std::pair<size_t, size_t> dims() const
```

```
inline T operator[](size_t k) const
```

Basic Applied Topology Subprograms

```
inline T &operator[](size_t k)

inline T operator()(size_t k) const

inline T &operator()(size_t k)

template<typename I1, typename I2>
inline MatrixView<T, I1, I2> view(I1 &rows, I2 &cols)

template<typename I1, typename I2>
inline MatrixView<T, I1, I2> view(I1 &&rows, I2 &&cols)

template<typename I1, typename I2>
inline const MatrixView<T, I1, I2> view(I1 &rows, I2 &cols) const

template<typename I1, typename I2>
inline const MatrixView<T, I1, I2> view(I1 &&rows, I2 &&cols) const

inline T operator()(size_t i, size_t j) const

inline T &operator()(size_t i, size_t j)

inline VectorView<T> row(size_t i)

inline VectorView<T> column(size_t j)

inline void print_info() const

inline void print() const

inline Matrix transpose() const

inline void swap_rows(size_t i1, size_t i2)

inline void swap_columns(size_t j1, size_t j2)

inline bool append_column(const T val = T(0))

inline bool delete_column()

inline void add_row(T a, size_t i1, size_t i0)

inline void add_row(size_t i1, size_t i0)
```

```
inline void add_column(T a, size_t j1, size_t j0)

inline void add_column(size_t j1, size_t j0)

inline void scale_row(T a, size_t i)

inline void scale_column(T a, size_t j)

template<typename TB>
inline auto mm(const TB &B) const

template<typename TB>
inline Matrix operator*(const TB &B) const

template<typename Tx>
inline auto mv(const Tx &x) const
```

Public Static Functions

```
static inline Matrix identity(size_t n)
```

Template Class MatrixView

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Class Documentation

```
template<typename T, typename I1, typename I2>
class bats::future::MatrixView
```

Public Types

```
typedef T val_type
```

Public Functions

```
inline MatrixView()  
  
inline MatrixView(Matrix<T> *m, I1 r, I2 c)  
  
inline MatrixView(Matrix<T> &m, I1 r, I2 c)  
  
inline T operator()(size_t i, size_t j) const  
  
inline T &operator()(size_t i, size_t j)  
  
inline size_t nrow() const  
  
inline size_t ncol() const  
  
inline void print_info() const  
  
inline void print() const
```

Class Permutation

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_permutation.hpp

Class Documentation

```
class bats::future::Permutation
```

Public Functions

```
inline Permutation()  
  
inline Permutation(size_t n)
```

Template Class range

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Nested Relationships

Nested Types

- Class range::const_iterator*

Class Documentation

```
template<typename T>
class bats::future::range
```

Public Types

```
typedef const_iterator iterator
```

Public Functions

```
inline range()
```

```
inline range(T b, T e)
```

```
inline range(T b, T e, T s)
```

```
inline T first() const
```

```
inline T last() const
```

```
inline T stride() const
```

```
inline size_t size() const
```

```
inline T operator[](size_t i) const
```

```
inline const_iterator const begin()
```

```
inline const_iterator const end()
```

```
inline const_iterator const cbegin()
```

```
inline const_iterator const cend()  
  
class const_iterator : public std::iterator<std::random_access_iterator_tag, T>
```

Public Functions

```
inline const_iterator()  
  
inline const_iterator(const T v, const T s)  
  
inline ~const_iterator()  
  
inline iterator operator++(int)  
  
inline iterator &operator++()  
  
inline iterator operator--(int)  
  
inline iterator &operator--()  
  
inline reference operator*() const  
  
inline pointer operator->() const  
  
inline bool operator==(const iterator &rhs) const  
  
inline bool operator!=(const iterator &rhs) const
```

Class *range*::**const_iterator**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Nested Relationships

This class is a nested type of *Template Class range*.

Inheritance Relationships

Base Type

- public std::iterator< std::random_access_iterator_tag, T >

Class Documentation

```
class bats::future::range::const_iterator : public std::iterator<std::random_access_iterator_tag, T>
```

Public Functions

```
inline const_iterator()
```

```
inline const_iterator(const T v, const T s)
```

```
inline ~const_iterator()
```

```
inline iterator operator++(int)
```

```
inline iterator &operator++()
```

```
inline iterator operator--(int)
```

```
inline iterator &operator--()
```

```
inline reference operator*() const
```

```
inline pointer operator->() const
```

```
inline bool operator==(const iterator &rhs) const
```

```
inline bool operator!=(const iterator &rhs) const
```

Template Class Span

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_span.hpp

Class Documentation

```
template<typename T>
class bats::future::Span
```

Public Functions

```
inline Span()
```

```
inline Span(T)
```

```
inline Span(size_t n, T)
```

```
inline size_t dim() const
```

```
inline size_t vdim() const
```

```
template<typename TV>
inline bool add(const TV &v)
```

```
template<typename TV>
inline bool contains(const TV &v) const
```

Public Members

```
Matrix<T> Pt
```

```
Matrix<T> L
```

```
size_t _vdim
```

Template Class strided_iterator

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Inheritance Relationships

Base Type

- public std::iterator< std::random_access_iterator_tag, T >

Class Documentation

```
template<typename T>
class bats::future::strided_iterator : public std::iterator<std::random_access_iterator_tag, T>
```

Public Functions

```
inline strided_iterator()
```

```
inline strided_iterator(T *v, ssize_t s)
```

```
inline ~strided_iterator()
```

```
inline iterator operator++(int)
```

```
inline iterator &operator++()
```

```
inline iterator operator--(int)
```

```
inline iterator &operator--()
```

```
inline reference operator*() const
```

```
inline pointer operator->() const
```

```
inline bool operator==(const iterator &rhs) const
```

```
inline bool operator!=(const iterator &rhs) const
```

```
inline iterator operator+(size_t i) const
```

```
inline reference operator[](size_t i) const
```

Template Class VectorView

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Class Documentation

```
template<typename T>
class bats::future::VectorView
```

Public Types

```
typedef strided_iterator<T> iterator
typedef const_strided_iterator<T> const_iterator
```

Public Functions

```
inline VectorView(T *s, T *e, size_t stride)
```

```
inline iterator begin()
```

```
inline iterator end()
```

```
inline const_iterator begin() const
```

```
inline const_iterator end() const
```

```
inline const_iterator cbegin() const
```

```
inline const_iterator cend() const
```

```
inline T &operator[](size_t i)
```

```
inline const T &operator[](size_t i) const
```

```
inline void print() const
```

```
inline void axpy(T a, const VectorView &other)
```

```
inline void axpy(T a, const VectorView &&other)
```

```
inline void scale(T a)
```

Template Class LightSimplicialComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_light_simplicial_complex.h

Nested Relationships

Nested Types

- Struct LightSimplicialComplex::simplex_boundary_iterator*

Class Documentation

```
template<typename index_type = size_t, typename hash_table = std::unordered_map<index_type, size_t>>
class bats::LightSimplicialComplex
```

Public Functions

```
inline index_type max_vertex(index_type s, size_t dim) const
```

```
inline LightSimplicialComplex()
```

```
inline LightSimplicialComplex(const index_type n, const index_type k)
```

```
inline index_type maxdim() const
```

```
inline size_t ncells(size_t dim) const
```

```
inline size_t ncells() const
```

```
inline index_type simplex_key(const std::vector<index_type> &s) const
```

```
inline void key_to_simplex(const size_t dim, index_type key, std::vector<index_type> &s) const
```

```
inline std::vector<index_type> key_to_simplex(const size_t dim, index_type key) const
```

```
inline std::vector<index_type> get_simplex(const size_t dim, const size_t i) const
```

```
inline void get_simplex(const size_t dim, const size_t i, std::vector<index_type> &s) const
```

```
inline auto get_cell(size_t dim, size_t i, std::vector<index_type> &s) const
```

```
inline auto get_cell(size_t dim, size_t i) const
```

Basic Applied Topology Subprograms

```
inline std::vector<std::vector<index_type>> get_simplices(const size_t dim) const  
  
inline std::vector<std::vector<size_t>> get_simplices() const  
  
inline size_t find_idx(const size_t dim, const index_type key) const  
  
inline size_t find_idx(const std::vector<index_type> &s) const  
  
inline cell_ind add_unsafe(const size_t dim, const index_type k)  
  
inline cell_ind add(const size_t dim, const index_type k)  
  
inline cell_ind add_unsafe(const std::vector<index_type> &s)  
  
inline auto add(const std::vector<index_type> &s)  
  
inline std::vector<cell_ind> add_recursive(size_t dim, const index_type k)  
  
inline std::vector<cell_ind> add_recursive(const std::vector<index_type> &s)  
  
inline auto simplex_begin(const size_t dim, const size_t i) const  
  
inline auto simplex_end(const size_t dim, const size_t i) const  
  
inline auto boundary(const size_t dim, const size_t i) const  
  
inline CSCMatrix<int, size_t> boundary_csc(const size_t dim) const  
  
inline void print_summary() const
```

Template Class ReducedChainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_basis.hpp

Class Documentation

```
template<typename MT>  
class bats::ReducedChainComplex
```

Public Types

```
using chain_type = typename MT::col_type
```

Public Functions

```
inline size_t hdim(size_t k) const
```

```
inline size_t betti(size_t k) const
```

```
inline size_t maxdim() const
```

```
inline size_t dim(size_t k) const
```

```
inline MT &operator[](size_t k)
```

```
inline void initialize(const ChainComplex<MT> &C)  
    initialize with chain complex C, but do not do reduction
```

```
inline ReducedChainComplex()
```

```
inline ReducedChainComplex(const ChainComplex<MT> &C)
```

```
template<typename algflag>  
inline ReducedChainComplex(const ChainComplex<MT> &C, algflag)
```

```
template<typename algflag>  
inline ReducedChainComplex(const ChainComplex<MT> &C, algflag, bats::compute_basis_flag)
```

```
template<typename algflag>  
inline ReducedChainComplex(const ChainComplex<MT> &C, algflag, bats::clearing_flag)
```

```
template<typename algflag>  
inline ReducedChainComplex(const ChainComplex<MT> &C, algflag, bats::compression_flag)
```

```
template<typename algflag>  
inline ReducedChainComplex(const ChainComplex<MT> &C, algflag, bats::compression_flag,  
                         bats::compute_basis_flag)
```

```
template<typename ...Args>  
inline void update_reduction2(size_t k, Args... args)
```

```
template<typename ...Args>  
inline void update_reduction(size_t k, Args... args)
```

```
inline void permute_matrices(size_t k, const std::vector<size_t> &perm)

template<typename ...Args>
inline void permute_basis(const std::vector<std::vector<size_t>> &perm, Args... args)

template<typename Information_type, typename ...Args>
inline void update_basis_general(const Information_type &UI, Args... args)

inline void sparsify_basis()
    greedily introduce sparsity into basis

inline void remove_extra_cycles()
    remove extra cycles from U[k]

template<typename TV>
inline TV to_hom_basis(const TV &v, size_t k) const

template<typename TV>
inline TV from_hom_basis(const TV &v, size_t k) const

inline chain_type get_preferredRepresentative(const size_t j, const size_t k) const

inline void find_preferredRepresentative(chain_type &y, const size_t k) const

inline chain_type chain_preferredRepresentative(const chain_type &c, size_t k) const

inline void print_summary(bool print_nnz = false) const
```

Public Members

```
std::vector<MT> U
std::vector<MT> R
std::vector<std::vector<size_t>> I
std::vector<std::vector<size_t>> p2c
```

Template Class ReducedCochainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_cohom_basis.hp

Class Documentation

```
template<typename MT>
class bats::ReducedCochainComplex
```

Public Types

```
using cochain_type = typename MT::col_type
```

Public Functions

```
inline size_t hdim(size_t k) const
```

```
inline size_t maxdim() const
```

```
inline MT &operator[](size_t k)
```

```
inline ReducedCochainComplex()
```

```
inline ReducedCochainComplex(const CochainComplex<MT> &C)
```

```
template<typename algflag>
```

```
inline ReducedCochainComplex(const CochainComplex<MT> &C, algflag)
```

```
template<typename algflag>
```

```
inline ReducedCochainComplex(const CochainComplex<MT> &C, algflag, bats::compute_basis_flag)
```

```
template<typename algflag>
```

```
inline ReducedCochainComplex(const CochainComplex<MT> &C, algflag, bats::clearing_flag)
```

```
template<typename algflag>
```

```
inline ReducedCochainComplex(const CochainComplex<MT> &C, algflag, bats::compression_flag)
```

```
template<typename TV>
```

```
inline TV to_hom_basis(const TV &v, size_t k) const
```

```
template<typename TV>
```

```
inline TV from_hom_basis(const TV &v, size_t k) const
```

```
inline cochain_type get_preferredRepresentative(size_t i, const size_t k) const
```

```
inline void findPreferredRepresentative(typename MT::col_type &y, const size_t k) const
```

```
inline cochain_type chain_preferredRepresentative(const cochain_type &c, size_t k) const
```

Public Members

```
std::vector<size_t> dim
std::vector<MT> U
std::vector<MT> R
std::vector<std::vector<size_t>> I
std::vector<std::vector<size_t>> p2c
```

Class SimplicialComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_complex.h

Class Documentation

```
class bats::SimplicialComplex
```

A simplicial complex based using a trie data structure.

A class which can be used to hold simplicial complexes on large or expanding vertex sets. For a lighter-weight option, see *LightSimplicialComplex*

Public Functions

```
inline SimplicialComplex()
```

```
inline SimplicialComplex(size_t maxdim)
```

Initialization up to a certain dimension

Parameters **maxdim** – [in] - the maximum dimension simplex expected to be added

```
inline SimplicialComplex(size_t n, size_t maxdim)
```

Initialization on a certain vertex

Parameters

- **n** – [in] - the maximum expected vertex index

- **maxdim** – [in] - the maximum dimension simplex expected to be added

```
inline SimplicialComplex(const std::vector<size_t> &dim)
```

```
inline SimplicialComplex(const std::string &&fname)
```

```
inline size_t find_idx(const std::vector<size_t> &s)
```

Find the index of a simplex

Parameters **s** – [in] A vector containing the simplex

Returns The index associated with the simplex. Returns bats::NO_IND if the simplex is not in the complex.

```
inline size_t find_idx(const std::vector<size_t> &s) const  
  
inline size_t maxdim() const  
  
inline size_t ncells(const size_t k) const  
  
inline size_t ncells() const  
  
inline cell_ind add(std::vector<size_t> &s)  
  
inline cell_ind add(std::vector<size_t> &&s)  
  
inline std::vector<cell_ind> add_recursive(std::vector<size_t> &s)  
  
inline std::vector<cell_ind> add_recursive(std::vector<size_t> &&s)  
  
inline auto faces_begin(const size_t dim, const size_t i) const  
  
inline auto faces_begin(const cell_ind &ci) const  
  
inline auto faces_end(const size_t dim, const size_t i) const  
  
inline auto faces_end(const cell_ind &ci) const  
  
inline auto simplex_begin(const size_t dim, const size_t i) const  
  
inline auto simplex_end(const size_t dim, const size_t i) const  
  
inline void get_simplex(size_t dim, size_t i, std::vector<size_t> &s) const  
    fill s with simple i in dimension dim  
  
inline std::vector<size_t> get_simplex(size_t dim, size_t i) const  
    return simplex i in dimension dim  
  
inline auto get_cell(size_t dim, size_t i, std::vector<size_t> &s) const  
  
inline auto get_cell(size_t dim, size_t i) const  
  
inline std::vector<std::vector<size_t>> get_simplices(const size_t dim) const  
  
inline std::vector<std::vector<size_t>> get_simplices() const
```

Basic Applied Topology Subprograms

```
inline void union_add(const SimplicialComplex &Y)

inline std::vector<size_t> get_indices(const SimplicialComplex &A, size_t dim) const

inline std::vector<std::vector<size_t>> get_indices(const SimplicialComplex &A) const

inline auto boundary(const size_t dim, const size_t k) const

inline CSCMatrix<int, size_t> boundary_csc(const size_t dim) const

inline ~SimplicialComplex()

inline void save(std::string &fname) const

inline void print_summary() const

inline void print_cells() const
```

Friends

```
friend class MorsePairing< SimplicialComplex >

inline friend friend SimplicialComplex simplicial_union (const SimplicialComplex &X,
const SimplicialComplex &Y)

inline friend friend SimplicialComplex intersection (const SimplicialComplex &X,
const SimplicialComplex &Y)
```

Template Class SparseTrie

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_trie.hpp

Class Documentation

```
template<typename A, typename T>

class bats::SparseTrie
```

Public Types

```
typedef SparseTrie<A, T> child_type
typedef std::unordered_map<A, child_type*> child_container
```

Public Functions

```
inline SparseTrie(const SparseTrie &t)

inline SparseTrie(SparseTrie &&t)

inline SparseTrie(T v)

inline SparseTrie()

inline ~SparseTrie()

inline SparseTrie &operator=(const SparseTrie &t)

inline SparseTrie &operator=(SparseTrie &&t)

template<typename ITT>
inline void insert(ITT stptr, const ITT endptr, const T &v)

inline void emplace(const std::vector<A> &k, T &&v)

inline void emplace(const std::vector<A> &k, const T &v)

template<typename ITT>
inline T &get(ITT stptr, const ITT endptr)

inline T &operator[](const std::vector<T> &k)

template<typename ITT>
inline T get(ITT stptr, const ITT endptr, const T &def_ret)

inline T get(const std::vector<T> &k, const T &def_ret)

template<typename ITT>
inline T get(ITT stptr, const ITT endptr, const T &def_ret) const

inline T get(const std::vector<T> &k, const T &def_ret) const

template<typename ITT>
```

```
inline size_t count(ITT stptr, const ITT endptr)
```

```
inline size_t count(const std::vector<T> &k)
```

Public Members

T **val**

child_container ***children** = nullptr

Class SimplexContainer

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_simplex.hpp

Class Documentation

```
class bats::util::SimplexContainer
```

Public Functions

```
inline SimplexContainer(size_t d)
```

```
inline void emplace_back(std::vector<size_t> &s)
```

```
inline size_t size() const
```

```
inline size_t dim() const
```

Template Class ZigzagFiltration

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_zigzag_filtration.hpp

Class Documentation

```
template<typename CpxT, typename T = double>
```

```
class bats::zigzag::ZigzagFiltration
```

A class that wraps a complex with a zigzag filtration.

A class that wraps a complex with a right filtration. Cells can have entry times and removal times. These intervals are stored as std::pair<T, T>

Public Functions

inline **ZigzagFiltration()**

template<class ...**Ts**>
inline **ZigzagFiltration**(const **Ts** (&... args))

Initialization which passes arguments to initialize the underlying complex

Parameters **args...** – passed to complex initialization

inline **ZigzagFiltration**(const **CpxT** &X, const std::vector<std::vector<std::vector<std::pair<**T**, **T**>>>&val)

Construct right filtration explicitly on a complex

val should be a vector of vector of pairs. val[k][i] is the pair of entry times for cell i in dimension k in X.

No checks are done to make sure the number of values matches the number of cells

Parameters

- **X** – complex representing topological space
- **val** – right filtration values for each cell in X

inline const **CpxT** &**complex**() const
return const reference to underlying complex

inline const std::vector<std::vector<std::vector<std::pair<**T**, **T**>>>&**vals**() const
return const reference to right filtration values

inline const std::vector<std::vector<std::pair<**T**, **T**>>>&**vals**(const size_t k) const
return const reference to right filtration values

Parameters **k** – dimension of values to return

inline size_t **maxdim**() const
return maximum dimension of cells

inline size_t **ncells**(const size_t dim) const
return number of cells in specified dimension

Parameters **dim** – dimension

template<class ...**Ts**>
inline **cell_ind** **add**(const **T** entry, const **T** exit, **Ts** (&... args))
add cell to right filtration

Parameters

- **entry** – entry parameter
- **exit** – exit parameter
- **...args** – passed to add method of underlying complex

inline **cell_ind** **add**(const **T** entry, const **T** exit, std::vector<size_t> &&s)

template<class ...**Ts**>

inline std::vector<**cell_ind**> **add_recursive**(const **T** entry, const **T** exit, **Ts** (&... args))

Add recursively to right filtration. Any cells added will take same entry and exit parameters

Parameters

- **entry** – entry parameter
- **exit** – exit parameter
- **...args** – passed to add_recursive method of underlying complex

```
inline std::vector<cell_ind> add_recursive(const T entry, const T exit, std::vector<size_t> &&s)
```

```
inline CpxT levelset(T s0, T s1) const
```

Return thickened levelset $f^{-1}([s0, s1])$ adds a cell to levelset if $[b, d] \cap [s0, s1]$ is non-empty

Parameters

- **s0** – lower bound of levelset
- **s1** – upper bound of levelset

Template Class ColumnMatrix

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Inheritance Relationships

Base Type

- public AbstractMatrix (*Class AbstractMatrix*)

Class Documentation

```
template<class TC>
```

```
class ColumnMatrix : public AbstractMatrix
```

Public Types

```
using val_type = typename TC::val_type
```

```
using col_type = TC
```

Public Functions

```
inline ColumnMatrix()
```

```
inline ColumnMatrix(size_t m, size_t n)
```

```
inline ColumnMatrix(size_t _m, size_t _n, val_type a)
    construct column matrix filled with entry a
```

```
inline ColumnMatrix(const std::vector<TC> &_col)
```

```
inline ColumnMatrix(size_t _m, size_t _n, const std::vector<TC> &_col)

template<typename TC2>
inline ColumnMatrix(const ColumnMatrix<TC2> &other)

inline ColumnMatrix(const CSCMatrix<int, size_t> &A)

inline void read(std::istream &io)

inline ColumnMatrix(std::istream &io)

inline ColumnMatrix(std::string &fname)

inline size_t nrow() const

inline size_t ncol() const

inline std::vector<TC> &cols()

inline const std::vector<TC> &cols() const

inline void set_nrow(size_t mnew)

inline auto getval(const size_t i, const size_t j) const

template<class ...Ts>
inline void append_column(Ts (&... args))
    append a column to the end of the matrix
    calls a column vector constructor on arguments passed in.

template<class ...Ts>
inline void append_column(Ts (&&... args))

inline void append_row()
    append an empty row to the end of the matrix

template<class ...Ts>
inline void insert_column(const size_t &index, Ts (&&... args))
    Do not recommend, because if we want to insert multiple columns, the index will change after the first
    insertion. Thus the important thing we need to assume is the index list are in ascending order!

inline void append_column()

inline void insert_column(const size_t &index)

inline void insert_columns(const std::vector<size_t> &c_inds, std::vector<TC> &insert_col)
    insert list of columns at list of specified indices
```

Basic Applied Topology Subprograms

mutates input inserted columns

inline void **append_row**(const std::vector<*val_type*> &row)

inline void **insert_row**(const size_t &index, const std::vector<*val_type*> &row)

inline void **insert_row**(const size_t &index)

inline void **insert_rows**(const std::vector<size_t> &r_inds)
 insert zero rows at specified locations

inline void **erase_column**(const size_t &index)

inline void **erase_column**()

inline void **erase_row**(const size_t &index)
 erase specified row

inline void **erase_row**()
 erase last row

inline void **erase_row_unsafe**()
 assumes that last row is zero so we only need to decrement number of rows

inline *TC* &**operator[]**(size_t index)

inline const *TC* &**operator[]**(size_t index) const

inline auto **operator()**(size_t i, size_t j) const

inline bool **operator==**(const *ColumnMatrix* &other) const

inline std::vector<std::vector<*val_type*>> **to_row_array**() const

inline *val_type* ***dump_dense**() const

inline *ColumnMatrix* **submatrix**(const std::vector<size_t> &rind, const std::vector<size_t> &cind) const

inline *ColumnMatrix* **block**(const size_t i0, const size_t i1, const size_t j0, const size_t j1) const

inline void **set_block**(const size_t i0, const size_t i1, const size_t j0, const size_t j1, const *ColumnMatrix* &B)

inline void **clear_rows**(const std::vector<bool> &c)
 clear rows i for which c[i] is true use vector of bools for quick lookup - vector of inds would require search

inline void **clear_cols**(const std::vector<bool> &c)
 clear columns j for which c[j] is true
 frees memory as well

```
inline void swap_rows(const size_t i, const size_t i2)

inline void mix_rows(const size_t i, const size_t i2, const val_type &a, const val_type &b, const val_type &c,
                     const val_type &d)

inline void add_rows(const size_t i, const val_type &c, const size_t i2)

inline TC gemv(const TC &x) const

inline ColumnMatrix operator*(const val_type a) const

inline TC operator*(const TC &x) const

inline ColumnMatrix operator*(const ColumnMatrix &B) const

inline ColumnMatrix operator+(const ColumnMatrix &B) const

inline ColumnMatrix &operator+=(const ColumnMatrix &B)

inline ColumnMatrix operator-(const ColumnMatrix &B) const

inline ColumnMatrix transpose() const

inline ColumnMatrix T() const

inline void permute_cols(const std::vector<size_t> &colperm)

inline void ipermute_cols(const std::vector<size_t> &colperm)

inline void mix_cols(const size_t j, const size_t k, const val_type &a, const val_type &b, const val_type &c,
                     const val_type &d)

inline void permute_rows(const std::vector<size_t> &rowperm)

inline void ipermute_rows(const std::vector<size_t> &rowperm)

inline void permute(const std::vector<size_t> &rowperm, const std::vector<size_t> &colperm)

inline ColumnMatrix &J_right_inplace()

inline ColumnMatrix J_right() const

inline ColumnMatrix &J_left_inplace()
```

```
inline ColumnMatrix J_left() const  
  
inline ColumnMatrix &J_conjugation_inplace()  
  
inline ColumnMatrix J_conjugation() const  
  
inline void swap_cols(size_t j1, size_t j2)  
  
inline void schur_complement(size_t i, size_t j)  
  
inline ColumnMatrix &row_scale(const std::vector<val_type> &coeff)  
  
inline ColumnMatrix &col_inv_scale(const std::vector<val_type> &coeff)  
  
inline size_t nnz() const  
  
inline bool is_zero() const  
  
inline bool is_upper() const  
  
inline bool is_upper_invert() const  
  
inline bool is_lower() const  
  
inline bool is_reduced() const  
  
inline bool is_pivot_matrix() const  
  
inline bool is_EL() const  
  
inline bool is_EU() const  
  
inline bool is_ELhat() const  
  
inline bool is_EUhat() const  
  
inline void print_size() const  
  
inline void print() const  
  
inline void write(std::ostream &io) const
```

```
inline std::string str()  
  
inline void save(std::string &fname) const
```

Public Static Functions

```
static inline ColumnMatrix identity(size_t n)  
  
static inline ColumnMatrix random(size_t m, size_t n, double p, int maxval, std::default_random_engine  
&generator)  
  
static inline ColumnMatrix random(size_t m, size_t n, double p, int maxval)
```

Friends

```
inline friend friend TC operator* (const TC &x, const ColumnMatrix &A)  
multiplication x^T A  
  
inline friend friend ColumnMatrix tensor_product (const ColumnMatrix &A,  
const ColumnMatrix &B)  
  
inline friend friend ColumnMatrix direct_sum (const ColumnMatrix &A,  
const ColumnMatrix &B)
```

Template Class CSCMatrix

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_csc_matrix.hpp

Inheritance Relationships

Base Type

- public *AbstractMatrix* (*Class AbstractMatrix*)

Class Documentation

```
template<typename TV, typename TI = size_t>  
class CSCMatrix : public AbstractMatrix
```

Public Functions

```
inline CSCMatrix()  
  
inline CSCMatrix(size_t m, size_t n, const std::vector<TI> &colptr, const std::vector<TI> &rowind, const std::vector<TV> &val)  
  
inline CSCMatrix(const std::vector<TI> &colptr, const std::vector<TI> &rowind, const std::vector<TV> &val)  
  
inline TV getval(size_t i, size_t j) const  
  
inline const std::vector<TI> &get_colptr() const  
  
inline const std::vector<TI> &get_rowind() const  
  
inline const std::vector<TV> &get_val() const  
  
inline size_t nrow() const  
  
inline size_t ncol() const  
  
inline void print_size() const  
  
inline void print(size_t rowmin, size_t rowmax, size_t colmin, size_t colmax) const  
  
inline void print() const  
  
inline CSCMatrix submatrix(const std::vector<size_t> &rind, const std::vector<size_t> &cind) const  
  
inline CSCMatrix operator*(const CSCMatrix &other) const
```

Friends

```
inline friend void block_select (const CSCMatrix &M,  
const std::vector< size_t > &cind, const std::vector< size_t > &prow,  
const size_t m, CSCMatrix &A)  
  
template<size_t N> inline friend void block_select (const CSCMatrix &M,  
const std::vector< size_t > &cind, const std::vector< size_t > *(&&prow)[N],  
const size_t(&&m)[N], CSCMatrix *(&&A)[N])  
  
inline friend void gemm (const CSCMatrix &A, const CSCMatrix &B,  
CSCMatrix &C)  
  
inline friend void sum (const CSCMatrix &A, const CSCMatrix &B, CSCMatrix &C)
```

```
inline friend friend void sum (const TV &alpha, const CSCMatrix &A,
const CSCMatrix &B, CSCMatrix &C)
inline friend friend void trilu (const CSCMatrix &A, const CSCMatrix &B,
CSCMatrix &C)
```

Template Class ModP

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_field.hpp

Inheritance Relationships

Base Type

- public AbstractField< ModP< IntT, P > > (*Template Class AbstractField*)

Class Documentation

```
template<typename IntT, unsigned P>
class ModP : public AbstractField<ModP<IntT, P>>
```

Public Functions

```
inline ModP()
```

```
inline ModP(IntT val)
```

```
inline IntT to_int() const
```

```
inline ModP operator+(const ModP &b) const
```

```
inline ModP &operator+=(const ModP &b)
```

```
inline ModP operator-(const ModP &b) const
```

```
inline ModP &operator-=(const ModP &b)
```

```
inline ModP operator-() const
```

```
inline ModP operator*(const ModP &b) const
```

```
inline ModP &operator*=(const ModP &b)
```

Basic Applied Topology Subprograms

```
inline bool operator==(const ModP &b) const
```

```
inline bool operator!=(const ModP &b) const
```

```
inline bool operator==(const int b) const
```

```
inline bool operator!=(const int b) const
```

```
inline bool operator<(const ModP &b) const
```

```
ModP inv() const
```

```
inline ModP operator/(const ModP &b) const
```

```
inline ModP &operator/=(const ModP &b)
```

```
inline bool iszero() const
```

Friends

```
inline friend friend std::ostream & operator<< (std::ostream &os, const ModP &x)
```

Template Class *ModP< IntT, 2 >*

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_field.hpp

Inheritance Relationships

Base Type

- public *AbstractField< ModP< IntT, 2 > >* (*Template Class AbstractField*)

Class Documentation

```
template<typename IntT>
```

```
class ModP<IntT, 2> : public AbstractField<ModP<IntT, 2>>
```

Public Functions

```
inline ModP()  
  
inline ModP(IntT val)  
  
inline IntT to_int() const  
  
inline ModP operator+(const ModP &b) const  
  
inline ModP &operator+=(const ModP &b)  
  
inline ModP operator-(const ModP &b) const  
  
inline ModP &operator-=(const ModP &b)  
  
inline ModP &operator-()  
  
inline ModP operator*(const ModP &b) const  
  
inline ModP &operator*=(const ModP &b)  
  
inline ModP operator/(const ModP &b) const  
  
inline ModP &operator/=(const ModP &b)  
  
inline ModP inv() const  
  
inline bool operator==(const ModP &b) const  
  
inline bool operator!=(const ModP &b) const  
  
inline bool operator==(const int b) const  
  
inline bool operator!=(const int b) const  
  
inline ModP operator=(const int &a)  
  
inline bool iszzero() const  
  
inline bool operator<(const ModP &b) const
```

Friends

```
inline friend friend std::ostream & operator<< (std::ostream &os, const ModP &x)
```

Template Class MorsePairing

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_morse_pairing.hpp

Class Documentation

```
template<class CpxT>
class MorsePairing
```

Public Functions

```
inline MorsePairing()
```

```
inline MorsePairing(CpxT &C)
```

```
inline MorsePairing(size_t maxdim)
```

```
inline MorsePairing(std::vector<size_t> ncells)
```

```
inline void clear()
```

```
inline size_t maxdim() const
```

```
inline size_t size(const size_t dim) const
```

```
inline size_t ncells(const size_t dim) const
```

```
inline bool is_paired(size_t dim, size_t i) const
```

```
inline bool set_pair(size_t dim, size_t i, size_t j)
```

```
inline bool set_pair_edge(const size_t i, const size_t j, const size_t ei)
```

```
template<typename TR>
inline bool set_pair_edge(const size_t i, const size_t j, const size_t ei, const std::vector<TR> &rank)
```

```
inline const std::vector<size_t> &up_paired(size_t dim) const
```

```
inline const std::vector<size_t> &down_paired(size_t dim) const  
  
inline std::vector<size_t> unpaired(size_t dim) const  
  
template<class ...Ts>  
inline cell_ind add(Ts (&... args))  
  
template<class ...Ts>  
inline cell_ind add_pair(Ts (&... args))  
  
template<class ...Ts>  
inline auto faces_begin(Ts (&... args))  
  
template<class ...Ts>  
inline auto faces_end(Ts (&... args))  
  
inline CSCMatrix<int, size_t> boundary_csc(const size_t dim) const
```

Friends

```
friend class Filtration
```

Template Class MultiGraph

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_multigraph.hpp

Nested Relationships

Nested Types

- Struct MultiGraph::Edge*
- Struct MultiGraph::Node*

Class Documentation

```
template<typename NT, typename ET>  
class MultiGraph
```

Public Functions

```
inline MultiGraph()  
  
inline Node &add_node(NT &a)  
  
inline Edge &add_edge(Node &a, Node &b, ET &data)
```

```
struct Edge
```

Public Functions

```
inline Edge(Node &sin, Node &tin, ET &x)  
  
inline ET *get_data()  
  
inline void print()
```

Public Members

```
ET *data  
Node *src  
Node *targ  
struct Node
```

Public Functions

```
inline Node(NT &x)  
  
inline Node(NT *x)  
  
inline void add_input(Edge *in)  
  
inline void add_output(Edge *out)  
  
inline NT *get_data()  
  
inline void print()
```

Public Members

```
NT *data  
std::vector<Edge*> input  
std::vector<Edge*> output
```

Template Class Rational

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_field.hpp

Inheritance Relationships

Base Type

- public AbstractField< Rational< IntT > > (*Template Class AbstractField*)

Class Documentation

```
template<typename IntT>  
class Rational : public AbstractField<Rational<IntT>>
```

Public Functions

```
inline Rational()  
  
inline Rational(IntT n0, IntT d0)  
  
inline Rational(IntT n)  
  
inline IntT to_int() const  
  
inline Rational operator+(const Rational &b) const  
  
inline Rational &operator+=(const Rational &b)  
  
inline Rational operator-(const Rational &b) const  
  
inline Rational &operator-=(const Rational &b)  
  
inline Rational operator-() const  
  
inline Rational operator*(const Rational &b) const
```

Basic Applied Topology Subprograms

```
inline Rational &operator*=(const Rational &b)

inline bool operator==(const Rational &b) const

inline bool operator!=(const Rational &b) const

inline bool operator==(const int b) const

inline bool operator!=(const int b) const

inline bool operator<(const Rational &b) const

inline Rational inv() const

inline Rational operator/(const Rational &b) const

inline Rational &operator/=(const Rational &b)

inline bool iszero() const
```

Friends

```
inline friend friend std::ostream & operator<< (std::ostream &os, const Rational &x)
```

Template Class SetVector

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_set_vector.hpp

Class Documentation

```
template<typename TV, typename TI = size_t>

class SetVector
```

Public Functions

```
inline SetVector()

inline SetVector(const std::set<key_type> indval)

inline SetVector(const std::vector<TI> &ind, const std::vector<TV> &val)

template<typename IT1, typename IT2>
```

```
inline SetVector(IT1 indit, IT2 valit, size_t n)

inline SetVector(const TI i)

inline auto nzbegin() const

inline auto zend() const

inline auto nzbegin()

inline auto zend()

inline size_t nnz() const

inline auto lower_bound(const TI &i)

inline auto lower_bound(const TI &i) const

inline auto upper_bound(const TI &i)

inline auto upper_bound(const TI &i) const

inline auto set(const key_type &k)

inline auto set(const TI ind, const TV val)

template<typename iT>
inline auto replace(iT &it, const key_type &k)

template<typename iT>
inline auto replace(iT &it, const TI ind, const TV val)

template<typename iT>
inline auto replace(iT &it, const TV val)

inline const key_type &lastnz() const

inline TV get(const TI ind) const

inline void permute(const std::vector<size_t> &perm)

template<class SVT>
inline void axpy(const TV &a, const SVT &x)
```

```
template<class SVT>
inline void axpy(const TV &a, const SVT &x, const TI &firstind, const TI &lastind)

inline void print() const

inline void print_row() const

template<typename T>
inline bool operator==(const T &other) const
```

Template Class SparseVector

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_vector.hpp

Class Documentation

```
template<typename TV, typename TI = size_t>

class SparseVector
```

Public Types

```
using val_type = TV
using tmp_type = std::vector<key_type>
```

Public Functions

```
inline void sort()

inline SparseVector()

inline SparseVector(const std::vector<key_type> &indval)

inline SparseVector(const std::vector<TI> &ind, const std::vector<TV> &val)

template<typename TI2>
inline SparseVector(const SparseVector<int, TI2> &other)

inline SparseVector(const std::vector<std::tuple<size_t, int>> &ival)

template<typename IT1, typename IT2>
inline SparseVector(IT1 indit, IT2 valit, size_t n)
```

```
inline SparseVector(const TI i, const TV v = TV(1))

inline SparseVector(const TV a, const TI m)
    constructor that fills vector with m copies of a

inline SparseVector(std::initializer_list<TI> ind, std::initializer_list<TV> val)
    constructor for initializer lists

Parameters

- ind – nonzero indices
- val – nonzero values



inline SparseVector(std::string &line)

inline SparseVector shift_inds(TI shift) const

template<typename T>
inline bool operator==(const T &other) const

template<typename T>
inline bool operator!=(const T &other) const

template<typename T>
inline SparseVector operator[](const T &indset) const

inline auto nzbegin() const

inline auto zend() const

inline auto nzbegin()

inline auto zend()

inline void clear()

inline void clear_dealloc()

inline void clear_zeros()

inline void clear_inds(const std::vector<bool> &c)
    clear indices marked true in c i.e. remove entry i if c[i] is true

inline void clear_inds(const std::vector<bool> &c, std::vector<key_type> &tmp)

inline size_t nnz() const
```

```
inline std::vector<size_t> nzinds() const  
  
inline std::vector<TV> nzvals() const  
  
inline std::tuple<std::vector<size_t>, std::vector<TV>> nzs() const  
  
inline auto lower_bound(const TI &i)  
  
inline auto lower_bound(const TI &i) const  
  
inline auto upper_bound(const TI &i)  
  
inline auto upper_bound(const TI &i) const  
  
template<typename iTT>  
inline auto replace(itT &it, const key_type &k)  
  
template<typename iTT>  
inline auto replace(itT &it, const TI ind, const TV val)  
  
template<typename iTT>  
inline auto replace(itT &it, const TV val)  
  
inline TV getval(const size_t i) const  
  
inline TV operator[](size_t i) const  
  
inline auto emplace_back(const key_type &k)  
  
inline auto emplace_back(TI ind, TV val)  
  
inline auto find_last_nz(TI i)  
  
inline const key_type &lastnz() const  
  
inline const key_type &firstnz() const  
  
inline void permute(const std::vector<size_t> &perm)  
  
inline void ipermute(const std::vector<size_t> &perm)  
  
inline SparseVector subvector(const std::vector<size_t> &pind) const
```

```
inline SparseVector block(const size_t i0, const size_t i1) const  
  
inline void set_block(const size_t i0, const size_t i1, const SparseVector &b)  
  
inline void J(const size_t m)  
  
inline void swap_rows(const size_t i, const size_t j)  
  
inline void scale_inplace(const TI i, const TV &c)  
  
inline void erase_last_row_of_matrix(const TI i)  
  
inline void erase_for_matrix(const TI i)  
  
inline void mix_rows(const size_t i, const size_t j, const TV &a, const TV &b, const TV &c, const TV &d)  
  
inline void insert_rows(const std::vector<size_t> &r_inds)  
    insert row indices at specified locations assumes that list of rows is in sorted order  
template<class SVT>  
inline size_t nnz_intersection(const SVT &x) const  
    calculate the number of non-zeros common to two vectors  
  
Parameters x – sparse vector for comparison  
  
Returns ct number of non-zeros common to both this vector and x  
  
template<class SVT>  
inline void coeff_intersection(const SVT &x, std::map<TV, size_t> &ct) const  
    calculate the number of non-zeros common with c * x where c ranges over any possible value  
  
Parameters

- x – sparse vector for comparison
- ct – map from coefficient c to number of identical nonzeros with c*x ct is not cleared in the function.

  
template<class SVT>  
inline void axpy(const TV &a, const SVT &x, std::vector<key_type> &tmp)  
  
template<class SVT>  
inline void axpy(const TV &a, const SVT &x)  
  
inline SparseVector operator+(const SparseVector &other) const  
  
inline SparseVector operator*(const TV a) const  
    scalar multiplication  
inline TV operator*(const SparseVector &x) const  
    dot product  
template<class SVT>
```

```
inline void axpy(const TV &a, const SVT &x, const TI &firstind, const TI &lastind, std::vector<key_type>&tmp)

template<class SVT>
inline void axpy(const SVT &x, const std::vector<TV> &coeff, const std::vector<TI> &inds,
                 std::vector<key_type> &tmp)

inline void scale_inplace(const std::vector<TV> &coeff)

inline void scale_inplace(const TV c)

inline SparseVector scale(const TV c) const

inline void print() const

inline void print_row() const

template<typename IO>
inline void write(IO &io) const

inline std::string str()

inline SparseVector kron(const SparseVector &other, size_t m) const

inline SparseVector tensor(const SparseVector &other, size_t m) const
```

Public Static Functions

```
static inline SparseVector random(size_t n, double p, int maxval, std::default_random_engine &generator)

static inline SparseVector random(size_t n, double p, int maxval)
```

Template Class UnivariatePolynomial

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_polynomial.hpp

Class Documentation

```
template<typename T>
```

```
class UnivariatePolynomial
```

Public Functions

```
inline UnivariatePolynomial(const std::vector<T> &c)
```

```
inline UnivariatePolynomial(std::initializer_list<T> l)
```

```
inline UnivariatePolynomial(const T &c0)
```

```
inline UnivariatePolynomial()
```

```
inline bool is_zero() const
```

```
template<typename TI>
```

```
inline const T operator[](const TI i) const
```

```
template<typename TI>
```

```
inline T &operator[](const TI i)
```

```
inline size_t dim() const
```

```
inline size_t degree() const
```

```
inline size_t size() const
```

```
inline T leading_coeff() const
```

```
inline T operator()(const T &v) const
```

```
template<typename TC>
```

```
inline TC operator()(const ColumnMatrix<TC> &A, const TC &v) const
```

```
inline UnivariatePolynomial operator-() const
```

```
inline UnivariatePolynomial operator+(const UnivariatePolynomial &other) const
```

```
inline UnivariatePolynomial &operator+=(const UnivariatePolynomial &other)
```

```
inline UnivariatePolynomial &operator-=(const UnivariatePolynomial &other)
```

Basic Applied Topology Subprograms

```
inline UnivariatePolynomial operator-(const UnivariatePolynomial &other) const  
  
inline UnivariatePolynomial operator*(const UnivariatePolynomial &other) const  
  
inline std::tuple<UnivariatePolynomial, UnivariatePolynomial> divrem(const UnivariatePolynomial &other)  
    const  
  
inline UnivariatePolynomial operator/(const UnivariatePolynomial &other) const  
  
inline UnivariatePolynomial remainder(const UnivariatePolynomial &other) const  
  
template<typename T2>  
inline bool operator==(const T2 &other) const  
  
inline bool operator==(const UnivariatePolynomial &other) const  
  
template<typename T2>  
inline bool operator!=(const T2 &other) const  
  
inline bool operator!=(const UnivariatePolynomial &other) const  
  
inline UnivariatePolynomial gcd(const UnivariatePolynomial &other) const  
  
inline bool is_monic() const  
  
inline ColumnMatrix<SparseVector<T>> companion_matrix() const  
  
inline void print()
```

Public Static Functions

```
static inline UnivariatePolynomial identity()  
  
static inline UnivariatePolynomial zero()  
  
static inline UnivariatePolynomial monomial(size_t d, T scale = T(1))
```

Friends

```
inline friend friend std::ostream & operator<< (std::ostream &os,  
const UnivariatePolynomial &p)
```

Functions

Function apply_inverse

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Function Documentation

MAT **apply_inverse**(*MAT*, *MAT*)

Function apply_inverse_on_left(*L<SI>*, *L<SI>*)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

L<SI> **apply_inverse_on_left**(*L<SI>* a, *L<SI>* b)

Function apply_inverse_on_left(*U<SI>*, *U<SI>*)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

U<SI> **apply_inverse_on_left**(*U<SI>* a, *U<SI>* b)

Function apply_inverse_on_left(*L<SI>*, *A<SI>*)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

A<*SI*> **apply_inverse_on_left**(*L*<*SI*> a, *A*<*SI*> b)

Function **apply_inverse_on_left(U<SI>, A<SI>)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

A<*SI*> **apply_inverse_on_left**(*U*<*SI*> a, *A*<*SI*> b)

Function **apply_inverse_on_right(L<SI>, L<SI>)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

L<*SI*> **apply_inverse_on_right**(*L*<*SI*> a, *L*<*SI*> b)

Function **apply_inverse_on_right(U<SI>, U<SI>)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

U<*SI*> **apply_inverse_on_right**(*U*<*SI*> a, *U*<*SI*> b)

Function **apply_inverse_on_right(A<SI>, L<SI>)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

A<*SI*> **apply_inverse_on_right**(*A*<*SI*> a, *L*<*SI*> b)

Function apply_inverse_on_right(A<SI>, U<SI>)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

A<*SI*> **apply_inverse_on_right**(*A*<*SI*> *a*, *U*<*SI*> *b*)

Template Function bats::__ChainComplex(const CpxT&, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_chain_complex.hpp

Function Documentation

```
template<typename T, typename CpxT>
inline auto bats::__ChainComplex(const CpxT &X, T)
```

Template Function bats::__ChainComplex(const CpxT&, const CpxT&, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_chain_complex.hpp

Function Documentation

```
template<typename T, typename CpxT>
inline auto bats::__ChainComplex(const CpxT &X, const CpxT &A, T)
```

Template Function bats::__ChainFunctor

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename DT, typename T>
inline auto bats::__ChainFunctor(const DT &D, T)
```

Template Function `bats::__CochainComplex`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_cochain_complex.hpp`

Function Documentation

```
template<typename T, typename CpxT>
inline auto bats::__CochainComplex(const CpxT &X, T)
```

Template Function `bats::__FilteredChainComplex`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_filtered_chain_complex.hpp`

Function Documentation

```
template<typename FT, typename T, typename CpxT>
inline auto bats::__FilteredChainComplex(const Filtration<FT, CpxT> &F, T)
```

Template Function `bats::__ReducedChainComplex`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_basis.hpp`

Function Documentation

```
template<typename T, typename CpxT, typename ...Args>
inline auto bats::__ReducedChainComplex(const CpxT &F, T, Args... args)
```

Template Function `bats::__ReducedCochainComplex`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_cohom_basis.hpp`

Function Documentation

```
template<typename T, typename CpxT, typename ...Args>
inline auto bats::__ReducedCochainComplex(const CpxT &F, T, Args... args)
```

Template Function bats::__ReducedFilteredChainComplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtered_basis.h

Function Documentation

```
template<typename FT, typename T, typename CpxT, typename ...Args>
inline auto bats::__ReducedFilteredChainComplex(const Filtration<FT, CpxT> &F, T, Args... args)
```

Template Function bats::add_dimension_recursive_flag(Filtration<T, CpxT>&, const NT&, const size_t, const size_t, const std::vector<size_t>&, std::vector<size_t>&, const T&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Function Documentation

```
template<typename CpxT, typename T, typename NT>
void bats::add_dimension_recursive_flag(Filtration<T, CpxT> &F, const NT &nbrs, const size_t d, const
                                         size_t maxd, const std::vector<size_t> &iter_idxs,
                                         std::vector<size_t> &spx_ids, const T &t)
```

Template Function bats::add_dimension_recursive_flag(Filtration<T, CpxT>&, const NT&, const size_t, const size_t, const std::vector<size_t>&, std::vector<size_t>&, const T&, bool, const cell_ind&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Function Documentation

```
template<typename CpxT, typename T, typename NT>
void bats::add_dimension_recursive_flag(Filtration<T, CpxT> &F, const NT &nbrs, const size_t d, const
                                         size_t maxd, const std::vector<size_t> &iter_idxs,
                                         std::vector<size_t> &spx_ids, const T &t, bool face_paired,
                                         const cell_ind &fi)
```

Template Function bats::add_dimension_recursive_flag(CpxT&, const NT&, const size_t, const size_t, const std::vector<size_t>&, std::vector<size_t>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_flag.hpp

Function Documentation

```
template<typename CpxT, typename NT>
void bats::add_dimension_recursive_flag(CpxT &X, const NT &nbrs, const size_t d, const size_t maxd,
                                         const std::vector<size_t> &iter_idxxs, std::vector<size_t>
                                         &spx_idxxs)
```

Template Function bats::add_dimension_recursive_flag_extension

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Function Documentation

```
template<typename CpxT, typename T, typename NT>
void bats::add_dimension_recursive_flag_extension(Filtration<T, CpxT> &F, const NT &nbrs, const
                                                 size_t d, const size_t maxd, const std::vector<size_t>
                                                 &iter_idxxs, std::vector<size_t> &spx_idxxs, const T
                                                 &t, const size_t index_of_edge,
                                                 std::vector<std::vector<size_t>> &inds)
```

Template Function bats::add_dimension_recursive_flag_unsafe

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Function Documentation

```
template<typename CpxT, typename T, typename NT>
void bats::add_dimension_recursive_flag_unsafe(Filtration<T, CpxT> &F, const NT &nbrs, const size_t
                                               d, const size_t maxd, const std::vector<size_t>
                                               &iter_idxxs, std::vector<size_t> &spx_idxxs, const T t)
```

Function bats::add_dimension_recursive_nerve

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_nerve.hpp

Function Documentation

```
void bats::add_dimension_recursive_nerve(SimplicialComplex &N, std::vector<size_t> spx, const
                                         bats::Cover &cover, std::vector<size_t> intersection, const size_t
                                         dmax)
```

Template Function `bats::add_normal_noise(Matrix<T>&, const T, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
Matrix<T> &bats::add_normal_noise(Matrix<T> &X, const T mu = T(0), const T sigma = T(1))
```

Template Function `bats::add_normal_noise(Matrix<T>&, unsigned, const T, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
Matrix<T> &bats::add_normal_noise(Matrix<T> &X, unsigned seed, const T mu = T(0), const T sigma =
T(1))
```

Template Function `bats::add_normal_noise(DataSet<T>&, const T, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
inline DataSet<T> &bats::add_normal_noise(DataSet<T> &X, const T mu = T(0), const T sigma = T(1))
```

Template Function `bats::add_normal_noise(DataSet<T>&, unsigned, const T, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
inline DataSet<T> &bats::add_normal_noise(DataSet<T> &X, unsigned seed, const T mu = T(0), const T
sigma = T(1))
```

Template Function `bats::add_uniform_noise(Matrix<T>&, unsigned, const T, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
Matrix<T> &bats::add_uniform_noise(Matrix<T> &X, unsigned seed, const T lb = T(0), const T ub = T(1))
```

Template Function `bats::add_uniform_noise(Matrix<T>&, const T, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
inline Matrix<T> &bats::add_uniform_noise(Matrix<T> &X, const T lb = T(0), const T ub = T(1))
```

Template Function `bats::add_uniform_noise(DataSet<T>&, const T, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
inline DataSet<T> &bats::add_uniform_noise(DataSet<T> &X, const T lb = T(-1), const T ub = T(1))
```

Function `bats::all_pairs`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
std::vector<size_t> bats::all_pairs(const size_t n)
```

Template Function `bats::approx_center`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_landmark.hpp

Function Documentation

```
template<typename T, typename M>
size_t bats::approx_center(const DataSet<T> &D, const M &dist, size_t k = 0, size_t i0 = 0)
```

Template Function `bats::assign_set_lower`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
template<typename T>
int bats::assign_set_lower(const T v, const T min_val, const double bin_width, const size_t nsets)
```

Template Function `bats::assign_set_upper`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
template<typename T>
int bats::assign_set_upper(const T v, const T min_val, const double bin_width, const size_t nsets)
```

Template Function `bats::barcode(const Diagram<NT, TM>&, size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
inline auto bats::barcode(const Diagram<NT, TM> &dgm, size_t hdim)
    Compute barcode from diagram of vector spaces and linear maps
    Uses divide and conquer algorithm by default.
```

Template Function `bats::barcode(const Diagram<NT, TM>&, size_t, flags::divide_conquer)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
inline auto bats::barcode(const Diagram<NT, TM> &dgm, size_t hdim, flags::divide_conquer)
    Compute barcode from diagram of vector spaces and linear maps
    Uses divide and conquer algorithm
```

Template Function `bats::barcode(const Diagram<NT, TM>&, size_t, flags::leftward)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
inline auto bats::barcode(const Diagram<NT, TM> &dgm, size_t hdim, flags::leftward)
    Compute barcode from diagram of vector spaces and linear maps
    Uses rightward algorithm (sweeps right to left)
```

Template Function `bats::barcode(const Diagram<NT, TM>&, size_t, flags::rightward)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
inline auto bats::barcode(const Diagram<NT, TM> &dgm, size_t hdim, flags::rightward)
    Compute barcode from diagram of vector spaces and linear maps
    Uses leftward algorithm (sweeps left to right)
```

Template Function `bats::barcode(const Diagram<NT, std::vector<TM>>&, Args ...)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM, typename ...Args>
inline auto bats::barcode(const Diagram<NT, std::vector<TM>> &dgm, Args... args)
    Compute barcode in all dimensions of diagram
```

Template Function bats::barcode_equality

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_barcode.hpp

Function Documentation

```
template<typename T>
bool bats::barcode_equality(const std::vector<PersistencePair<T>> &ps1, const
                           std::vector<PersistencePair<T>> &ps2)
```

Template Function bats::barcode_form_divide_conquer

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
auto bats::barcode_form_divide_conquer(const Diagram<NT, TM> &dgm)
```

Template Function bats::barcode_form_leftright

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
auto bats::barcode_form_leftright(const Diagram<NT, TM> &dgm)
```

Template Function bats::barcode_form_rightleft

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
auto bats::barcode_form_rightleft(const Diagram<NT, TM> &dgm)
```

Template Function bats::barcode_from_barcode_form

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename TN, typename TM>
std::vector<bar> bats::barcode_from_barcode_form(const std::vector<TM> &mat, const Diagram<TN, TM>
&dgm)
```

Function bats::bars_to_pairs

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
std::vector<PersistencePair<size_t>> bats::bars_to_pairs(const std::vector<bar> &bars, size_t hdim)
```

Function bats::bivariate_cover

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
auto bats::bivariate_cover(const std::vector<std::set<size_t>> &cover1, const std::vector<std::set<size_t>>
&cover2)
```

Template Function bats::Chain(const CpxT&, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_chain_complex.hpp

Function Documentation

```
template<typename T, typename CpxT>
inline auto bats::Chain(const CpxT &X, T)
```

Template Function bats::Chain(const CpxT&, const CpxT&, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_chain_complex.hpp

Function Documentation

```
template<typename T, typename CpxT>
inline auto bats::Chain(const CpxT &X, const CpxT &A, T)
```

Template Function bats::Chain(const CellularMap&, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_chain_map.hpp

Function Documentation

```
template<typename T>
inline auto bats::Chain(const CellularMap &F, T)
```

Template Function bats::Chain(const Filtration<FT, CpxT>&, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_chain_filtered_chain_compt.hpp

Function Documentation

```
template<typename FT, typename T, typename CpxT>
inline auto bats::Chain(const Filtration<FT, CpxT> &F, T)
```

Template Function bats::Chain(const Diagram<CpxT, CellularMap>&, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename CpxT, typename T>
inline auto bats::Chain(const Diagram<CpxT, CellularMap> &D, T)
```

Template Function bats::ChainFunctor(const DT&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename TM, typename DT>
Diagram<ChainComplex<TM>, ChainMap<TM>> bats::ChainFunctor(const DT &D)
```

Template Function bats::ChainFunctor(const DT&, TF)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename TF, typename DT>
inline auto bats::ChainFunctor(const DT &D, TF)
```

Template Function bats::circle

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::circle(const T rad, const size_t n)
```

Template Function bats::CompleteFlagFiltration

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Function Documentation

```
template<typename T>
std::tuple<SimplicialComplex, Filtration<T, SimplicialComplex>> bats::CompleteFlagFiltration(const
    std::vector<size_t>
    &edges,
    const
    std::vector<T>
    &t, const
    size_t n,
    const size_t
    maxdim,
    const T t0)
```

Template Function bats::coordinate_projection

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
template<typename T>
std::vector<T> bats::coordinate_projection(const DataSet<T> &X, const size_t i)
```

Function bats::Cube(size_t, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

CubicalComplex bats::**Cube**(size_t m, size_t n)
Cubical complex on 2-dimensional grid on m x n vertices

Function bats::Cube(size_t, size_t, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

CubicalComplex bats::**Cube**(size_t n1, size_t n2, size_t n3)
Cubical complex on 3-dimensional grid on n1 x n2 x n3 vertices

Basic Applied Topology Subprograms

Function `bats::Cube(size_t, size_t, size_t, size_t, size_t, size_t, size_t, size_t, size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

CubicalComplex `bats::Cube(size_t n1, size_t n2, size_t n3, size_t i0, size_t i1, size_t j0, size_t j1, size_t k0, size_t k1)`

Subset of Cubical complex of 3-dimensional grid on $n_1 \times n_2 \times n_3$ vertices

This function is useful for constructing zigzags through a grid

Parameters

- `n1` – grid size in 1st index
- `n2` – grid size in 2nd index
- `n3` – grid size in 3rd index
- `i0` – start of first index
- `i1` – end of first index
- `j0` – start of second index
- `j1` – end of second index
- `k0` – start of third index
- `k1` – end of third index

Function `bats::CubicalMap`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_cubical_map.hpp

Function Documentation

inline *CellularMap* `bats::CubicalMap(const CubicalComplex &X, const CubicalComplex &Y)`

Template Function `bats::detail::pivot_coeff`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<typename TVec>
auto bats::detail::pivot_coeff(const TVec &a, const TVec &b)
    Calculate
        Returns c coefficient for a += c*b
        Returns d difference in number of nonzeros of a using this coefficient
```

Template Function bats::DGLinearFunctor

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename TM, typename DT>
Diagram<DGVectorSpace<TM>, DGLinearMap<TM>> bats::DGLinearFunctor(const DT &D, int degree = -1)
    Functor from topological category to category of differential graded vector spaces
    Chain functor is degree = -1 (default) Cochain functor is degree = +1. This is contravariant (reverses arrows)
```

Template Function bats::DiscreteMorozovZigzag

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_zigzag_zoo.hpp

Function Documentation

```
template<typename T, typename M>
std::tuple<Diagram<SimplicialComplex, CellularMap>, std::vector<T>> bats::DiscreteMorozovZigzag(const
    DataSet<T>
    &D,
    const
    M
    &dist,
    T rho,
    size_t
    dmax)
```

Template Function bats::DiscreteMorozovZigzagSets

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_zigzag_zoo.hpp

Function Documentation

```
template<typename T, typename M>
std::tuple<Diagram<std::set<size_t>, std::vector<size_t>, std::vector<T>> bats::DiscreteMorozovZigzagSets(const
DataSet<T>
&D,
const
M
&dist,
T
rho)
```

Template Function `bats::dowker_edge_param(const Matrix<T>&, const size_t, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T>
T bats::dowker_edge_param(const Matrix<T> &pdist, const size_t i, const size_t j)
```

Template Function `bats::dowker_edge_param(const Matrix<T>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T>
Matrix<T> bats::dowker_edge_param(const Matrix<T> &pdist)
```

Template Function `bats::dowker_filtration_edges`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker_cover.hpp

Function Documentation

```
template<typename T>
std::vector<filtered_edge<T>> bats::dowker_filtration_edges(const Matrix<T> &pdist, const bats::Cover
&cover, const T rmax)
```

Template Function `bats::DowkerFiltration(const Matrix<T>&, T, size_t)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp`

Function Documentation

```
template<typename T>
Filtration<T, SimplicialComplex> bats::DowkerFiltration(const Matrix<T> &pdist, T rmax, size_t dmax)
```

Template Function `bats::DowkerFiltration(const DataSet<T>&, const DataSet<T>&, const M&, T, size_t)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp`

Function Documentation

```
template<typename T, typename M>
Filtration<T, SimplicialComplex> bats::DowkerFiltration(const DataSet<T> &L, const DataSet<T> &X,
                                                       const M &dist, T rmax, size_t dmax)
```

Template Function `bats::DowkerFiltration(const Matrix<T>&, const bats::Cover&, T, size_t)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker_cover.hpp`

Function Documentation

```
template<typename T>
Filtration<T, SimplicialComplex> bats::DowkerFiltration(const Matrix<T> &pdist, const bats::Cover &cover,
                                                       T rmax, size_t dmax)
```

Template Function `bats::DowkerFiltration(const DataSet<T>&, const DataSet<T>&, const M&, const bats::Cover&, T, size_t)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker_cover.hpp`

Function Documentation

```
template<typename T, typename M>
Filtration<T, SimplicialComplex> bats::DowkerFiltration(const DataSet<T> &L, const DataSet<T> &X,
                                                       const M &dist, const bats::Cover &cover, T rmax,
                                                       size_t dmax)
```

Template Function bats::EilenbergZilber(const CpxT&, const CpxT&, const size_t, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_eilenberg_zilber.h

Function Documentation

```
template<typename CpxT, typename T>
auto bats::EilenbergZilber(const CpxT &X, const CpxT &Y, const size_t maxdim, T)
```

Template Function bats::EilenbergZilber(const CpxT&, const CpxT&, const CpxT&, const CpxT&, const size_t, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_eilenberg_zilber.h

Function Documentation

```
template<typename CpxT, typename T>
auto bats::EilenbergZilber(const CpxT &X, const CpxT &A, const CpxT &Y, const CpxT &B, const size_t
                           maxdim, T)
```

Template Function bats::enclosing_radius

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_metric.hpp

Function Documentation

```
template<typename T>
T bats::enclosing_radius(const Matrix<T> &D)
compute the enclosing radius from matrix of pairwise distances
this is the minimum of the largest entry of each row
```

Template Function `bats::euclidean`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
template<typename T, typename TI>
T bats::euclidean(TI a, TI b, size_t d)
```

Function `bats::extension_perm`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
std::vector<size_t> bats::extension_perm(const std::vector<size_t> &perm, const size_t &length)
```

Template Function `bats::extract_basis_indices(const MT&, const std::vector<size_t>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<typename MT>
std::vector<size_t> bats::extract_basis_indices(const MT &Rk, const std::vector<size_t> &p2ck1)
```

Template Function `bats::extract_basis_indices(const MT&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<typename MT>
std::vector<size_t> bats::extract_basis_indices(const MT &Rk)
```

Template Function `bats::extract_dimension`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TM>
auto bats::extract_dimension(const Diagram<NT>, std::vector<TM>& D, size_t k)
    extracts dimension k from a diagram with stacked dimensions
```

Function `bats::filtration_iperm`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_filtration.hpp

Function Documentation

```
std::vector<std::vector<size_t>> bats::filtration_iperm(const std::vector<std::vector<size_t>> &perms)
```

Template Function `bats::filtration_sortperm(const std::vector<T>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_filtration.hpp

Function Documentation

```
template<typename T>
inline std::vector<size_t> bats::filtration_sortperm(const std::vector<T> &v)
```

Template Function `bats::filtration_sortperm(const std::vector<std::vector<T>>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_filtration.hpp

Function Documentation

```
template<typename T>
std::vector<std::vector<size_t>> bats::filtration_sortperm(const std::vector<std::vector<T>> &v)
```

Template Function `bats::find_perm_from_vector`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::find_perm_from_vector(const std::vector<T> &v)
```

Template Function `bats::flag_filtration_edges`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T>
std::vector<filtered\_edge<T>> bats::flag_filtration_edges(const Matrix<T> &pdist, const T rmax)
```

Template Function `bats::FlagComplex`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_flag.hpp

Function Documentation

```
template<typename CpxT>
CpxT bats::FlagComplex(const std::vector<size_t> &edges, const size_t n, const size_t maxdim)
```

Template Function `bats::FlagFiltration`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Function Documentation

```
template<typename CpxT, typename T>
Filtration<T, CpxT> bats::FlagFiltration(std::vector<filtered\_edge<T>> &edges, const size_t n, const size_t maxdim, const T t0)
```

Template Function `bats::FlagFiltration_extension`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_flag.hpp

Function Documentation

```
template<typename CpxT, typename T>
auto bats::FlagFiltration_extension(std::vector<filtered_edge<T>> &edges, const size_t n, const size_t
maxdim, const T t0)
```

Template Function `bats::force_repel_rp`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_spherical.hpp

Function Documentation

```
template<typename T>
void bats::force_repel_rp(DataSet<T> &v, T step_max)
```

Template Function `bats::Freudenthal(size_t, size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

```
template<typename CpxT>
CpxT bats::Freudenthal(size_t m, size_t n)
Freudenthal triangulation of 2-dimensional grid on m x n vertices
```

The grid is indexed in row-major order. The index for vertex (i, j) is j + n * i

Parameters

- m – number of rows
- n – number of columns

Template Function bats::Freudenthal(size_t, size_t, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

```
template<typename CpxT>
CpxT bats::Freudenthal(size_t n1, size_t n2, size_t n3)
    Freudenthal triangulation of 3-dimensional grid on n1 x n2 x n3 vertices
```

The grid is indexed in row-major order. The index for vertex (i, j, k) is $k + n2 * (j + n1 * i)$

Parameters

- n1** – grid size in 1st index
- n2** – grid size in 2nd index
- n3** – grid size in 3rd index

Template Function bats::Freudenthal(size_t, size_t, size_t, size_t, size_t, size_t, size_t, size_t, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

```
template<typename CpxT>
CpxT bats::Freudenthal(size_t n1, size_t n2, size_t n3, size_t i0, size_t i1, size_t j0, size_t j1, size_t k0, size_t k1)
    Subset of Freudenthal triangulation of 3-dimensional grid on n1 x n2 x n3 vertices
```

The grid is indexed in row-major order. The index for vertex (i, j, k) is $k + n2 * (j + n1 * i)$

This function is useful for constructing zigzags through a grid

Parameters

- n1** – grid size in 1st index
- n2** – grid size in 2nd index
- n3** – grid size in 3rd index
- i0** – start of first index
- i1** – end of first index
- j0** – start of second index
- j1** – end of second index
- k0** – start of third index
- k1** – end of third index

Template Function `bats::Freudenthal(const CubicalComplex&, size_t, size_t, size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

```
template<typename CpxT>
CpxT bats::Freudenthal(const CubicalComplex &X, size_t n1, size_t n2, size_t n3)
    Freudenthal Triangulation of CubicalComplex
```

Parameters

- `X` – cubical complex
- `n1` – 1st dimension grid size
- `n2` – 2nd dimension grid size
- `n3` – 3rd dimension grid size

Template Function `bats::future::find_pivot_complete`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT>
std::pair<size_t, size_t> bats::future::find_pivot_complete(const MT &A, size_t k)
```

Template Function `bats::future::find_pivot_high(const RandomAccessIterator&, ssize_t, ssize_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_util.hpp

Function Documentation

```
template<typename RandomAccessIterator>
ssize_t bats::future::find_pivot_high(const RandomAccessIterator &v, ssize_t start, ssize_t end)
```

Template Function `bats::future::find_pivot_high(const RandomAccessIterator&, ssize_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_util.hpp

Function Documentation

```
template<typename RandomAccessIterator>
inline ssize_t bats::future::find_pivot_high(const RandomAccessIterator &v, ssize_t end)
```

Template Function bats::future::gemm

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Function Documentation

```
template<typename M1, typename M2>
auto bats::future::gemm(const M1 &A, const M2 &B)
```

Template Function bats::future::gemv(const MT&, const VT&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Function Documentation

```
template<typename MT, typename VT>
auto bats::future::gemv(const MT &A, const VT &x)
```

Template Function bats::future::gemv(const MT&, const VT1&, VT2&&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_dense.hpp

Function Documentation

```
template<typename MT, typename VT1, typename VT2>
VT2 &bats::future::gemv(const MT &A, const VT1 &x, VT2 &&y)
```

Template Function bats::future::l_residual(const MT&, l1&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT, typename I1>
bool bats::future::l_residual(const MT &L, I1 &y)
```

Template Function bats::future::l_residual(const MT&&, I1&&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT, typename I1>
bool bats::future::l_residual(const MT &&L, I1 &&y)
```

Template Function bats::future::l_solve(const MT&, I1&, I2&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT, typename I1, typename I2>
bool bats::future::l_solve(const MT &L, I1 &y, I2 &x)
```

Template Function bats::future::l_solve(const MT1&, const MT2&, I1&, I2&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT1, typename MT2, typename I1, typename I2>
bool bats::future::l_solve(const MT1 &Pt, const MT2 &L, I1 &y, I2 &x)
```

Template Function bats::future::LU

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT>
LUFact<MT> bats::future::LU(const MT &A0)
```

Function bats::future::operator<<(std::ostream&, const ElementaryPermutation&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_permutation.hpp

Function Documentation

```
std::ostream &bats::future::operator<<(std::ostream &os, const ElementaryPermutation &p)
```

Function bats::future::operator<<(std::ostream&, const CompositePermutation&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_permutation.hpp

Function Documentation

```
std::ostream &bats::future::operator<<(std::ostream &os, const CompositePermutation &p)
```

Template Function bats::future::unit_lower

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT>
MT bats::future::unit_lower(const MT &A)
```

Template Function bats::future::upper

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_future_lu.hpp

Function Documentation

```
template<typename MT>
MT bats::future::upper(const MT &A)
```

Function bats::gen_cylinder

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

DataSet<double> bats::gen_cylinder(const size_t n_len, const size_t n_cir, const double rad = 1.0)

Function bats::get_clearing_inds

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
std::vector<size_t> bats::get_clearing_inds(const std::vector<size_t> &p2c)
```

Template Function bats::get_compression_inds

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
std::vector<bool> bats::get_compression_inds(const ColumnMatrix<TVec> &R)
```

Template Function bats::get_dM_ZZ_inds

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_zigzag_zoo.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::get_dM_ZZ_inds(const std::vector<T> &hds, const T rho, const T theta)
determine set of indices to use for dM-ZZ construction
```

Parameters

- **hds** – hausdorff distance of each point to point set. assume in decreasing order.
- **rho** – rips multiplier - should be > 10 [OS15 thm 4.6]
- **theta** – depends on dimension of data. In $[0.5, 1/\sqrt{2})$ [OS15 eq. 1]
 - if unsure, set to 0.5 for finer discretization

Template Function bats::get_m

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T>
std::vector<T> bats::get_m(const Matrix<T> &pdist, size_t nu)
```

Template Function bats::get_subset

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::get_subset(const DataSet<T> &X, const std::set<size_t> &ind)
```

Template Function bats::greedy_landmarks

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_landmark.hpp

Function Documentation

```
template<typename T, typename M>
DataSet<T> bats::greedy_landmarks(const DataSet<T> &D, const size_t k, const M &dist, const size_t i0 = 0)
```

Basic Applied Topology Subprograms

Template Function `bats::greedy_landmarks_hausdorff(const DataSet<T>&, const M&, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_landmark.hpp

Function Documentation

```
template<typename T, typename M>
std::tuple<std::vector<size_t>, std::vector<T>> bats::greedy_landmarks_hausdorff(const DataSet<T> &D,
                                                                 const M &dist, const
                                                                 size_t i0 = 0)
```

Template Function `bats::greedy_landmarks_hausdorff(const Matrix<T>&, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_landmark.hpp

Function Documentation

```
template<typename T>
std::tuple<std::vector<size_t>, std::vector<T>> bats::greedy_landmarks_hausdorff(const Matrix<T> &pdist,
                                                                 const size_t i0 = 0)
```

Template Function `bats::hausdorff_landmarks`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_landmark.hpp

Function Documentation

```
template<typename T, typename M>
DataSet<T> bats::hausdorff_landmarks(const DataSet<T> &D, const T r, const M &dist, const size_t i0 = 0)
```

Template Function `bats::Hom(const Diagram<ChainComplex<TM>, ChainMap<TM>>&, size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename TM>
Diagram<ReducedChainComplex<TM>, TM> bats::Hom(const Diagram<ChainComplex<TM>,
                                                 ChainMap<TM>> &D, size_t k)
```

Homology functor for dimension k template over matrix type

Template Function bats::Hom(const Diagram<ChainComplex<TM>, ChainMap<TM>>&, bool)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename TM>
Diagram<ReducedChainComplex<TM>, std::vector<TM>> bats::Hom(const Diagram<ChainComplex<TM>, ChainMap<TM>>& D, bool topd = false)
```

Homology functor in all dimensions template over matrix type

when topd is true, a k-dimensional Chain complex will be assumed to be 0 in dimension k+1 and H_k will be computed.

Assumes that all chain complexes have same dimension.

Parameters

- D – diagram of ChainComplexes and ChainMaps
- topd – (optional, default: false) if true will compute top dimensional homology.

Template Function bats::Hom(const Diagram<DGVectorSpace<TM>, DGLinearMap<TM>>&, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename TM>
Diagram<ReducedDGVectorSpace<TM>, TM> bats::Hom(const Diagram<DGVectorSpace<TM>, DGLinearMap<TM>>& D, size_t k)
```

Homology functor for dimension k template over matrix type

Function bats::identity_perm

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
std::vector<size_t> bats::identity_perm(const size_t &k)
```

Template Function bats::increment_m

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T>
std::vector<T> &bats::increment_m(const Matrix<T> &pdist, std::vector<T> &m)
```

Template Function bats::induced_map(const ChainMap<ColumnMatrix<TVec>>&, const ReducedChainComplex<ColumnMatrix<TVec>>&, const ReducedChainComplex<ColumnMatrix<TVec>>&, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_induced_map.hpp

Function Documentation

```
template<class TVec>
ColumnMatrix<TVec> bats::induced_map(const ChainMap<ColumnMatrix<TVec>> &F, const
                                         ReducedChainComplex<ColumnMatrix<TVec>> &C, const
                                         ReducedChainComplex<ColumnMatrix<TVec>> &D, size_t k)
```

Template Function bats::induced_map(const ChainMap<ColumnMatrix<TVec>>&, const ReducedCochainComplex<ColumnMatrix<TVec>>&, const ReducedCochainComplex<ColumnMatrix<TVec>>&, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_induced_map.hpp

Function Documentation

```
template<class TVec>
ColumnMatrix<TVec> bats::induced_map(const ChainMap<ColumnMatrix<TVec>> &F, const
                                         ReducedCochainComplex<ColumnMatrix<TVec>> &C, const
                                         ReducedCochainComplex<ColumnMatrix<TVec>> &D, size_t k)
```

obtain induced map on cohomology for dimension k

We assume that F is a chain map, so it is dualized before computing the map

Parameters

- F – *ChainMap*
- C – ReducedCoChainComplex
- D – ReducedCoChainComplex k dimension

```
Template Function bats::induced_map(const DGLinearMap<ColumnMatrix<TVec>>&, const ReducedDGVectorSpace<ColumnMatrix<TVec>>&, const ReducedDGVectorSpace<ColumnMatrix<TVec>>&, size_t)
```

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_induced_map.hpp

Function Documentation

```
template<class TVec>
ColumnMatrix<TVec> bats::induced_map(const DGLinearMap<ColumnMatrix<TVec>> &F, const ReducedDGVectorSpace<ColumnMatrix<TVec>> &C, const ReducedDGVectorSpace<ColumnMatrix<TVec>> &D, size_t k)
```

obtain induced map on cohomology for dimension k

We assume that F is a chain map, so it is dualized before computing the map

Parameters

- F** – *ChainMap*
- C** – ReducedCoChainComplex
- D** – ReducedCoChainComplex k dimension

Template Function bats::interval

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::interval(const T min, const T max, const size_t n)
```

Template Function bats::is_left_arrow

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename Edge>
inline bool bats::is_left_arrow(const Edge &e)
```

Template Function `bats::kdist`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_density.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<T> bats::kdist(const DataSet<T> &X, const M &dist, const size_t k)
```

Template Function `bats::kron_chain_shift`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_eilenberg_zilber.hpp

Function Documentation

```
template<typename ChainCpx>
size_t bats::kron_chain_shift(const size_t dx, const ChainCpx &CX, const size_t dy, const ChainCpx &CY)
```

Template Function `bats::kron_chains`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_eilenberg_zilber.hpp

Function Documentation

```
template<typename VT, typename ChainCpx>
auto bats::kron_chains(const VT &cx, const size_t dx, const ChainCpx &CX, const VT &cy, const size_t dy,
                        const ChainCpx &CY)
```

Template Function `bats::kron_homology`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_eilenberg_zilber.hpp

Function Documentation

```
template<typename ReducedCpx>
auto bats::kron_homology(const size_t dx, const ReducedCpx &RX, const size_t dy, const ReducedCpx &RY,
                           const ReducedCpx &RXRY)
```

Template Function `bats::kron_index`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_eilenberg_zilber.h

Function Documentation

```
template<typename CpxT>
std::vector<std::vector<size_t>> bats::kron_index(const CpxT &X, std::vector<std::vector<size_t>> &Ainds,
                                                     const CpxT &Y, std::vector<std::vector<size_t>> &Binds,
                                                     size_t maxdim)
```

Template Function `bats::landmark_cover`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
template<typename T, typename M>
bats::Cover bats::landmark_cover(const DataSet<T> &X, const DataSet<T> &L, const M &dist, size_t k)
```

Template Function `bats::landmark_eps_cover`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
template<typename T, typename M>
bats::Cover bats::landmark_eps_cover(const DataSet<T> &X, const DataSet<T> &L, const M &dist, T eps)
```

Function `bats::linear_cover_intersection_diagram`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_inclusion.hpp

Function Documentation

```
Diagram<std::set<size_t>, std::vector<size_t>> bats::linear_cover_intersection_diagram(std::vector<std::set<size_t>>
&cover)
```

Basic Applied Topology Subprograms

Function bats::linear_subset_union_diagram

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_inclusion.hpp

Function Documentation

```
Diagram<std::set<size_t>, std::vector<size_t>> bats::linear_subset_union_diagram(std::vector<std::set<size_t>>
&subsets)
```

Template Function bats::LowerStarFiltration

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_star.hpp

Function Documentation

```
template<class TC, typename TF>
Filtration<TC, TF> bats::LowerStarFiltration(TC cpx, std::vector<TF> f)
```

Template Function bats::make_edge

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
template<typename TF, typename TI>
inline tedge<TF, TI> bats::make_edge(TI s, TI t, TF v)
```

Template Function bats::mayer_vietoris_boundary

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_mayer_vietoris.hpp

Function Documentation

```
template<typename CpxT>
auto bats::mayer_vietoris_boundary(const CpxT &A, const CpxT &X, const CpxT &Y, size_t k)
```

Template Function bats::neighborhood(const VectorView<T>&, const DataSet<T>&, const M&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_neighborhood.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<size_t> bats::neighborhood(const VectorView<T> &x, const DataSet<T> &X, const M &dist, const
                                         T r)
```

Template Function bats::neighborhood(const VectorView<T>&, const DataSet<T>&, const M&, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_neighborhood.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<size_t> bats::neighborhood(const VectorView<T> &x, const DataSet<T> &X, const M &dist, const
                                         size_t k)
```

Template Function bats::neighborhoods(const DataSet<T>&, const DataSet<T>&, const M&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_neighborhood.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<std::vector<size_t>> bats::neighborhoods(const DataSet<T> &X, const DataSet<T> &Y, const M
                                                       &dist, const T r)
```

Template Function bats::neighborhoods(const DataSet<T>&, const DataSet<T>&, const M&, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_neighborhood.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<std::vector<size_t>> bats::neighborhoods(const DataSet<T> &X, const DataSet<T> &Y, const M
&dist, const size_t k)
```

Template Function bats::neighborhoods(const Matrix<T>&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_neighborhood.hpp

Function Documentation

```
template<typename T>
std::vector<std::set<size_t>> bats::neighborhoods(const Matrix<T> &pdist, const T eps = T(0))
```

Function bats::Nerve(const Diagram<bats::Cover, std::vector<size_t>>&, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
Diagram<SimplicialComplex, CellularMap> bats::Nerve(const Diagram<bats::Cover, std::vector<size_t>> &D,
const size_t dmax)
```

Function bats::Nerve(const bats::Cover&, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_nerve.hpp

Function Documentation

```
SimplicialComplex bats::Nerve(const bats::Cover &cover, const size_t dmax)
```

Template Function bats::normalize_entries

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_spherical.hpp

Function Documentation

```
template<typename T>
void bats::normalize_entries(DataSet<T> &data)
```

Template Function bats::operator<

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
template<typename TF, typename TI>
inline bool bats::operator<(const tedge<TF, TI> &a, const tedge<TF, TI> &b)
```

Template Function bats::operator<<

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
template<typename TF, typename TI>
std::ostream &bats::operator<<(std::ostream &os, tedge<TF, TI> &x)
```

Template Function bats::OscillatingRipsZigzagSets

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_zigzag_zoo.hpp

Function Documentation

```
template<typename T, typename M>
std::tuple<Diagram<std::set<size_t>, std::vector<size_t>>, std::vector<T>> bats::OscillatingRipsZigzagSets(const
                                                                 DataSet<T>
&D,
const
M
&dist,
T
rho,
T
eta)
```

Construct diagram of sets with a vector of Rips parameters

Creates this for Oscillating Rips Zigzag construction

Ref Oudot-Sheehy '15

Parameters

- **D** – data set
- **dist** – metric
- **rho** – multiplier
- **eta** – multiplier. Must have eta <= rho

Template Function `bats::pairwise_dist`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
template<typename T>
std::vector<T> bats::pairwise_dist(const std::vector<T> &x, const std::vector<size_t> &edges, const size_t d)
```

Template Function `bats::partial_reduce_parallel(ColumnMatrix<TVec> &, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<typename TVec>
void bats::partial_reduce_parallel(ColumnMatrix<TVec> &M, const size_t block_size)
    do an initial parallel sweep to zero out columns as possible
```

Parameters

- **M** – matrix to reduce
- **block_size** – size of column blocks to be processed in parallel

Template Function `bats::partial_reduce_parallel(ColumnMatrix<TVec> &, ColumnMatrix<TVec> &, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<typename TVec>
void bats::partial_reduce_parallel(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U, const size_t
    block_size)
    do an initial parallel sweep to zero out columns as possible
```

Parameters

- **M** – matrix to reduce
- **U** – change of basis

- **block_size** – size of column blocks to be processed in parallel

Template Function `bats::pass_L_left`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::pass_L_left(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts, ssize_t i)
```

Template Function `bats::pass_P_left`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::pass_P_left(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts, ssize_t i)
```

Template Function `bats::pass_P_right`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::pass_P_right(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts, ssize_t i)
```

Template Function `bats::pass_PL_left`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::pass_PL_left(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                      std::vector<TM> &mats, ssize_t i)
```

Template Function `bats::pass_U_right`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::pass_U_right(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts, ssize_t i)
```

Template Function `bats::pass_UP_right`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::pass_UP_right(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                        std::vector<TM> &mats, ssize_t i)
```

Function `bats::perm_to_the_end(const size_t&, const size_t&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
std::vector<size_t> bats::perm_to_the_end(const size_t &index, const size_t &length)
```

Function `bats::perm_to_the_end(const std::vector<size_t>&, const size_t&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
std::vector<size_t> bats::perm_to_the_end(const std::vector<size_t> &index_list, const size_t &length)
```

Template Function `bats::print_1D_vectors`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_print.hpp

Function Documentation

```
template<typename T>
void bats::print_1D_vectors(const T &perm)
```

Template Function `bats::print_2D_vectors`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_print.hpp

Function Documentation

```
template<typename T>
void bats::print_2D_vectors(const T &perms)
```

Template Function `bats::print_filtration_info`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_print.hpp

Function Documentation

```
template<class Filtration>
void bats::print_filtration_info(const Filtration &F)
```

Template Function `bats::print_simplex`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_print.hpp

Function Documentation

```
template<typename T>
void bats::print_simplex(const T &perm)
```

Template Function `bats::print_summary_of_filtration`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_print.hpp

Function Documentation

```
template<typename CpxT, typename T>
void bats::print_summary_of_filtration(const CpxT &X, std::function<T(const std::vector<size_t>&)>
&filtfn)
```

Function `bats::prod_ind`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_compl

Function Documentation

```
inline size_t bats::prod_ind(size_t i, size_t j, size_t n)
```

Template Function `bats::product_paths(CpxT&, iT, const iT, iT, const iT, std::vector<size_t>&, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_compl

Function Documentation

```
template<typename CpxT, typename iT>
void bats::product_paths(CpxT &XY, iT xit, const iT xend, iT yit, const iT yend, std::vector<size_t> &s,
const size_t n)
```

Template Function `bats::product_paths(CpxT&, iT, const iT, iT, const iT, std::vector<size_t>&, const size_t, std::vector<cell_ind>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_compl

Function Documentation

```
template<typename CpxT, typename iT>
void bats::product_paths(CpxT &XY, iT xit, const iT xend, iT yit, const iT yend, std::vector<size_t> &s,
const size_t n, std::vector<cell_ind> &ci)
```

Template Function `bats::product_space`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::product_space(const DataSet<T> &X, const DataSet<T> &Y)
```

Template Function `bats::random_landmarks`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_landmark.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::random_landmarks(const DataSet<T> &D, const size_t k)
```

Template Function `bats::read_point_cloud`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data.hpp

Function Documentation

```
template<typename T = double>
Matrix<T> bats::read_point_cloud(std::string &fname, bool header = false)
```

Template Function `bats::Reduce(const CpxT&, T, Args ...)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_basis.hpp

Function Documentation

```
template<typename T, typename CpxT, typename ...Args>
inline auto bats::Reduce(const CpxT &F, T, Args... args)
```

Template Function `bats::Reduce(const ChainComplex<MT>&, Args ...)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_basis.hpp

Function Documentation

```
template<typename MT, typename ...Args>
inline auto bats::Reduce(const ChainComplex<MT> &C, Args... args)
```

Template Function `bats::Reduce(const Filtration<FT, CpxT>&, T, Args ...)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtered_basis.hpp

Function Documentation

```
template<typename FT, typename T, typename CpxT, typename ...Args>
inline auto bats::Reduce(const Filtration<FT, CpxT> &F, T, Args... args)
```

Template Function `bats::Reduce(const FilteredChainComplex<T, MT>&, Args ...)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtered_basis.hpp

Function Documentation

```
template<typename T, typename MT, typename ...Args>
inline auto bats::Reduce(const FilteredChainComplex<T, MT> &C, Args... args)
```

Template Function `bats::reduce_block_dq(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, const size_t, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<typename TVec>
std::tuple<std::unordered_map<size_t, size_t>, std::vector<size_t>> bats::reduce_block_dq(ColumnMatrix<TVec>
&M, ColumnMatrix<TVec> &U,
const size_t j0,
const size_t j1,
const size_t max_block_size)
```

reduce a block of columns via divide and conquer

Parameters

- **M** – matrix to be reduced
- **U** – change of basis matrix
- **j0** – start of column range
- **j1** – upper bound of column range
- **max_block_size** – maximum block size for sequential base case

Returns p2c map from pivots to columns for this block

Returns nzcol vector of nonzero columns after reduction

Template Function bats::reduce_block_dq(ColumnMatrix<TVec>&, const size_t, const size_t, const size_t, const size_t, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<typename TVec>
std::tuple<std::unordered_map<size_t, size_t>, std::vector<size_t>> bats::reduce_block_dq(ColumnMatrix<TVec>
&M, const size_t
j0, const size_t j1,
const size_t
max_block_size,
const size_t level,
const size_t
max_depth)
```

reduce a block of columns via divide and conquer

Parameters

- **M** – matrix to be reduced
- **j0** – start of column range
- **j1** – upper bound of column range
- **max_block_size** – maximum block size for sequential base case

Returns p2c map from pivots to columns for this block

Returns nzcol vector of nonzero columns after reduction

Template Function bats::reduce_block_sequential(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<typename TVec>
std::tuple<std::unordered_map<size_t, size_t>, std::vector<size_t>> bats::reduce_block_sequential(ColumnMatrix<TVec>
&M,
Column-
Ma-
trix<TVec>
&U,
const
size_t j0,
const
size_t
j1)
```

reduce a block of columns sequentially

Parameters

- **M** – matrix to be reduced
- **U** – change of basis matrix
- **j0** – start of column range
- **j1** – upper bound of column range

Returns p2c map from pivots to columns for this block

Returns nzcol vector of nonzero columns after reduction

Template Function `bats::reduce_block_sequential(ColumnMatrix<TVec>&, const size_t, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<typename TVec>
std::tuple<std::unordered_map<size_t, size_t>, std::vector<size_t>> bats::reduce_block_sequential(ColumnMatrix<TVec>
&M,
const
size_t j0,
const
size_t
j1)
```

reduce a block of columns sequentially

Parameters

- **M** – matrix to be reduced
- **j0** – start of column range
- **j1** – upper bound of column range

Returns p2c map from pivots to columns for this block

Returns nzcol vector of nonzero columns after reduction

Template Function bats::reduce_column_extra

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<typename TVec>
void bats::reduce_column_extra(ColumnMatrix<TVec> &M, const size_t j, std::unordered_map<size_t,
size_t> &p2c, typename TVec::tmp_type &tmp)
    reduce a single column of the matrix M continue eliminating entries after finding pivot
```

assumes that p2c only contains columns < j

Parameters

- M** – matrix
- j** – column to reduce
- p2c** – map from pivots to columns
- tmp** – preallocated for faster axpys

Template Function bats::reduce_column_sparsify

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<typename TVec, typename F>
void bats::reduce_column_sparsify(ColumnMatrix<TVec> &M, const size_t j, std::vector<size_t>
&pivot_to_col, std::map<F, size_t> &coeff, typename TVec::tmp_type
&tmp)
```

greedily introduce sparsity into column j of M using columns k < j has the effect of reducing column j if not already reduced.

Parameters

- M** – matrix
- j** – column to reduce
- pivot_to_col** – maps pivots to columns
- coeff** – preallocated map to use when sparsifying.
- tmp** – preallocated to use with axpy

Template Function `bats::reduce_column_standard(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, std::unordered_map<size_t, size_t>&, typename TVec::tmp_type&)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp`

Function Documentation

```
template<typename TVec>
void bats::reduce_column_standard(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U, const size_t j,
                                  std::unordered_map<size_t, size_t> &p2c, typename TVec::tmp_type
                                  &tmp)
```

reduce a single column of the matrix M

assumes that p2c only contains columns < j

Parameters

- `M` – matrix
- `U` – change of basis matrix
- `j` – column to reduce
- `p2c` – map from pivots to columns
- `tmp` – preallocated for faster axpys

Template Function `bats::reduce_column_standard(ColumnMatrix<TVec>&, const size_t, std::unordered_map<size_t, size_t>&, typename TVec::tmp_type&)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp`

Function Documentation

```
template<typename TVec>
void bats::reduce_column_standard(ColumnMatrix<TVec> &M, const size_t j, std::unordered_map<size_t,
                                     size_t> &p2c, typename TVec::tmp_type &tmp)
```

reduce a single column of the matrix M

assumes that p2c only contains columns < j

Parameters

- `M` – matrix
- `j` – column to reduce
- `p2c` – map from pivots to columns
- `tmp` – preallocated for faster axpys

Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, divide_conquer_flag)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U,
                                                divide_conquer_flag)
```

Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, divide_conquer_flag)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_parallel.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M, divide_conquer_flag)
```

Template Function bats::reduce_matrix(ColumnMatrix<TVec>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M)
```

Template Function bats::reduce_matrix(ColumnMatrix<TVec>&, bats::standard_reduction_flag)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M, bats::standard_reduction_flag)
```

Template Function `bats::reduce_matrix(ColumnMatrix<TVec>&, bats::extra_reduction_flag)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M, bats::extra_reduction_flag)
```

Template Function `bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U)
```

Template Function `bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, bats::standard_reduction_flag)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U,
                                                bats::standard_reduction_flag)
```

Template Function `bats::reduce_matrix(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, bats::extra_reduction_flag)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
inline std::vector<size_t> bats::reduce_matrix(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U,
                                                bats::extra_reduction_flag)
```

Template Function bats::reduce_matrix_clearing

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec, typename flag>
std::vector<size_t> bats::reduce_matrix_clearing(ColumnMatrix<TVec> &M, const std::vector<size_t>
&clear_inds, flag)
```

Template Function bats::reduce_matrix_compression(ColumnMatrix<TVec>&, const std::vector<bool>&, flag)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec, typename flag>
std::vector<size_t> bats::reduce_matrix_compression(ColumnMatrix<TVec> &M, const std::vector<bool>
&comp_inds, flag)
```

Template Function bats::reduce_matrix_compression(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const std::vector<bool>&, flag)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec, typename flag>
std::vector<size_t> bats::reduce_matrix_compression(ColumnMatrix<TVec> &M, ColumnMatrix<TVec>
&U, const std::vector<bool> &comp_inds, flag)
```

Template Function bats::reduce_matrix_extra(ColumnMatrix<TVec>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
std::vector<size_t> bats::reduce_matrix_extra(ColumnMatrix<TVec> &M)
```

Template Function bats::reduce_matrix_extra(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
std::vector<size_t> bats::reduce_matrix_extra(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U)
```

Template Function bats::reduce_matrix_standard(ColumnMatrix<TVec>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
std::vector<size_t> bats::reduce_matrix_standard(ColumnMatrix<TVec> &M)
```

Template Function bats::reduce_matrix_standard(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
std::vector<size_t> bats::reduce_matrix_standard(ColumnMatrix<TVec> &M, ColumnMatrix<TVec> &U)
```

Template Function bats::remove_extra_cycles

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

```
template<class TVec>
void bats::remove_extra_cycles(const ColumnMatrix<TVec> &R, ColumnMatrix<TVec> &U)
    Update change of basis matrix to not be as dense by removing lower grade cycles from U.
```

Let $j_1 < j_2$, and $R[j_1] = 0$ Then, we can add a linear combination of $U[j_1]$ to $U[j_2]$ without changing the matrix invariant $B^*U = R$

Parameters

- R – reduced matrix
- U – change of basis matrix

Template Function bats::Rips(const Diagram<std::set<size_t>, std::vector<size_t>>&, const DataSet<T>&, const M&, const T, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename T, typename M>
Diagram<SimplicialComplex, CellularMap> bats::Rips(const Diagram<std::set<size_t>, std::vector<size_t>>& D,
                                                       const DataSet<T> &X, const M &dist, const T rmax, const size_t dmax)
```

Template Function bats::Rips(const Diagram<std::set<size_t>, std::vector<size_t>>&, const DataSet<T>&, const M&, const std::vector<T>&, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename T, typename M>
Diagram<SimplicialComplex, CellularMap> bats::Rips(const Diagram<std::set<size_t>, std::vector<size_t>>& D,
                                                       const DataSet<T> &X, const M &dist, const std::vector<T> &rmax, const size_t dmax)
```

Template Function bats::rips_edges(std::vector<T>&, std::vector<size_t>&, std::vector<T>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
template<typename T>
void bats::rips_edges(std::vector<T> &x, std::vector<size_t> &edges, std::vector<T> &t)
```

Template Function bats::rips_edges(const DataSet<T>&, const M&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<size_t> bats::rips_edges(const DataSet<T> &X, const M &dist, const T rmax)
```

Template Function bats::rips_edges(const Matrix<T>&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::rips_edges(const Matrix<T> &pdist, const T rmax)
```

Template Function bats::rips_filtration_edges(const DataSet<T>&, const M&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<filtered_edge<T>> bats::rips_filtration_edges(const DataSet<T> &X, const M &dist, const T
rmax)
```

Template Function bats::rips_filtration_edges(const Matrix<T>&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp

Function Documentation

```
template<typename T>
std::vector<filtered_edge<T>> bats::rips_filtration_edges(const Matrix<T> &pdist, const T rmax)
```

Template Function bats::rips_filtration_edges(const DataSet<T>&, const bats::Cover&, const M&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips_cover.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<filtered_edge<T>> bats::rips_filtration_edges(const DataSet<T> &X, const bats::Cover &cover, const M &dist, const T rmax)
```

Template Function bats::RipsComplex(const DataSet<T>&, const M&, T, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp

Function Documentation

```
template<typename CpxT, typename T, typename M>
CpxT bats::RipsComplex(const DataSet<T> &X, const M &dist, T rmax, size_t dmax)
```

Template Function bats::RipsComplex(const Matrix<T>&, T, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp

Function Documentation

```
template<typename CpxT, typename T>
CpxT bats::RipsComplex(const Matrix<T> &pdist, T rmax, size_t dmax)
```

Template Function `bats::RipsFiltration(const DataSet<T>&, const M&, T, size_t)`

- Defined in file `file__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp`

Function Documentation

```
template<typename CpxT, typename T, typename M>
Filtration<T, CpxT> bats::RipsFiltration(const DataSet<T> &X, const M &dist, T rmax, size_t dmax)
```

Template Function `bats::RipsFiltration(const Matrix<T>&, T, size_t)`

- Defined in file `file__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp`

Function Documentation

```
template<typename CpxT, typename T>
Filtration<T, CpxT> bats::RipsFiltration(const Matrix<T> &pdist, T rmax, size_t dmax)
```

Template Function `bats::RipsFiltration(const DataSet<T>&, const bats::Cover&, const M&, T, size_t)`

- Defined in file `file__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips_cover.hpp`

Function Documentation

```
template<typename T, typename M>
Filtration<T, SimplicialComplex> bats::RipsFiltration(const DataSet<T> &X, const bats::Cover &cover,
                                                       const M &dist, T rmax, size_t dmax)
```

Template Function `bats::RipsFiltration_extension(const DataSet<T>&, const M&, T, size_t)`

- Defined in file `file__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp`

Function Documentation

```
template<typename CpxT, typename T, typename M>
auto bats::RipsFiltration_extension(const DataSet<T> &X, const M &dist, T rmax, size_t dmax)
```

Template Function bats::RipsFiltration_extension(const Matrix<T>&, T, size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_rips.hpp

Function Documentation

```
template<typename CpxT, typename T>
auto bats::RipsFiltration_extension(const Matrix<T> &pdist, T rmax, size_t dmax)
```

Template Function bats::RipsHom

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_multigraph_functors.hpp

Function Documentation

```
template<typename T, typename M, typename FT>
auto bats::RipsHom(const Diagram<std::set<size_t>, std::vector<size_t> > &D, const DataSet<T> &X, const M
&dist, const std::vector<T> &rmax, const size_t hdim, FT)
```

Template Function bats::rowmajor::get_idx(T, T, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

```
template<typename T>
inline T bats::rowmajor::get_idx(T i, T j, T n)
Utility for translating to row-major index
```

Template Function bats::rowmajor::get_idx(T, T, T, T, T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_grid.hpp

Function Documentation

```
template<typename T>
inline T bats::rowmajor::get_idx(T i, T j, T k, T n1, T n2)
```

Template Function `bats::sample_cube(const size_t, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::sample_cube(const size_t d, const size_t n)
```

Template Function `bats::sample_cube(const size_t, const size_t, unsigned)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::sample_cube(const size_t d, const size_t n, unsigned seed)
```

Template Function `bats::sample_sphere`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data_gen.hpp

Function Documentation

```
template<typename T>
DataSet<T> bats::sample_sphere(const size_t d, const size_t n)
```

Function `bats::serpinski_diagram`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_extras.hpp

Function Documentation

```
Diagram<CellComplex, CellularMap> bats::serpinski_diagram(size_t k)
```

Template Function `bats::SimplicialMap(const CpxT&, const CpxT&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_map.hpp

Function Documentation

```
template<typename CpxT>
inline CellularMap bats::SimplicialMap(const CpxT &X, const CpxT &Y)
```

Template Function `bats::SimplicialMap(const CpxT&, const CpxT&, const std::vector<size_t>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_map.hpp

Function Documentation

```
template<typename CpxT>
CellularMap bats::SimplicialMap(const CpxT &X, const CpxT &Y, const std::vector<size_t> &f0)
```

Template Function `bats::sort_edges`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_rips.hpp

Function Documentation

```
template<typename T>
void bats::sort_edges(std::vector<size_t> &edges, std::vector<T> &v)
```

Template Function `bats::sort_indexes`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::sort_indexes(const std::vector<T> &v)
```

Basic Applied Topology Subprograms

Template Function `bats::sparsify_basis(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&, const size_t, std::map<F, size_t>&, typename TVec::tmp_type&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

template<typename **TVec**, typename **F**>
void **bats::sparsify_basis**(*ColumnMatrix<TVec> &R*, *ColumnMatrix<TVec> &U*, const *size_t j*, *std::map<F, size_t> &coeff*, typename *TVec::tmp_type &tmp*)
greedily introduce sparsity into columns j of *U* and R using columns k < j assumes columns k <= j are already reduced
objective to greedily minimize is $\text{nnz}(U[j]) + \text{nnz}(R[j])$

Parameters

- R** – reduced matrix
- U** – change of basis matrix
- j** – column
- coeff** – preallocated map to use when sparsifying.
- tmp** – preallocated to use with axpy

Template Function `bats::sparsify_basis(ColumnMatrix<TVec>&, ColumnMatrix<TVec>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Function Documentation

template<typename **TVec**>
void **bats::sparsify_basis**(*ColumnMatrix<TVec> &R*, *ColumnMatrix<TVec> &U*)
greedily introduce sparsity into columns of *U* and R assumes R is already reduced
objective to greedily minimize is $\text{nnz}(U[j]) + \text{nnz}(R[j])$

Parameters

- R** – reduced matrix
- U** – change of basis matrix

Template Function `bats::StrictWitnessComplex`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
SimplicialComplex bats::StrictWitnessComplex(const DataSet<T> &X, const DataSet<T> &L, const M
&dist, const size_t nu, const T rmax, const size_t dmax)
```

Template Function bats::test_reduce_result

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtered_basis.h

Function Documentation

```
template<typename T>
bool bats::test_reduce_result(const T &RFCC2, const T &RFCC)
```

Template Function bats::TriangulatedProduct(const CpxT&, const CpxT&, const size_t, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_compl

Function Documentation

```
template<typename CpxT>
CpxT bats::TriangulatedProduct(const CpxT &X, const CpxT &Y, const size_t maxdim, const size_t n)
```

Template Function bats::TriangulatedProduct(const CpxT&, const CpxT&, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_compl

Function Documentation

```
template<typename CpxT>
inline CpxT bats::TriangulatedProduct(const CpxT &X, const CpxT &Y, const size_t maxdim)
```

Template Function bats::TriangulatedProduct(const CpxT&, const CpxT&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_complex_simplicial_compl

Function Documentation

```
template<typename CpxT>
inline CpxT bats::TriangulatedProduct(const CpxT &X, const CpxT &Y)
```

Template Function bats::type_A_dq_common

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
ssize_t bats::type_A_dq_common(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                               std::vector<TM> &mats, ssize_t j0, ssize_t j1)
```

Template Function bats::type_A_dq_EL

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::type_A_dq_EL(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                        std::vector<TM> &mats, ssize_t j0, ssize_t j1)
```

Template Function bats::type_A_dq_EU

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::type_A_dq_EU(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                        std::vector<TM> &mats, ssize_t j0, ssize_t j1)
```

Template Function `bats::type_A_leftright_sweep1`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::type_A_leftright_sweep1(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                                    std::vector<TM> &mats, ssize_t j0, ssize_t j1)
```

Template Function `bats::type_A_leftright_sweep2`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::type_A_leftright_sweep2(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                                    ssize_t j0, ssize_t j1)
```

Template Function `bats::type_A_rightleft_sweep1`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::type_A_rightleft_sweep1(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                                    std::vector<TM> &mats, ssize_t j0, ssize_t j1)
```

Template Function `bats::type_A_rightleft_sweep2`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_quiver_sparse.hpp

Function Documentation

```
template<typename NT, typename TC, typename TM>
void bats::type_A_rightleft_sweep2(const Diagram<NT, TM> &dgm, std::vector<SparseFact<TC>> &facts,
                                    ssize_t j0, ssize_t j1)
```

Template Function `bats::uniform_interval_cover`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Function Documentation

```
template<typename T>
bats::Cover bats::uniform_interval_cover(const std::vector<T> &x, const size_t nsets)
```

Template Function `bats::util::apply_iperm_swap`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
inline void bats::util::apply_iperm_swap(std::vector<T> &data, const std::vector<size_t> &perm)
```

Template Function `bats::util::apply_perm(T, std::vector<T2>&, const std::vector<size_t>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T, typename T2>
void bats::util::apply_perm(T begin, std::vector<T2> &tmp, const std::vector<size_t> &perm)
```

Template Function `bats::util::apply_perm(T *, const std::vector<size_t>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
void bats::util::apply_perm(T *begin, const std::vector<size_t> &perm)
```

Template Function `bats::util::apply_perm(std::vector<T>&, const std::vector<size_t>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
inline void bats::util::apply_perm(std::vector<T> &data, const std::vector<size_t> &perm)
```

Template Function `bats::util::apply_perm_swap`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
inline void bats::util::apply_perm_swap(std::vector<T> &data, const std::vector<size_t> &perm)
```

Function `bats::util::fill_partial_sortperm`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
void bats::util::fill_partial_sortperm(const std::vector<size_t> &ind, const std::vector<size_t> &perm,
                                      std::vector<size_t> &indperm)
```

Template Function `bats::util::fill_sortperm(const T&, const T&, std::vector<size_t>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
void bats::util::fill_sortperm(const T &begin, const T &end, std::vector<size_t> &perm)
```

Template Function `bats::util::fill_sortperm(const std::vector<T>&, std::vector<size_t>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
inline void bats::util::fill_sortperm(const std::vector<T> &data, std::vector<size_t> &perm)
```

Template Function `bats::util::find_sorted_lt`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename T, typename TI>
size_t bats::util::find_sorted_lt(const TI &begin, const TI &end, const T &v)
```

Template Function `bats::util::firstk`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename TI>
std::vector<size_t> bats::util::firstk(const TI &begin, const TI &end, const size_t k)
```

Template Function `bats::util::has_intersect_sorted`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename C1, typename C2>
bool bats::util::has_intersect_sorted(const C1 &a, const C2 &b)
```

Template Function `bats::util::has_intersect_sorted_lt`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename T, typename C1, typename C2>
bool bats::util::has_intersect_sorted_lt(const C1 &a, const C2 &b, const T maxval)
```

Template Function `bats::util::intersect_sorted(const C1&, const C2&, std::vector<T>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename T, typename C1, typename C2>
void bats::util::intersect_sorted(const C1 &a, const C2 &b, std::vector<T> &c)
```

Template Function `bats::util::intersect_sorted(const C1&, const C2&, std::set<T>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename T, typename C1, typename C2>
void bats::util::intersect_sorted(const C1 &a, const C2 &b, std::set<T> &c)
```

Template Function `bats::util::intersect_sorted_lt`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename T, typename C1, typename C2>
void bats::util::intersect_sorted_lt(const C1 &a, const C2 &b, const T maxval, std::vector<T> &c)
```

Function bats::util::inv_perm

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
inline std::vector<size_t> bats::util::inv_perm(const std::vector<size_t> &p)
```

Template Function bats::util::io::parse_argv(const int, char **, const std::string&&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_io.hpp

Function Documentation

```
template<typename T>
T bats::util::io::parse_argv(const int argc, char **argv, const std::string &&token, const T default_return)
```

Function bats::util::io::parse_argv(const int, char **, const std::string&&, const std::string)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_io.hpp

Function Documentation

```
template<>
std::string bats::util::io::parse_argv(const int argc, char **argv, const std::string &&token, const std::string
default_return)
```

Template Function bats::util::is_degenerate

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_simplex.hpp

Function Documentation

```
template<typename T>
bool bats::util::is_degenerate(const std::vector<T> &s)
```

Function bats::util::partial_perm

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
std::vector<size_t> bats::util::partial_perm(const std::vector<size_t> &ind, const size_t n)
```

Template Function bats::util::perm_inversions

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
size_t bats::util::perm_inversions(const std::vector<T> &p)
```

Template Function bats::util::perm_sign

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
inline int bats::util::perm_sign(const std::vector<T> &p)
```

Function bats::util::rand_perm

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
std::vector<size_t> bats::util::rand_perm(const size_t n)
```

Function bats::util::random_subset

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_set.hpp

Function Documentation

```
std::set<size_t> bats::util::random_subset(const size_t n, const size_t ns)
```

Template Function bats::util::read_simplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_simplex.hpp

Function Documentation

```
template<typename T>
void bats::util::read_simplex(std::string &line, std::vector<T> &s)
```

Template Function bats::util::set_intersection

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_set.hpp

Function Documentation

```
template<typename C1, typename C2>
std::set<size_t> bats::util::set_intersection(const C1 &a, const C2 &b)
```

Template Function bats::util::set_union

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_set.hpp

Function Documentation

```
template<typename CT1, typename CT2>
std::set<size_t> bats::util::set_union(const CT1 &s1, const CT2 &s2)
```

Template Function `bats::util::simplex_sign`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_simplex.hpp

Function Documentation

```
template<typename T>
int bats::util::simplex_sign(std::vector<T> &s)
```

Function `bats::util::sort_ind_by_perm`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
inline void bats::util::sort_ind_by_perm(std::vector<size_t> &ind, const std::vector<size_t> &perm)
```

Function `bats::util::sort_ind_pair_by_perm`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
void bats::util::sort_ind_pair_by_perm(std::vector<size_t> &ind1, std::vector<size_t> &ind2, const
                                      std::vector<size_t> &perm)
```

Template Function `bats::util::sort_into`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename T>
void bats::util::sort_into(const std::vector<T> &x, std::vector<T> &y)
```

Template Function `bats::util::sort_sum_reduce`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename TI, typename TV>
void bats::util::sort_sum_reduce(std::vector<TI> &ind, std::vector<TV> &val, const size_t offset,
                                std::vector<size_t> &perm, std::vector<TI> &tmpind, std::vector<TV>
                                &tmpval)
```

Template Function `bats::util::sorted_complement`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_sorted.hpp

Function Documentation

```
template<typename T>
std::vector<T> bats::util::sorted_complement(const std::vector<T> &ind, size_t n)
```

Template Function `bats::util::sortperm(const std::vector<T>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::util::sortperm(const std::vector<T> &data)
```

Template Function `bats::util::sortperm(const TI&, const TI&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename TI>
std::vector<size_t> bats::util::sortperm(const TI &begin, const TI &end)
```

Template Function `bats::util::sortperm(RAI, RAI, Compare)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename RAI, class Compare>
std::vector<size_t> bats::util::sortperm(RAI first, RAI last, Compare comp)
fill a sortperm using custom comparator
```

Parameters

- first** – random acces iterator at beginning of range to sort
- last** – random access iterator just past the last element of range to sort
- comp** – comparison function, comp(a, b) should return whether a should come before b

Template Function `bats::util::sortperm(const size_t, const size_t, Compare)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<class Compare>
std::vector<size_t> bats::util::sortperm(const size_t first, const size_t last, Compare comp)
fill a sortperm using custom comparator
```

Parameters

- first** – random acces iterator at beginning of range to sort
- last** – random access iterator just past the last element of range to sort
- comp** – comparison function, comp(a, b) should return whether a should come before b

Template Function `bats::util::stable_sortperm`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::util::stable_sortperm(const std::vector<T> &data)
```

Template Function `bats::util::to_set`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_set.hpp

Function Documentation

```
template<typename T>
std::set<T> bats::util::to_set(const std::vector<T> &v)
```

Template Function `bats::util::top_k`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::util::top_k(const std::vector<T> &data, const size_t k)
```

Template Function `bats::util::top_p`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_permutation.hpp

Function Documentation

```
template<typename T>
std::vector<size_t> bats::util::top_p(const std::vector<T> &data, const double p)
```

Template Function `bats::util::write_simplex(IO&, std::vector<T>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_simplex.hpp

Function Documentation

```
template<typename IO, typename T>
void bats::util::write_simplex(IO &io, std::vector<T> &s)
```

Template Function `bats::util::write_simplex(IO&, TI&&, TI&&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_simplex.hpp

Function Documentation

```
template<typename IO, typename TI>
void bats::util::write_simplex(IO &io, TI &&begin, TI &&end)
```

Template Function `bats::vertex_inclusion_map`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_inclusion.hpp

Function Documentation

```
template<typename T1, typename T2>
std::vector<size_t> bats::vertex_inclusion_map(const T1 &s, const T2 &t)
```

Template Function `bats::witness_edge_param`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
Matrix<T> bats::witness_edge_param(const DataSet<T> &X, const DataSet<T> &L, const M &dist, const
size_t nu)
```

Template Function `bats::witness_edges(const DataSet<T>&, const DataSet<T>&, const M&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<size_t> bats::witness_edges(const DataSet<T> &X, const DataSet<T> &L, const M &dist)
```

Template Function `bats::witness_edges(const DataSet<T>&, const DataSet<T>&, const M&, const T)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
std::vector<size_t> bats::witness_edges(const DataSet<T> &X, const DataSet<T> &L, const M &dist, const T
                                         rmax)
```

Template Function `bats::witness_neighborhoods`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
inline auto bats::witness_neighborhoods(const DataSet<T> &X, const DataSet<T> &L, const M &dist, const
                                         size_t nu, const T rmax)
```

Template Function `bats::WitnessComplex(const DataSet<T>&, const DataSet<T>&, const M&, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
SimplicialComplex bats::WitnessComplex(const DataSet<T> &X, const DataSet<T> &L, const M &dist, const
                                         size_t dmax)
```

Template Function `bats::WitnessComplex(const DataSet<T>&, const DataSet<T>&, const M&, const size_t, const T, const size_t)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
SimplicialComplex bats::WitnessComplex(const DataSet<T> &X, const DataSet<T> &L, const M &dist, const
size_t nu, const T rmax, const size_t dmax)
```

Template Function bats::WitnessFiltration

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_dowker.hpp

Function Documentation

```
template<typename T, typename M>
Filtration<T, SimplicialComplex> bats::WitnessFiltration(const DataSet<T> &L, const DataSet<T> &X,
const M &dist, T rmax, size_t dmax)
```

Template Function bats::zigzag::barcode

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_zigzag_filtration.hpp

Function Documentation

```
template<typename CpxT, typename T, typename FT, typename opt_flag, typename reduction_flag>
auto bats::zigzag::barcode(const ZigzagFiltration<CpxT, T> &F, ssize_t maxdim, FT, opt_flag,
reduction_flag)
```

Template Function bats::zigzag::detail::apply_basis

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Function Documentation

```
template<typename MT>
void bats::zigzag::detail::apply_basis(MT &A, MT &L, MT &P, const bool prev_dir, const bool dir)
```

Template Function `bats::zigzag::detail::boundary_insertion_map`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Function Documentation

```
template<typename VecT>
ColumnMatrix<VecT> bats::zigzag::detail::boundary_insertion_map(const std::vector<size_t> &I, const
size_t i, const VecT &v)
```

Template Function `bats::zigzag::detail::cube_extrema`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_extension.hpp

Function Documentation

```
template<typename T>
std::pair<T, T> bats::zigzag::detail::cube_extrema(const std::vector<T> &f0, const std::vector<size_t>
&cube, const size_t n)
```

get maximum and minimum value of a function on cube vertices

Parameters

- f0** – function on vertices - in column-major order
- cube** – representation of cube, can be degenerate
- n** – length of 3D cube

Template Function `bats::zigzag::detail::cube_val`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_extension.hpp

Function Documentation

```
template<typename T>
inline T bats::zigzag::detail::cube_val(const std::vector<T> &f0, const size_t i, const size_t j, const size_t
k, const size_t n)
```

Template Function bats::zigzag::detail::cycle_insertion_map

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Function Documentation

```
template<typename VecT>
ColumnMatrix<VecT> bats::zigzag::detail::cycle_insertion_map(const std::vector<size_t> &I, const
size_t j)
```

Function bats::zigzag::detail::lex_cmp

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_zigzag_filtration.hpp

Function Documentation

```
bool bats::zigzag::detail::lex_cmp(const bats::SimplicialComplex &X, size_t dimi, size_t i, size_t dimj,
size_t j)
Compare simplices in lexicographical order looking at largest vertex first (v_0,...,v_p) < (w_0,...,w_q) if v_p
< w_q
```

compare simplex i in dimension dimi with simplex j in dimension dimj

Parameters

- X** – simplicial complex
- dimi** – dimension of first simplex
- i** – index of first simplex
- dimj** – dimension of second simplex
- j** – index of second simplex

Returns true if first simplex < second simplex, false otherwise

Function bats::zigzag::detail::rlex_cmp

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_zigzag_filtration.hpp

Function Documentation

```
bool bats::zigzag::detail::rlex_cmp(const bats::SimplicialComplex &X, size_t dimi, size_t i, size_t dimj,
size_t j)
```

Template Function `bats::zigzag::detail::simplex_extrema`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_extension.hpp

Function Documentation

```
template<typename T, typename Iterator>
std::pair<T, T> bats::zigzag::detail::simplex_extrema(Iterator it, const Iterator &end, const
                                                       std::vector<T> &f0)
```

Template Function `bats::zigzag::detail::update_bars`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Function Documentation

```
template<typename T, typename MT, typename Map>
void bats::zigzag::detail::update_bars(std::vector<ZigzagPair<T>> &bars, const rfilter_val<T> &fval,
                                       const size_t hdim, MT &E, Map &piv_to_ind, Map &piv_to_ind2)
    incrementally update barcode
    see quiver/sparse.hpp barcode_from_barcode_form
```

Template Function `bats::zigzag::extend_levelset`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_extension.hpp

Function Documentation

```
template<typename T>
std::vector<std::vector<std::pair<T, T>>> bats::zigzag::extend_levelset(const std::vector<T> &f0, const
                                                               CubicalComplex &X, const T eps,
                                                               const size_t n)
```

Extension of zigzag filtration on vertices to a zigzag filtration on a cubical complex. The filtration progresses from low to high values.

Parameters

- f0** – function on vertices - stored in column-major format
- X** – `CubicalComplex` - on a vertex set of size n^3
- eps** – thickened levelset radius
- n** – length of cube

Returns val vector of vector of pairs holding zigzag filtration values for each cube.

Template Function bats::zigzag::extend_zigzag_filtration(const std::vector<T>&, const CpxT&, const T)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_extension.hpp

Function Documentation

template<typename T, typename CpxT>

auto bats::zigzag::**extend_zigzag_filtration**(const std::vector<*T*> &f0, const *CpxT* &X, const *T* eps)

Extension of right filtration on 0-cells to right-filtration on all cells in a complex. Right filtration goes from low to high values

A 0-cell x enters the filtration at parameter f0(x) - eps and is removed from the filtration at parameter f0(x) + eps

Higher-dimensional cells are present for the interval that all faces are also present.

Parameters

- f0** – function on 0-cells
- X** – complex representing topological space
- eps** – thickened levelset radius

Template Function bats::zigzag::extend_zigzag_filtration(const std::vector<T>&, const CubicalComplex&, const T, const size_t)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_extension.hpp

Function Documentation

template<typename T>

ZigzagFiltration<CubicalComplex, *T*> bats::zigzag::**extend_zigzag_filtration**(const std::vector<*T*> &f0,

const *CubicalComplex*
&X, const *T* eps, const
size_t n)

Template Function bats::zigzag::extra_col_reduction

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Function Documentation

template<class **VecT**>

void bats::zigzag::**extra_col_reduction**(const size_t j, ColumnMatrix<*VecT*> &M, ColumnMatrix<*VecT*>
&U, const std::vector<size_t> &p2c, typename *VecT*::tmp_type
&tmp)

reduce column j past the pivot. Heuristic strategy to reduce fill-in during reduction

Template Function `bats::zigzag::prepare_ChainComplex(const ZigzagFiltration<CpxT, T>&, FT)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_zigzag_filtration.hpp`

Function Documentation

```
template<typename CpxT, typename T, typename FT>
auto bats::zigzag::prepare_ChainComplex(const ZigzagFiltration<CpxT, T> &F, FT)
```

Template Function `bats::zigzag::prepare_ChainComplex(const ZigzagFiltration<bats::SimplicialComplex, T>&, FT)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_zigzag_filtration.hpp`

Function Documentation

```
template<typename T, typename FT>
auto bats::zigzag::prepare_ChainComplex(const ZigzagFiltration<bats::SimplicialComplex, T> &F, FT)
```

Template Function `bats::zigzag::reduce_column(size_t, ColumnMatrix<VecT>&, ColumnMatrix<VecT>&, std::vector<size_t>&, typename VecT::tmp_type&, reduction_flag)`

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp`

Function Documentation

```
template<typename VecT, typename reduction_flag>
size_t bats::zigzag::reduce_column(size_t j, ColumnMatrix<VecT> &M, ColumnMatrix<VecT> &U,
                                   std::vector<size_t> &p2c, typename VecT::tmp_type &tmp,
                                   reduction_flag)
```

reduce column `j` past the pivot. Heuristic strategy to reduce fill-in during reduction reduce a column of `M`. Will eliminate pivots in column using columns to the left. If a pivot is shared by column to right, we will continue reduction on the column to the right.

Parameters

- `j` – column to reduce
- `M` – partially reduced matrix
- `U` – basis matrix
- `p2c` – maps pivots to columns for reduction

Returns final column which was updated

Template Function bats::zigzag::reduce_column(size_t, ColumnMatrix<VecT>&, ColumnMatrix<VecT>&, std::vector<size_t>&, typename VecT::tmp_type&, bats::extra_reduction_flag)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Function Documentation

```
template<typename VecT>
size_t bats::zigzag::reduce_column(size_t j, ColumnMatrix<VecT> &M, ColumnMatrix<VecT> &U,
                                   std::vector<size_t> &p2c, typename VecT::tmp_type &tmp,
                                   bats::extra_reduction_flag)
```

Template Function bats::zigzag::zigzag_barcode_reduction

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_zigzag_reduction.hpp

Function Documentation

```
template<typename MT, typename T, typename opt_flag, typename reduction_flag>
auto bats::zigzag::zigzag_barcode_reduction(const ChainComplex<MT> &C, const
                                             std::vector<rfilt_val<T>> &filt_order, ssize_t maxdim,
                                             opt_flag, reduction_flag)
```

computes zigzag barcode

Computes a zigzag barcode given a chain complex, entry times, and exit times

Computes reduced matrices directly, and assumes that they have already been permuted into the correct order.

TODO: don't compute top dimension homology - assume spurious TODO: strategy for keeping homology dimensions small when adding a bunch of cells at the same time.

Parameters

- C** – Chain complex (in zigzag reduction order)
- filt_order** – order in which zigzag filtration occurs
- maxdim** – maximum homology dimension to compute. If set to -1, will default to computing all but top dimension.

Template Function bats::zigzag_levelsets

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_levelset.hpp

Function Documentation

```
template<typename CpxT, typename T>
auto bats::zigzag_levelsets(const zigzag::ZigzagFiltration<CpxT, T> &X, T eps, T t0, T t1)
    Function which creates a blocked levelset zigzag diagram from a zigzag::ZigzagFiltration
        f^{ -1 }([s_i, s_{i+1}]) f^{ -1 }([s_i, s_{i+2}]) f^{ -1 }([s_{i+1}, s_{i+2}])
    where eps = s_{i+1} - s_i
```

Parameters

- **X** – zigzag::ZigzagFiltration
- **eps** – window size
- **t0** – lower bound on first window
- **t1** – upper bound on last window

Template Function bats::zigzag_toplex

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_levelset.hpp

Function Documentation

```
template<typename T>
zigzag::ZigzagFiltration<CubicalComplex, T> bats::zigzag_toplex(const
    std::vector<std::vector<std::vector<T>>>
    &img)
```

Create a zigzag filtration from a 3D image.

Extend zigzag filtration from toplexes i.e. the maximal cubes correspond to the pixel grid.

Lower-dimensional cube filtration values are extended from cofaces

This means a $n_1 \times n_2 \times n_3$ image will be on a vertex set of size $(n_1 + 1) \times (n_2 + 1) \times (n_3 + 1)$

Template Function block_reduce

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtration.hpp

Function Documentation

```
template<typename T, class CpxT, typename FT>
std::vector<std::vector<T>> block_reduce(Filtration<T, CpxT> &F, FT)
```

Template Function characteristic_matrix

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_polynomial.hpp

Function Documentation

```
template<typename T>
auto characteristic_matrix(const ColumnMatrix<SparseVector<T>> &A)
```

Function commute(MAT, MAT)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Function Documentation

```
MAT commute(MAT, MAT)
```

Function commute(EL<SI>, L<SI>)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

```
L<SI> commute(EL<SI> el1, L<SI> l1)
```

Template Function complete_pairs

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtration.hpp

Function Documentation

```
template<typename T, class CpxT, typename FTcomplete_pairs(Filtration<T, CpxT> &F, MorsePairing<CpxT> &M, size_t d, FT)
```

Template Function CU_inplace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
void CU_inplace(ColumnMatrix<TC> &C, ColumnMatrix<TC> &U)
```

Template Function delete_pivot

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
inline void delete_pivot(const ColumnMatrix<TC> &A, std::map<size_t, std::vector<size_t>> &p2c, size_t j,
size_t i0)
```

Template Function EL_L_commute

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<typename TC>
ColumnMatrix<TC> EL_L_commute(const ColumnMatrix<TC> &E, const ColumnMatrix<TC> &L)
```

Template Function EU_U_commute

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<typename TC>
inline ColumnMatrix<TC> EU_U_commute(const ColumnMatrix<TC> &EU, const ColumnMatrix<TC> &U)
```

Template Function `extend_filtration`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_extension.hpp

Function Documentation

```
template<typename CpxT, typename T>
auto extend_filtration(const CpxT &X, std::function<std::tuple<T, size_t>(const std::vector<size_t>&) &f)
```

Template Function `extended_euclidean`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_pid.hpp

Function Documentation

```
template<typename PID>
std::tuple<PID, PID, PID, PID, PID> extended_euclidean(const PID &a, const PID &b)
```

Function `extract_pairs`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_extract.hpp

Function Documentation

```
std::vector<size_t> extract_pairs(ColumnMatrix<TVec> &M, std::map<size_t, size_t> pivot_to_col)
```

Template Function `extract_row_scale`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<typename TC>
auto extract_row_scale(ColumnMatrix<TC> &E)
```

Template Function ff_inv

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_field.hpp

Function Documentation

```
template<typename IntT, unsigned P>
IntT ff_inv(const IntT val)
```

Template Function gemv

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Function Documentation

```
template<class TC>
TC gemv(ColumnMatrix<TC> &A, const TC &x)
```

Template Function generating_basis

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_rcf.hpp

Function Documentation

```
template<typename T>
ColumnMatrix<SparseVector<T>> generating_basis(const ColumnMatrix<SparseVector<UnivariatePolynomial<T>>> &R,
const ColumnMatrix<SparseVector<T>> &A)
```

Template Function get_pivots

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
std::map<size_t, std::vector<size_t>> get_pivots(const ColumnMatrix<TC> &A)
```

Template Function inv

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
ColumnMatrix<TC> inv(const ColumnMatrix<TC> &A)
```

Function isprime

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_field.hpp

Function Documentation

```
constexpr bool isprime(unsigned p)
```

Template Function L_EL_commute

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<typename TC>
inline ColumnMatrix<TC> L_EL_commute(const ColumnMatrix<TC> &L, const ColumnMatrix<TC> &EL)
```

Template Function l_inv

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Function Documentation

```
template<class TC>
ColumnMatrix<TC> l_inv(const ColumnMatrix<TC> &L)
```

Template Function `I_solve(const ColumnMatrix<TC>&, const TC&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Function Documentation

```
template<class TC>
TC I_solve(const ColumnMatrix<TC> &L, const TC &y)
```

Template Function `I_solve(const ColumnMatrix<TC>&, const ColumnMatrix<TC>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Function Documentation

```
template<class TC>
ColumnMatrix<TC> I_solve(const ColumnMatrix<TC> &L, const ColumnMatrix<TC> &A)
```

Template Function LEUP

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
SparseFact<TC> LEUP(const ColumnMatrix<TC> &A)
```

Function LEUP_Fact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Function Documentation

```
std::tuple<MAT, MAT, MAT, MAT> LEUP_Fact(MAT)
```

Function LEUP_fact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

```
std::tuple<L<SI>, EL<SI>, U<SI>, P<SI>> LEUP_fact(A<SI> a)
```

Template Function LEUP_inplace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
void LEUP_inplace(SparseFact<TC> &F)
```

Template Function lower_star_filtration(const CpxT&, const std::vector<T>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_extension.hpp

Function Documentation

```
template<typename CpxT, typename T>
auto lower_star_filtration(const CpxT &X, const std::vector<T> &f0)
```

Template Function lower_star_filtration(const std::vector<std::vector<T>>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_extension.hpp

Function Documentation

```
template<typename T>
auto lower_star_filtration(const bats::CubicalComplex &X, const std::vector<std::vector<T>> &f0)
```

Template Function `lower_star_filtration(const std::vector<std::vector<std::vector<T>>>&)` **const**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_extension.hpp

Function Documentation

```
template<typename T>
auto lower_star_filtration(const bats::CubicalComplex &X, const std::vector<std::vector<std::vector<T>>>&f0)
```

Template Function LQU

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
SparseFact<TC> LQU(const ColumnMatrix<TC> &A)
```

Template Function LQU_inplace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
void LQU_inplace(SparseFact<TC> &F)
```

Function matmul(MAT, MAT)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Function Documentation

```
MAT matmul(MAT, MAT)
```

Function matmul(A<SI>, A<SI>)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

A<SI> **matmul**(*A<SI>* a, *A<SI>* b)

Function matmul(D<SI>, D<SI>)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

D<SI> **matmul**(*D<SI>* a, *D<SI>* b)

Function matmul(L<SI>, L<SI>)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

L<SI> **matmul**(*L<SI>* a, *L<SI>* b)

Function matmul(U<SI>, U<SI>)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

U<SI> **matmul**(*U<SI>* a, *U<SI>* b)

Function matmul(L<SI>, U<SI>)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

A<*SI*> **matmul**(*L*<*SI*> *a*, *U*<*SI*> *b*)

Template Function **max_cube_val**(**const std::vector<size_t>&**, **const std::vector<std::vector<T>>&**)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_extension.hpp

Function Documentation

```
template<typename T>
auto max_cube_val(const std::vector<size_t> &c, const std::vector<std::vector<T>> &f0)
    return maximum vertex value on a cube c assume 2 dimensions
```

Template Function **max_cube_val**(**const std::vector<size_t>&**, **const std::vector<std::vector<std::vector<T>>&**)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_filtration_extension.hpp

Function Documentation

```
template<typename T>
auto max_cube_val(const std::vector<size_t> &c, const std::vector<std::vector<std::vector<T>>> &f0)
    return maximum vertex value on a cube c assume 3 dimensions
```

Template Function **operator<**(**const TI&**, **const nzpair<TI, TV>&**)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_abstract_vector.hpp

Function Documentation

```
template<typename TI, typename TV>
bool operator<(const TI &a, const nzpair<TI, TV> &b)
```

Template Function **operator<**(**const nzpair<TI, TV>&**, **const TI&**)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_abstract_vector.hpp

Function Documentation

```
template<typename TI, typename TV>
bool operator<(const nzpair<TI, TV> &a, const TI &b)
```

Template Function **operator**<(const nzpair<TI, TV>&, const nzpair<TI, TV>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_abstract_vector.hpp

Function Documentation

```
template<typename TI, typename TV>
bool operator<(const nzpair<TI, TV> &a, const nzpair<TI, TV> &b)
```

Template Function **operator**<<(std::ostream&, const nzpair<TI, TV>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_abstract_vector.hpp

Function Documentation

```
template<typename TI, typename TV>
std::ostream &operator<<(std::ostream &os, const nzpair<TI, TV> &x)
```

Function **operator**<<(std::ostream&, L<SI>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

```
std::ostream &operator<<(std::ostream &out, L<SI> &c)
```

Function **operator**<<(std::ostream&, U<SI>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

```
std::ostream &operator<<(std::ostream &out, U<SI> &c)
```

Function operator<<(std::ostream&, *EL<SI>*&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

```
std::ostream &operator<<(std::ostream &out, EL<SI> &c)
```

Function operator<<(std::ostream&, *EU<SI>*&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

```
std::ostream &operator<<(std::ostream &out, EU<SI> &c)
```

Function operator<<(std::ostream&, *ELH<SI>*&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

```
std::ostream &operator<<(std::ostream &out, ELH<SI> &c)
```

Function operator<<(std::ostream&, *EUH<SI>*&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

```
std::ostream &operator<<(std::ostream &out, EUH<SI> &c)
```

Function operator<<(std::ostream&, P<SI>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

```
std::ostream &operator<<(std::ostream &out, P<SI> &c)
```

Function operator<<(std::ostream&, A<SI>&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Function Documentation

```
std::ostream &operator<<(std::ostream &out, A<SI> &c)
```

Template Function pivot_ind

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<typename TC>
inline size_t pivot_ind(const ColumnMatrix<TC> &E, size_t j)
```

Template Function PLEU

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
SparseFact<TC> PLEU(const ColumnMatrix<TC> &A)
```

Function PLEU_Fact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Function Documentation

```
std::tuple<MAT, MAT, MAT, MAT> PLEU_Fact(MAT)
```

Function PLEU_fact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

```
std::tuple<P<SI>, L<SI>, EU<SI>, U<SI>> PLEU_fact(A<SI> a)
```

Template Function PLEU_inplace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
void PLEU_inplace(SparseFact<TC> &F)
```

Template Function PUEL

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
SparseFact<TC> PUEL(const ColumnMatrix<TC> &A)
```

Function PUEL_Fact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Function Documentation

```
std::tuple<MAT, MAT, MAT, MAT> PUEL_Fact(MAT)
```

Function PUEL_fact

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

```
std::tuple<P<SI>, U<SI>, ELH<SI>, L<SI>> PUEL_fact(A<SI> a)
```

Template Function PUEL_inplace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
void PUEL_inplace(SparseFact<TC> &F)
```

Template Function RCF_basis

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_rcf.hpp

Function Documentation

```
template<typename T>
ColumnMatrix<SparseVector<T>> RCF_basis(const ColumnMatrix<SparseVector<UnivariatePolynomial<T>>>
&S, const ColumnMatrix<SparseVector<T>> &A, const
ColumnMatrix<SparseVector<T>> &B)
```

Template Function **schur(T&, T&, T&, T&)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_schur.hpp

Function Documentation

```
template<typename T>
T schur(T &A, T &B, T &C, T &D)
```

Template Function **schur(ColumnMatrix<CT>&, ColumnMatrix<CT>&, ColumnMatrix<CT>&, ColumnMatrix<CT>&)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_schur.hpp

Function Documentation

```
template<typename CT>
ColumnMatrix<CT> schur(ColumnMatrix<CT> &A, ColumnMatrix<CT> &B, ColumnMatrix<CT> &C,
                           ColumnMatrix<CT> &D)
```

Template Function **schur(const ColumnMatrix<TV>&, const size_t, const size_t, const size_t, const size_t)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_schur.hpp

Function Documentation

```
template<typename TV>
auto schur(const ColumnMatrix<TV> &A, const size_t i0, const size_t i1, const size_t j0, const size_t j1)
```

Template Function **sgn(T)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_field.hpp

Function Documentation

```
template<typename T>
inline T sgn(T val)
```

Function **sgn(const int&)**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_pid.hpp

Function Documentation

```
int sgn(const int &a)
```

Template Function **smith_factorization**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_pid.hpp

Function Documentation

```
template<class TC>
SmithFact<TC> smith_factorization(const ColumnMatrix<TC> &A)
```

Template Function **smith_normal_form**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_pid.hpp

Function Documentation

```
template<typename TC>
void smith_normal_form(ColumnMatrix<TC> &A)
```

Template Function **smith_rows**

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_pid.hpp

Function Documentation

```
template<class TC>
std::tuple<ColumnMatrix<TC>, ColumnMatrix<TC>> smith_rows(const ColumnMatrix<TC> &A)
```

Template Function standard_reduce

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_persistence_filtration.hpp

Function Documentation

```
template<typename T, class CpxT, typename FT>
std::vector<std::vector<T>> standard_reduce(const Filtration<T, CpxT> &F, FT)
```

Template Function U_EU_commute

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<typename TC>
inline ColumnMatrix<TC> U_EU_commute(const ColumnMatrix<TC> &U, const ColumnMatrix<TC> &EU)
```

Template Function u_inv

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Function Documentation

```
template<class TC>
ColumnMatrix<TC> u_inv(const ColumnMatrix<TC> &U)
```

Template Function u_solve(const ColumnMatrix<TC>&, const TC&)

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Function Documentation

```
template<class TC>
TC u_solve(const ColumnMatrix<TC> &U, const TC &y)
```

Template Function `u_solve(const ColumnMatrix<TC>&, const ColumnMatrix<TC>&)`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_col_matrix.hpp

Function Documentation

```
template<class TC>
ColumnMatrix<TC> u_solve(const ColumnMatrix<TC> &U, const ColumnMatrix<TC> &A)
```

Template Function `UELP`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
SparseFact<TC> UELP(const ColumnMatrix<TC> &A)
```

Function `UELP_Fact`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_matrix_interface.hpp

Function Documentation

```
std::tuple<MAT, MAT, MAT, MAT> UELP_Fact(MAT)
```

Function `UELP_fact`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.hpp

Function Documentation

```
std::tuple<U<SI>, EUH<SI>, L<SI>, P<SI>> UELP_fact(A<SI> a)
```

Template Function UELP_inplace

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
void UELP_inplace(SparseFact<TC> &F)
```

Template Function update_pivot

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
inline void update_pivot(const ColumnMatrix<TC> &A, std::map<size_t, std::vector<size_t>> &p2c, size_t j,
                        size_t i0)
```

Template Function UQL

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_sparse_fact.hpp

Function Documentation

```
template<class TC>
SparseFact<TC> UQL(const ColumnMatrix<TC> &A)
```

Variables

Variable bats::NO_IND

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_util_common.hpp

Variable Documentation

```
const size_t bats::NO_IND = std::numeric_limits<size_t>::max()
```

Defines

Define `APPLY_INVERSE_ON_LEFT`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Define Documentation

`APPLY_INVERSE_ON_LEFT(A, B, C)`

Define `APPLY_INVERSE_ON_RIGHT`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Define Documentation

`APPLY_INVERSE_ON_RIGHT(A, B, C)`

Define `IMPL_COUT`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Define Documentation

`IMPL_COUT(M)`

Define `IMPL_FACT`

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Define Documentation

`IMPL_FACT(TYPE, F1, F2, F3, F4, f1, f2, f3, f4)`

Define MM

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_linalg_symbolic_implementations.h

Define Documentation

MM(A, B, C)

Define p2c_type

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_homology_reduction.hpp

Define Documentation

p2c_type

Typedefs

Typedef bats::Cover

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_cover.hpp

Typedef Documentation

using bats::Cover = std::vector<std::set<size_t>>

Typedef bats::Matrix

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_bats_checkouts_stable_include_topology_data.hpp

Typedef Documentation

using bats::Matrix = A<Dense<*T*, RowMaj>>

1.6 About BATS

BATS is a library for applied algebraic topology.

**CHAPTER
TWO**

INDICES AND TABLES

- genindex
- modindex
- search

INDEX

A

`A (C++ struct)`, 27
`AbstractField (C++ class)`, 70
`AbstractField::inv (C++ function)`, 70
`AbstractField::operator* (C++ function)`, 70
`AbstractField::operator+ (C++ function)`, 70
`AbstractField::operator/ (C++ function)`, 70
`AbstractField::operator== (C++ function)`, 70
`AbstractField::operator- (C++ function)`, 70
`AbstractField::print (C++ function)`, 70
`AbstractField::str (C++ function)`, 70
`AbstractMatrix (C++ class)`, 71
`apply_inverse (C++ function)`, 125
`APPLY_INVERSE_ON_LEFT (C macro)`, 233
`apply_inverse_on_left (C++ function)`, 125, 126
`APPLY_INVERSE_ON_RIGHT (C macro)`, 233
`apply_inverse_on_right (C++ function)`, 126, 127

B

`bats::__ChainComplex (C++ function)`, 127
`bats::__ChainFunctor (C++ function)`, 127
`bats::__CochainComplex (C++ function)`, 128
`bats::__FilteredChainComplex (C++ function)`, 128
`bats::__ReducedChainComplex (C++ function)`, 128
`bats::__ReducedCochainComplex (C++ function)`, 128
`bats::__ReducedFilteredChainComplex (C++ function)`, 129
`bats::AbstractMetric (C++ struct)`, 27
`bats::AbstractMetric::dist (C++ function)`, 27
`bats::AbstractMetric::operator() (C++ function)`, 27
`bats::add_dimension_recursive_flag (C++ function)`, 129, 130
`bats::add_dimension_recursive_flag_extension (C++ function)`, 130
`bats::add_dimension_recursive_flag_unsafe (C++ function)`, 130
`bats::add_dimension_recursive_nerve (C++ function)`, 130
`bats::add_normal_noise (C++ function)`, 131
`bats::add_uniform_noise (C++ function)`, 132

`bats::all_pairs (C++ function)`, 132
`bats::AngleDist (C++ struct)`, 28
`bats::AngleDist::dist (C++ function)`, 28
`bats::apparent_pairs_flag (C++ struct)`, 28
`bats::approx_center (C++ function)`, 133
`bats::assign_set_lower (C++ function)`, 133
`bats::assign_set_upper (C++ function)`, 133
`bats::bar (C++ struct)`, 28
`bats::bar::bar (C++ function)`, 28
`bats::bar::end (C++ member)`, 29
`bats::bar::end_ind (C++ member)`, 29
`bats::bar::start (C++ member)`, 29
`bats::bar::start_ind (C++ member)`, 29
`bats::barcode (C++ function)`, 133–135
`bats::barcode_equality (C++ function)`, 135
`bats::barcode_form_divide_conquer (C++ function)`, 135
`bats::barcode_form_leftright (C++ function)`, 135
`bats::barcode_form_rightleft (C++ function)`, 136
`bats::barcode_from_barcode_form (C++ function)`, 136
`bats::BarcodePair (C++ class)`, 71
`bats::BarcodePair::BarcodePair (C++ function)`, 71
`bats::BarcodePair::birth (C++ member)`, 72
`bats::BarcodePair::death (C++ member)`, 72
`bats::BarcodePair::print (C++ function)`, 71
`bats::bars_to_pairs (C++ function)`, 136
`bats::bivariate_cover (C++ function)`, 136
`bats::CellComplex (C++ class)`, 72
`bats::CellComplex::add (C++ function)`, 72
`bats::CellComplex::add_vertex (C++ function)`, 72
`bats::CellComplex::add_vertices (C++ function)`, 72
`bats::CellComplex::boundary (C++ function)`, 72
`bats::CellComplex::boundary_csc (C++ function)`, 72
`bats::CellComplex::CellComplex (C++ function)`, 72
`bats::CellComplex::maxdim (C++ function)`, 72
`bats::CellComplex::ncells (C++ function)`, 72
`bats::CellularMap (C++ class)`, 73

```

bats::CellularMap::CellularMap (C++ function), 73
bats::CellularMap::identity (C++ function), 73
bats::CellularMap::maxdim (C++ function), 73
bats::CellularMap::operator[] (C++ function), 73
bats::CellularMap::save (C++ function), 73
bats::Chain (C++ function), 137, 138
bats::ChainComplex (C++ struct), 29
bats::ChainComplex::boundary (C++ member), 30
bats::ChainComplex::ChainComplex (C++ function), 29
bats::ChainComplex::clear_compress_apparent_points (C++ function), 30
bats::ChainComplex::dim (C++ function), 29
bats::ChainComplex::ipermute_basis (C++ function), 30
bats::ChainComplex::is_valid_complex (C++ function), 29
bats::ChainComplex::maxdim (C++ function), 29
bats::ChainComplex::operator[] (C++ function), 29, 30
bats::ChainComplex::permute_basis (C++ function), 30
bats::ChainComplex::relative_complex (C++ function), 29
bats::ChainComplex::subcomplex (C++ function), 29
bats::ChainComplex::update_basis_general (C++ function), 30
bats::ChainFunctor (C++ function), 138
bats::ChainMap (C++ struct), 31
bats::ChainMap::ChainMap (C++ function), 31
bats::ChainMap::map (C++ member), 32
bats::ChainMap::maxdim (C++ function), 31
bats::ChainMap::operator[] (C++ function), 31
bats::ChainMap::permute_column_basis (C++ function), 31
bats::ChainMap::permute_row_basis (C++ function), 31
bats::ChainMap::relative_map (C++ function), 31
bats::circle (C++ function), 138
bats::clearing_flag (C++ struct), 32
bats::CochainComplex (C++ struct), 32
bats::CochainComplex::coboundary (C++ member), 33
bats::CochainComplex::CochainComplex (C++ function), 32
bats::CochainComplex::dim (C++ member), 33
bats::CochainComplex::ipermute_basis (C++ function), 32
bats::CochainComplex::maxdim (C++ function), 32
bats::CochainComplex::operator[] (C++ function), 32
bats::CochainComplex::permute_basis (C++ function), 32
bats::CompleteFlagFiltration (C++ function), 139
bats::compression_flag (C++ struct), 33
bats::compute_basis_flag (C++ struct), 33
bats::coordinate_projection (C++ function), 139
bats::CosineDist (C++ struct), 33
bats::CosineDist::dist (C++ function), 34
bats::Cover (C++ type), 234
bats::Cube (C++ function), 139, 140
bats::CubicalComplex (C++ class), 74
bats::CubicalComplex::add (C++ function), 74
bats::CubicalComplex::add_recursive (C++ function), 74
bats::CubicalComplex::boundary_csc (C++ function), 75
bats::CubicalComplex::cell_begin (C++ function), 74
bats::CubicalComplex::cell_end (C++ function), 75
bats::CubicalComplex::CubicalComplex (C++ function), 74
bats::CubicalComplex::faces_begin (C++ function), 74
bats::CubicalComplex::faces_end (C++ function), 74
bats::CubicalComplex::find_idx (C++ function), 74
bats::CubicalComplex::generate_cube (C++ function), 75
bats::CubicalComplex::get_cell (C++ function), 75
bats::CubicalComplex::get_cube (C++ function), 75
bats::CubicalComplex::get_cubes (C++ function), 75
bats::CubicalComplex::load_cubes (C++ function), 75
bats::CubicalComplex::maxdim (C++ function), 74
bats::CubicalComplex::ncells (C++ function), 74
bats::CubicalComplex::print_summary (C++ function), 74
bats::CubicalComplex::set_dimension (C++ function), 74
bats::CubicalComplex::skeleton (C++ function), 75
bats::CubicalMap (C++ function), 140
bats::DataSet (C++ struct), 34
bats::DataSet::data (C++ member), 35
bats::DataSet::DataSet (C++ function), 34
bats::DataSet::dim (C++ function), 34
bats::DataSet::get_data (C++ function), 34
bats::DataSet::operator() (C++ function), 34
bats::DataSet::operator[] (C++ function), 34
bats::DataSet::size (C++ function), 34

```

```

bats::detail::pivot_coeff (C++ function), 141
bats::DGLinearFunctor (C++ function), 141
bats::DGLinearMap (C++ struct), 35
bats::DGLinearMap::DGLinearMap (C++ function),
    35
bats::DGLinearMap::map (C++ member), 36
bats::DGLinearMap::maxdim (C++ function), 35
bats::DGLinearMap::operator[] (C++ function), 35
bats::DGLinearMap::permute_column_basis
    (C++ function), 35
bats::DGLinearMap::permute_row_basis (C++ function),
    35
bats::DGVectorSpace (C++ struct), 36
bats::DGVectorSpace::degree (C++ member), 37
bats::DGVectorSpace::DGVectorSpace (C++ function), 36
bats::DGVectorSpace::differential (C++ member), 37
bats::DGVectorSpace::dim (C++ function), 36
bats::DGVectorSpace::maxdim (C++ function), 36
bats::DGVectorSpace::operator[] (C++ function),
    36
bats::Diagram (C++ class), 76
bats::Diagram::add_edge (C++ function), 76
bats::Diagram::add_node (C++ function), 76
bats::Diagram::Diagram (C++ function), 76
bats::Diagram::edata (C++ member), 77
bats::Diagram::Edge (C++ struct), 37, 77
bats::Diagram::Edge::Edge (C++ function), 37, 77
bats::Diagram::Edge::src (C++ member), 37, 77
bats::Diagram::Edge::targ (C++ member), 37, 77
bats::Diagram::edge_data (C++ function), 76
bats::Diagram::edge_source (C++ function), 76
bats::Diagram::edge_target (C++ function), 76
bats::Diagram::elist (C++ member), 77
bats::Diagram::nedge (C++ function), 76
bats::Diagram::nnode (C++ function), 76
bats::Diagram::node (C++ member), 77
bats::Diagram::node_data (C++ function), 76
bats::Diagram::save (C++ function), 76
bats::Diagram::save_metadata (C++ function), 76
bats::Diagram::set_edge (C++ function), 76
bats::Diagram::set_node (C++ function), 76
bats::DiscreteMorozovZigzag (C++ function), 141
bats::DiscreteMorozovZigzagSets (C++ function),
    142
bats::divide_conquer_flag (C++ struct), 37
bats::dowker_edge_param (C++ function), 142
bats::dowker_filtration_edges (C++ function),
    142
bats::DowkerFiltration (C++ function), 143, 144
bats::EilenbergZilber (C++ function), 144
bats::enclosing_radius (C++ function), 144
bats::euclidean (C++ function), 145
bats::Euclidean (C++ struct), 38
bats::Euclidean::dist (C++ function), 38
bats::extension_perm (C++ function), 145
bats::extra_reduction_flag (C++ struct), 38
bats::extract_basis_indices (C++ function), 145
bats::extract_dimension (C++ function), 146
bats::filtered_edge (C++ struct), 38
bats::filtered_edge::filtered_edge (C++ function),
    39
bats::filtered_edge::operator< (C++ function),
    39
bats::filtered_edge::r (C++ member), 39
bats::filtered_edge::s (C++ member), 39
bats::filtered_edge::t (C++ member), 39
bats::FilteredChainComplex (C++ struct), 39
bats::FilteredChainComplex::C (C++ member), 40
bats::FilteredChainComplex::complex (C++ function),
    39
bats::FilteredChainComplex::dim (C++ function),
    39
bats::FilteredChainComplex::FilteredChainComplex
    (C++ function), 39
bats::FilteredChainComplex::perm (C++ member),
    40
bats::FilteredChainComplex::update_filtration
    (C++ function), 39
bats::FilteredChainComplex::update_filtration_general
    (C++ function), 39
bats::FilteredChainComplex::val (C++ member),
    40
bats::FilteredChainComplex::vals (C++ function),
    39
bats::FilteredCochainComplex (C++ struct), 40
bats::FilteredCochainComplex::C (C++ member),
    40
bats::FilteredCochainComplex::complex (C++ function),
    40
bats::FilteredCochainComplex::dim (C++ function),
    40
bats::FilteredCochainComplex::FilteredCochainComplex
    (C++ function), 40
bats::FilteredCochainComplex::perm (C++ member),
    40
bats::FilteredCochainComplex::update_filtration
    (C++ function), 40
bats::FilteredCochainComplex::update_filtration_general
    (C++ function), 40
bats::FilteredCochainComplex::val (C++ member),
    40
bats::FilteredCochainComplex::vals (C++ function),
    40
bats::Filtration (C++ class), 77
bats::Filtration::add (C++ function), 78
bats::Filtration::add_recursive (C++ function),
    78

```

bats::Filtration::complex (C++ function), 78
 bats::Filtration::Filtration (C++ function), 77, 78
 bats::Filtration::maxdim (C++ function), 78
 bats::Filtration::ncells (C++ function), 78
 bats::Filtration::sortperm (C++ function), 78
 bats::Filtration::sublevelset (C++ function), 78
 bats::Filtration::vals (C++ function), 78
 bats::filtration_iperm (C++ function), 146
 bats::filtration_sortperm (C++ function), 146
 bats::find_perm_from_vector (C++ function), 147
 bats::flag_filtration_edges (C++ function), 147
 bats::FlagComplex (C++ function), 147
 bats::FlagFiltration (C++ function), 147
 bats::FlagFiltration_extension (C++ function), 148
 bats::flags::divide_conquer (C++ struct), 41
 bats::flags::leftward (C++ struct), 41
 bats::flags::rightward (C++ struct), 41
 bats::force_repel_rp (C++ function), 148
 bats::Freudenthal (C++ function), 148–150
 bats::future::ColumnMajor (C++ struct), 41
 bats::future::CompositePermutation (C++ class), 79
 bats::future::CompositePermutation::append (C++ function), 79
 bats::future::CompositePermutation::CompositePermutation (C++ function), 79
 bats::future::CompositePermutation::operator() (C++ function), 79
 bats::future::CompositePermutation::swap (C++ function), 79
 bats::future::const_strided_iterator (C++ class), 80
 bats::future::const_strided_iterator::~const_strided_iterator (C++ function), 80
 bats::future::const_strided_iterator::const_strided_iterator (C++ function), 80
 bats::future::const_strided_iterator::operator* (C++ function), 80
 bats::future::const_strided_iterator::operator[] (C++ function), 80
 bats::future::ElementaryPermutation (C++ struct), 42
 bats::future::ElementaryPermutation::ElementaryPermutation (C++ function), 42
 bats::future::ElementaryPermutation::i (C++ member), 42
 bats::future::ElementaryPermutation::j (C++ member), 42
 bats::future::ElementaryPermutation::operator() (C++ function), 42
 bats::future::find_pivot_complete (C++ function), 150
 bats::future::find_pivot_high (C++ function), 150, 151
 bats::future::gemm (C++ function), 151
 bats::future::gemv (C++ function), 151
 bats::future::l_residual (C++ function), 152
 bats::future::l_solve (C++ function), 152
 bats::future::LU (C++ function), 153
 bats::future::LUFact (C++ struct), 43
 bats::future::LUFact::L (C++ member), 43
 bats::future::LUFact::LUFact (C++ function), 43
 bats::future::LUFact::P (C++ member), 43
 bats::future::LUFact::print (C++ function), 43
 bats::future::LUFact::print_info (C++ function), 43
 bats::future::LUFact::prod (C++ function), 43
 bats::future::LUFact::Q (C++ member), 43
 bats::future::LUFact::U (C++ member), 43
 bats::future::LUFact::val_type (C++ type), 43
 bats::future::Matrix (C++ class), 81
 bats::future::Matrix::add_column (C++ function), 82, 83
 bats::future::Matrix::add_row (C++ function), 82
 bats::future::Matrix::append_column (C++ function), 82
 bats::future::Matrix::append_matrix (C++ function), 82
 bats::future::Matrix::column (C++ function), 82
 bats::future::Matrix::data (C++ function), 81
 bats::future::Matrix::delete_column (C++ function), 82
 bats::future::Matrix::dims (C++ function), 81
 bats::future::Matrix::fill (C++ function), 81
 bats::future::Matrix::identity (C++ function), 83
 bats::future::Matrix::len (C++ function), 81
 bats::future::Matrix::Matrix (C++ function), 81
 bats::future::Matrix::mm (C++ function), 83
 bats::future::Matrix::mv (C++ function), 83
 bats::future::Matrix::ncol (C++ function), 81
 bats::future::Matrix::nrow (C++ function), 81
 bats::future::Matrix::operator() (C++ function), 82
 bats::future::const_strided_iterator::operator[]

```

bats::future::Matrix::operator* (C++ function), 83
bats::future::Matrix::operator[] (C++ function), 81
bats::future::Matrix::print (C++ function), 82
bats::future::Matrix::print_info (C++ function), 82
bats::future::Matrix::row (C++ function), 82
bats::future::Matrix::scale_column (C++ function), 83
bats::future::Matrix::scale_row (C++ function), 83
bats::future::Matrix::swap_columns (C++ function), 82
bats::future::Matrix::swap_rows (C++ function), 82
bats::future::Matrix::transpose (C++ function), 82
bats::future::Matrix::value_type (C++ type), 81
bats::future::Matrix::view (C++ function), 82
bats::future::MatrixView (C++ class), 83
bats::future::MatrixView::MatrixView (C++ function), 84
bats::future::MatrixView::ncol (C++ function), 84
bats::future::MatrixView::nrow (C++ function), 84
bats::future::MatrixView::operator() (C++ function), 84
bats::future::MatrixView::print (C++ function), 84
bats::future::MatrixView::print_info (C++ function), 84
bats::future::MatrixView::val_type (C++ type), 83
bats::future::operator<< (C++ function), 153
bats::future::Permutation (C++ class), 84
bats::future::Permutation::Permutation (C++ function), 84
bats::future::range (C++ class), 85
bats::future::range::begin (C++ function), 85
bats::future::range::cbegin (C++ function), 85
bats::future::range::cend (C++ function), 85
bats::future::range::const_iterator (C++ class), 86, 87
bats::future::range::const_iterator::~const_iterator (C++ function), 86, 87
bats::future::range::const_iterator::const_iterator (C++ function), 86, 87
bats::future::range::const_iterator::operator!= (C++ function), 86, 87
bats::future::range::const_iterator::operator* (C++ function), 86, 87
bats::future::range::const_iterator::operator+ (C++ function), 86, 87
bats::future::range::const_iterator::operator- (C++ function), 86, 87
bats::future::range::const_iterator::operator== (C++ function), 86, 87
bats::future::range::const_iterator::operator-- (C++ function), 86, 87
bats::future::range::const_iterator::operator-> (C++ function), 86, 87
bats::future::range::end (C++ function), 85
bats::future::range::first (C++ function), 85
bats::future::range::iterator (C++ type), 85
bats::future::range::last (C++ function), 85
bats::future::range::operator[] (C++ function), 85
bats::future::range::range (C++ function), 85
bats::future::range::size (C++ function), 85
bats::future::range::stride (C++ function), 85
bats::future::RowMajor (C++ struct), 43
bats::future::SimilarityTransform (C++ struct), 44
bats::future::SimilarityTransform::A (C++ member), 44
bats::future::SimilarityTransform::add_row (C++ function), 44
bats::future::SimilarityTransform::operator() (C++ function), 44
bats::future::SimilarityTransform::print (C++ function), 44
bats::future::SimilarityTransform::print_info (C++ function), 44
bats::future::SimilarityTransform::prod (C++ function), 44
bats::future::SimilarityTransform::S (C++ member), 44
bats::future::SimilarityTransform::scale_column (C++ function), 44
bats::future::SimilarityTransform::scale_row (C++ function), 44
bats::future::SimilarityTransform::SimilarityTransform (C++ function), 44
bats::future::SimilarityTransform::Sinv (C++ member), 44
bats::future::SimilarityTransform::size (C++ function), 44
bats::future::SimilarityTransform::swap_columns (C++ function), 44
bats::future::SimilarityTransform::swap_rows (C++ function), 44
bats::future::Span (C++ class), 88
bats::future::Span::_vdim (C++ member), 88
bats::future::Span::add (C++ function), 88
bats::future::Span::contains (C++ function), 88
bats::future::Span::dim (C++ function), 88
bats::future::Span::L (C++ member), 88
bats::future::Span::Pt (C++ member), 88

```

```

bats::future::Span::Span (C++ function), 88
bats::future::Span::vdim (C++ function), 88
bats::future::strided_iterator (C++ class), 89
bats::future::strided_iterator::~strided_iterator
    (C++ function), 89
bats::future::strided_iterator::operator!=
    (C++ function), 89
bats::future::strided_iterator::operator*
    (C++ function), 89
bats::future::strided_iterator::operator+
    (C++ function), 89
bats::future::strided_iterator::operator++
    (C++ function), 89
bats::future::strided_iterator::operator==
    (C++ function), 89
bats::future::strided_iterator::operator--
    (C++ function), 89
bats::future::strided_iterator::operator->
    (C++ function), 89
bats::future::strided_iterator::operator[]
    (C++ function), 89
bats::future::strided_iterator::strided_iterator
    (C++ function), 89
bats::future::unit_lower (C++ function), 153
bats::future::upper (C++ function), 154
bats::future::VectorView (C++ class), 90
bats::future::VectorView::axpy (C++ function),
    90
bats::future::VectorView::begin (C++ function),
    90
bats::future::VectorView::cbegin (C++ function),
    90
bats::future::VectorView::cend (C++ function),
    90
bats::future::VectorView::const_iterator
    (C++ type), 90
bats::future::VectorView::end (C++ function), 90
bats::future::VectorView::iterator (C++ type),
    90
bats::future::VectorView::operator[] (C++ function),
    90
bats::future::VectorView::print (C++ function),
    90
bats::future::VectorView::scale (C++ function),
    90
bats::future::VectorView::VectorView (C++ function),
    90
bats::gen_cylinder (C++ function), 154
bats::get_clearing_inds (C++ function), 154
bats::get_compression_inds (C++ function), 154
bats::get_dM_ZZ_inds (C++ function), 155
bats::get_m (C++ function), 155
bats::get_subset (C++ function), 155
bats::greedy_landmarks (C++ function), 155
bats::greedy_landmarks_hausdorff (C++ func-
    tion), 156
bats::hausdorff_landmarks (C++ function), 156
bats::Hom (C++ function), 156, 157
bats::identity_perm (C++ function), 157
bats::increment_m (C++ function), 158
bats::induced_map (C++ function), 158, 159
bats::interval (C++ function), 159
bats::is_left_arrow (C++ function), 159
bats::kdist (C++ function), 160
bats::kron_chain_shift (C++ function), 160
bats::kron_chains (C++ function), 160
bats::kron_homology (C++ function), 160
bats::kron_index (C++ function), 161
bats::L1Dist (C++ struct), 45
bats::L1Dist::dist (C++ function), 45
bats::landmark_cover (C++ function), 161
bats::landmark_eps_cover (C++ function), 161
bats::LightSimplicialComplex (C++ class), 91
bats::LightSimplicialComplex::add (C++ func-
    tion), 92
bats::LightSimplicialComplex::add_recursive
    (C++ function), 92
bats::LightSimplicialComplex::add_unsafe
    (C++ function), 92
bats::LightSimplicialComplex::boundary (C++ 
    function), 92
bats::LightSimplicialComplex::boundary_csc
    (C++ function), 92
bats::LightSimplicialComplex::find_idx (C++ 
    function), 92
bats::LightSimplicialComplex::get_cell (C++ 
    function), 91
bats::LightSimplicialComplex::get_simplex
    (C++ function), 91
bats::LightSimplicialComplex::get_simplices
    (C++ function), 91, 92
bats::LightSimplicialComplex::key_to_simplex
    (C++ function), 91
bats::LightSimplicialComplex::LightSimplicialComplex
    (C++ function), 91
bats::LightSimplicialComplex::max_vertex
    (C++ function), 91
bats::LightSimplicialComplex::maxdim (C++ 
    function), 91
bats::LightSimplicialComplex::ncells (C++ 
    function), 91
bats::LightSimplicialComplex::print_summary
    (C++ function), 92
bats::LightSimplicialComplex::simplex_begin
    (C++ function), 92
bats::LightSimplicialComplex::simplex_boundary_iterator
    (C++ struct), 45
bats::LightSimplicialComplex::simplex_boundary_iterator::a

```

```

(C++ member), 46
bats::LightSimplicialComplex::simplex_boundary_iterator (C++ member), 46
bats::LightSimplicialComplex::simplex_end (C++ function), 92
bats::LightSimplicialComplex::simplex_key (C++ function), 91
bats::linear_cover_intersection_diagram (C++ function), 161
bats::linear_subset_union_diagram (C++ function), 162
bats::LInfDist (C++ struct), 46
bats::LInfDist::dist (C++ function), 47
bats::LowerStarFiltration (C++ function), 162
bats::make_edge (C++ function), 162
bats::Matrix (C++ type), 234
bats::mayer_vietoris_boundary (C++ function), 162
bats::neighborhood (C++ function), 163
bats::neighborhoods (C++ function), 163, 164
bats::Nerve (C++ function), 164
bats::no_apparent_pairs_flag (C++ struct), 47
bats::NO_IND (C++ member), 232
bats::no_optimization_flag (C++ struct), 47
bats::normalize_entries (C++ function), 165
bats::operator< (C++ function), 165
bats::operator<< (C++ function), 165
bats::OscillatingRipsZigzagSets (C++ function), 165
bats::pairwise_dist (C++ function), 166
bats::partial_reduce_parallel (C++ function), 166:before
bats::pass_L_left (C++ function), 167
bats::pass_R_left (C++ function), 167
bats::pass_P_right (C++ function), 167
bats::pass_U_right (C++ function), 168
bats::perm_to_the_end (C++ function), 168
bats::PersistencePair (C++ struct), 47
bats::PersistencePair::birth (C++ member), 48
bats::PersistencePair::birth (C++ function), 45
bats::PersistencePair::birth (C++ member), 48
bats::PersistencePair::birth (C++ function), 46
bats::PersistencePair::dim (C++ member), 48
bats::PersistencePair::dim (C++ function), 46
bats::PersistencePair::get_birth (C++ function), 48
bats::PersistencePair::get_birth (C++ function), 46
bats::PersistencePair::get_death (C++ function), 48
bats::PersistencePair::get_death (C++ function), 46
bats::PersistencePair::get_death (C++ function), 48
bats::PersistencePair::operator< (C++ function), 47
bats::PersistencePair::length (C++ function), 48
bats::PersistencePair::mid (C++ function), 48
bats::PersistencePair::operator!= (C++ function), 47
bats::PersistencePair::operator== (C++ function), 47
bats::PersistencePair::PersistencePair (C++ function), 47
bats::PersistencePair::str (C++ function), 48
bats::print_1D_vectors (C++ function), 169
bats::print_2D_vectors (C++ function), 169
bats::print_filtration_info (C++ function), 169
bats::print_simplex (C++ function), 169
bats::print_summary_of_filtration (C++ function), 170
bats::prod_ind (C++ function), 170
bats::product_paths (C++ function), 170
bats::product_space (C++ function), 171
bats::random_landmarks (C++ function), 171
bats::read_point_cloud (C++ function), 171
bats::Reduce (C++ function), 171, 172
bats::reduce_block_dq (C++ function), 172, 173
bats::reduce_block_sequential (C++ function), 174
bats::reduce_column_extra (C++ function), 175
bats::reduce_column_sparsify (C++ function), 175
bats::reduce_column_standard (C++ function), 176

```

```

bats::reduce_matrix (C++ function), 177, 178
bats::reduce_matrix_clearing (C++ function), 179
bats::reduce_matrix_compression (C++ function),
    179
bats::reduce_matrix_extra (C++ function), 180
bats::reduce_matrix_standard (C++ function), 180
bats::ReducedChainComplex (C++ class), 92
bats::ReducedChainComplex::betti (C++ func-
    tion), 93
bats::ReducedChainComplex::chain_preferred_repre-
    sentative (C++ function), 94
bats::ReducedChainComplex::chain_type (C++ type),
    93
bats::ReducedChainComplex::dim (C++ function),
    93
bats::ReducedChainComplex::find_preferred_repre-
    sentative (C++ function), 94
bats::ReducedChainComplex::from_hom_basis
    (C++ function), 94
bats::ReducedChainComplex::get_preferred_repre-
    sentative (C++ function), 94
bats::ReducedChainComplex::hdim (C++ function),
    93
bats::ReducedChainComplex::I (C++ member), 94
bats::ReducedChainComplex::initialize (C++ func-
    tion), 93
bats::ReducedChainComplex::maxdim (C++ func-
    tion), 93
bats::ReducedChainComplex::operator[] (C++ func-
    tion), 93
bats::ReducedChainComplex::p2c (C++ member),
    94
bats::ReducedChainComplex::permute_basis
    (C++ function), 94
bats::ReducedChainComplex::permute_matrices
    (C++ function), 93
bats::ReducedChainComplex::print_summary
    (C++ function), 94
bats::ReducedChainComplex::R (C++ member), 94
bats::ReducedChainComplex::ReducedChainComplex
    (C++ function), 93
bats::ReducedChainComplex::remove_extra_cycles
    (C++ function), 94
bats::ReducedChainComplex::sparsify_basis
    (C++ function), 94
bats::ReducedChainComplex::to_hom_basis
    (C++ function), 94
bats::ReducedChainComplex::U (C++ member), 94
bats::ReducedChainComplex::update_basis_general
    (C++ function), 94
bats::ReducedChainComplex::update_reduction
    (C++ function), 93
bats::ReducedChainComplex::update_reduction2
    (C++ function), 93
bats::ReducedCochainComplex (C++ class), 95
bats::ReducedCochainComplex::chain_preferred_representati-
    ve (C++ function), 95
bats::ReducedCochainComplex::cochain_type
    (C++ type), 95
bats::ReducedCochainComplex::dim (C++ mem-
    ber), 96
bats::ReducedCochainComplex::find_preferred_representative
    (C++ function), 95
bats::ReducedCochainComplex::from_hom_basis
    (C++ function), 95
bats::ReducedCochainComplex::get_preferred_representative
    (C++ function), 95
bats::ReducedCochainComplex::hdim (C++ func-
    tion), 95
bats::ReducedCochainComplex::I (C++ member),
    96
bats::ReducedCochainComplex::maxdim (C++ func-
    tion), 95
bats::ReducedCochainComplex::operator[]
    (C++ function), 95
bats::ReducedCochainComplex::p2c (C++ mem-
    ber), 96
bats::ReducedCochainComplex::R (C++ member),
    96
bats::ReducedCochainComplex::ReducedCochainComplex
    (C++ function), 95
bats::ReducedCochainComplex::to_hom_basis
    (C++ function), 95
bats::ReducedCochainComplex::U (C++ member),
    96
bats::ReducedDGVectorSpace (C++ struct), 48
bats::ReducedDGVectorSpace::betti (C++ func-
    tion), 49
bats::ReducedDGVectorSpace::chain_preferred_representative
    (C++ function), 49
bats::ReducedDGVectorSpace::degree (C++ mem-
    ber), 50
bats::ReducedDGVectorSpace::dim (C++ function),
    49
bats::ReducedDGVectorSpace::find_preferred_representative
    (C++ function), 49
bats::ReducedDGVectorSpace::from_hom_basis
    (C++ function), 49
bats::ReducedDGVectorSpace::get_preferred_representative
    (C++ function), 49
bats::ReducedDGVectorSpace::hdim (C++ func-
    tion), 49
bats::ReducedDGVectorSpace::I (C++ member), 50
bats::ReducedDGVectorSpace::initialize (C++ func-
    tion), 49
bats::ReducedDGVectorSpace::maxdim (C++ func-
    tion), 49
bats::ReducedDGVectorSpace::operator[] (C++ func-
    tion), 49

```

```

    function), 49
bats::ReducedDGVectorSpace::p2c (C++ member),
    50
bats::ReducedDGVectorSpace::print_summary
    (C++ function), 49
bats::ReducedDGVectorSpace::R (C++ member), 50
bats::ReducedDGVectorSpace::ReducedDGVectorSpace
    (C++ function), 49
bats::ReducedDGVectorSpace::set_indices
    (C++ function), 49
bats::ReducedDGVectorSpace::to_hom_basis
    (C++ function), 49
bats::ReducedDGVectorSpace::U (C++ member), 50
bats::ReducedDGVectorSpace::vect_type (C++
    type), 49
bats::ReducedFilteredChainComplex (C++ struct),
    50
bats::ReducedFilteredChainComplex::barcode
    (C++ function), 51
bats::ReducedFilteredChainComplex::critical_cells
    (C++ function), 51
bats::ReducedFilteredChainComplex::dim (C++
    function), 50
bats::ReducedFilteredChainComplex::get_nnz_R
    (C++ function), 51
bats::ReducedFilteredChainComplex::get_nnz_U
    (C++ function), 51
bats::ReducedFilteredChainComplex::get_subcomplex
    (C++ function), 51
bats::ReducedFilteredChainComplex::hdim
    (C++ function), 50
bats::ReducedFilteredChainComplex::maxdim
    (C++ function), 50
bats::ReducedFilteredChainComplex::perm
    (C++ member), 51
bats::ReducedFilteredChainComplex::persistence
    (C++ function), 50
bats::ReducedFilteredChainComplex::print_summary
    (C++ function), 51
bats::ReducedFilteredChainComplex::RC (C++ member),
    51
bats::ReducedFilteredChainComplex::ReducedFilter
    (C++ function), 50
bats::ReducedFilteredChainComplex::remove_extra_
    (C++ function), 51
bats::ReducedFilteredChainComplex::representations
    (C++ function), 50
bats::ReducedFilteredChainComplex::sparsify_bak
    (C++ function), 51
bats::ReducedFilteredChainComplex::update_filtrat
    (C++ function), 51
bats::ReducedFilteredChainComplex::update_filtrat
    (C++ function), 51
bats::ReducedFilteredChainComplex::val (C++ mem
    ber), 51
bats::remove_extra_cycles (C++ function), 181
bats::Rips (C++ function), 181
bats::rips_edges (C++ function), 182
bats::rips_filtration_edges (C++ function), 182,
    183
bats::RipsComplex (C++ function), 183
bats::RipsFiltration (C++ function), 184
bats::RipsFiltration_extension (C++ function),
    184, 185
bats::RipsHom (C++ function), 185
bats::rowmajor::get_idx (C++ function), 185
bats::RPAngleDist (C++ struct), 52
bats::RPAngleDist::dist (C++ function), 52
bats::RPCosineDist (C++ struct), 52
bats::RPCosineDist::dist (C++ function), 52
bats::sample_cube (C++ function), 186
bats::sample_sphere (C++ function), 186
bats::serpinski_diagram (C++ function), 186
bats::SimplicialComplex (C++ class), 96
bats::SimplicialComplex::~SimplicialComplex
    (C++ function), 98
bats::SimplicialComplex::add (C++ function), 97
bats::SimplicialComplex::add_recursive (C++
    function), 97
bats::SimplicialComplex::boundary (C++ func
    tion), 98
bats::SimplicialComplex::boundary_csc (C++
    function), 98
bats::SimplicialComplex::faces_begin (C++ func
    tion), 97
bats::SimplicialComplex::faces_end (C++ func
    tion), 97
bats::SimplicialComplex::find_idx (C++ func
    tion), 96, 97
bats::SimplicialComplex::get_cell (C++ func
    tion), 97
bats::SimplicialComplex::get_indices (C++ func
    tion), 98
bats::SimplicialComplex::get_simplex (C++ func
    tion), 97
bats::SimplicialComplex::get_simplices (C++ func
    tion), 97
bats::SimplicialComplex::maxdim (C++ function),
    97
bats::SimplicialComplex::ncells (C++ function),
    97
bats::SimplicialComplex::print_cells (C++ func
    tion), 98
bats::SimplicialComplex::print_summary (C++ func
    tion), 98
bats::SimplicialComplex::save (C++ function), 98
bats::SimplicialComplex::simplex_begin (C++ func
    tion), 97

```

```

bats::SimplicialComplex::simplex_end    (C++ function), 97
bats::SimplicialComplex::SimplicialComplex (C++ function), 96
bats::SimplicialComplex::union_add (C++ function), 97
bats::SimplicialMap (C++ function), 187
bats::sort_edges (C++ function), 187
bats::sort_indexes (C++ function), 187
bats::sparse_reduction_flag (C++ struct), 53
bats::SparseTrie (C++ class), 98
bats::SparseTrie::~SparseTrie (C++ function), 99
bats::SparseTrie::child_container (C++ type), 99
bats::SparseTrie::child_type (C++ type), 99
bats::SparseTrie::children (C++ member), 100
bats::SparseTrie::count (C++ function), 99, 100
bats::SparseTrie::emplace (C++ function), 99
bats::SparseTrie::get (C++ function), 99
bats::SparseTrie::insert (C++ function), 99
bats::SparseTrie::operator= (C++ function), 99
bats::SparseTrie::operator[] (C++ function), 99
bats::SparseTrie::SparseTrie (C++ function), 99
bats::SparseTrie::val (C++ member), 100
bats::sparsify_basis (C++ function), 188
bats::standard_reduction_flag (C++ struct), 53
bats::StrictWitnessComplex (C++ function), 189
bats::tedge (C++ struct), 53
bats::tedge::s (C++ member), 53
bats::tedge::t (C++ member), 53
bats::tedge::tedge (C++ function), 53
bats::tedge::v (C++ member), 53
bats::test_reduce_result (C++ function), 189
bats::triangle (C++ struct), 54
bats::triangle::a (C++ member), 54
bats::triangle::ab (C++ member), 54
bats::triangle::b (C++ member), 54
bats::triangle::bc (C++ member), 54
bats::triangle::c (C++ member), 54
bats::triangle::ca (C++ member), 54
bats::triangle::triangle (C++ function), 54
bats::TriangulatedProduct (C++ function), 189, 190
bats::type_A_dq_common (C++ function), 190
bats::type_A_dq_EL (C++ function), 190
bats::type_A_dq_EU (C++ function), 190
bats::type_A_leftright_sweep1 (C++ function), 191
bats::type_A_leftright_sweep2 (C++ function), 191
bats::type_A_rightleft_sweep1 (C++ function), 191
bats::type_A_rightleft_sweep2 (C++ function), 191
bats::uniform_interval_cover (C++ function), 192
bats::Update_info (C++ struct), 54
bats::Update_info::addition_indices (C++ member), 55
bats::Update_info::boundary_indices (C++ member), 55
bats::Update_info::deletion_indices (C++ member), 55
bats::Update_info::F_new (C++ member), 55
bats::Update_info::F_old (C++ member), 55
bats::Update_info::F_X_perms (C++ member), 55
bats::Update_info::F_X_vals (C++ member), 55
bats::Update_info::F_Y_perms (C++ member), 55
bats::Update_info::F_Y_vals (C++ member), 55
bats::Update_info::filtered_boolean (C++ member), 55
bats::Update_info::filtered_info (C++ function), 54
bats::Update_info::intersection_indices_X (C++ member), 55
bats::Update_info::intersection_indices_Y (C++ member), 55
bats::Update_info::max_dim (C++ member), 55
bats::Update_info::perms_X_inv (C++ member), 55
bats::Update_info::perms_Y_inv (C++ member), 55
bats::Update_info::permutation_deletion_end (C++ function), 54
bats::Update_info::permutations (C++ member), 55
bats::Update_info::print_detail (C++ function), 55
bats::Update_info::print_summary (C++ function), 54
bats::Update_info::Update_info (C++ function), 54
bats::util::apply_iperm_swap (C++ function), 192
bats::util::apply_perm (C++ function), 192, 193
bats::util::apply_perm_swap (C++ function), 193
bats::util::fill_partial_sortperm (C++ function), 193
bats::util::fill_sortperm (C++ function), 193, 194
bats::util::find_sorted_lt (C++ function), 194
bats::util::firstk (C++ function), 194
bats::util::has_intersect_sorted (C++ function), 194
bats::util::has_intersect_sorted_lt (C++ function), 195
bats::util::intersect_sorted (C++ function), 195
bats::util::intersect_sorted_lt (C++ function), 195
bats::util::inv_perm (C++ function), 196

```

bats::util::io::parse_argv (*C++ function*), 196
 bats::util::is_degenerate (*C++ function*), 196
 bats::util::partial_perm (*C++ function*), 197
 bats::util::perm_inversions (*C++ function*), 197
 bats::util::perm_sign (*C++ function*), 197
 bats::util::rand_perm (*C++ function*), 197
 bats::util::random_subset (*C++ function*), 198
 bats::util::read_simplex (*C++ function*), 198
 bats::util::set_intersection (*C++ function*), 198
 bats::util::set_union (*C++ function*), 198
 bats::util::simplex_sign (*C++ function*), 199
 bats::util::SimplexContainer (*C++ class*), 100
 bats::util::SimplexContainer::dim (*C++ function*), 100
 bats::util::SimplexContainer::emplace_back (*C++ function*), 100
 bats::util::SimplexContainer::SimplexContainer
 bats::util::SimplexContainer::size (*C++ function*), 100
 bats::util::SimplexHasher (*C++ struct*), 55
 bats::util::SimplexHasher::operator() (*C++ function*), 56
 bats::util::sort_ind_by_perm (*C++ function*), 199
 bats::util::sort_ind_pair_by_perm (*C++ function*), 199
 bats::util::sort_into (*C++ function*), 199
 bats::util::sort_sum_reduce (*C++ function*), 200
 bats::util::sorted_complement (*C++ function*), 200
 bats::util::sortperm (*C++ function*), 200, 201
 bats::util::stable_sortperm (*C++ function*), 201
 bats::util::to_set (*C++ function*), 202
 bats::util::top_k (*C++ function*), 202
 bats::util::top_p (*C++ function*), 202
 bats::util::write_simplex (*C++ function*), 202, 203
 bats::vertex_inclusion_map (*C++ function*), 203
 bats::witness_edge_param (*C++ function*), 203
 bats::witness_edges (*C++ function*), 203, 204
 bats::witness_neighborhoods (*C++ function*), 204
 bats::WitnessComplex (*C++ function*), 204, 205
 bats::WitnessFiltration (*C++ function*), 205
 bats::zigzag::barcode (*C++ function*), 205
 bats::zigzag::detail::apply_basis (*C++ function*), 205
 bats::zigzag::detail::boundary_insertion_map
 (*C++ function*), 206
 bats::zigzag::detail::cube_extrema (*C++ function*), 206
 bats::zigzag::detail::cube_val (*C++ function*), 206
 bats::zigzag::detail::cycle_insertion_map
 (*C++ function*), 207
 bats::zigzag::detail::lex_cmp (*C++ function*), 207
 bats::zigzag::detail::rlex_cmp (*C++ function*), 207
 bats::zigzag::detail::simplex_extrema (*C++ function*), 208
 bats::zigzag::detail::update_bars (*C++ function*), 208
 bats::zigzag::extend_levelset (*C++ function*), 208
 bats::zigzag::extend_zigzag_filtration (*C++ function*), 209
 bats::zigzag::extra_col_reduction (*C++ function*), 209
 bats::zigzag::prepare_ChainComplex (*C++ function*), 210
 bats::zigzag::reduce_column (*C++ function*), 210, 211
 bats::zigzag::rfilt_val (*C++ struct*), 56
 bats::zigzag::rfilt_val::cind (*C++ member*), 56
 bats::zigzag::rfilt_val::dim (*C++ member*), 56
 bats::zigzag::rfilt_val::entry (*C++ member*), 56
 bats::zigzag::rfilt_val::ind (*C++ member*), 56
 bats::zigzag::rfilt_val::rfilt_val (*C++ function*), 56
 bats::zigzag::rfilt_val::val (*C++ member*), 56
 bats::zigzag::zigzag_barcode_reduction (*C++ function*), 211
 bats::zigzag::ZigzagChainComplex (*C++ struct*), 57
 bats::zigzag::ZigzagChainComplex::_correct_indices
 (*C++ function*), 57
 bats::zigzag::ZigzagChainComplex::C
 (*C++ member*), 58
 bats::zigzag::ZigzagChainComplex::cind
 (*C++ member*), 58
 bats::zigzag::ZigzagChainComplex::dim
 (*C++ function*), 57
 bats::zigzag::ZigzagChainComplex::maxdim
 (*C++ function*), 57
 bats::zigzag::ZigzagChainComplex::val
 (*C++ member*), 58
 bats::zigzag::ZigzagChainComplex::vals
 (*C++ function*), 57
 bats::zigzag::ZigzagChainComplex::ZigzagChainComplex
 (*C++ function*), 57
 bats::zigzag::ZigzagFiltration (*C++ class*), 100
 bats::zigzag::ZigzagFiltration::add
 (*C++ function*), 101
 bats::zigzag::ZigzagFiltration::add_recursive
 (*C++ function*), 101, 102
 bats::zigzag::ZigzagFiltration::complex
 (*C++ function*), 101

```

bats::zigzag::ZigzagFiltration::levelset      characteristic_matrix (C++ function), 213
                                                (C++ function), 102
bats::zigzag::ZigzagFiltration::maxdim (C++ function), 101
bats::zigzag::ZigzagFiltration::ncells (C++ function), 101
bats::zigzag::ZigzagFiltration::vals   (C++ function), 101
bats::zigzag::ZigzagFiltration::ZigzagFiltration (C++ function), 101
bats::zigzag::ZigzagPair (C++ struct), 58
bats::zigzag::ZigzagPair::birth (C++ member), 59
bats::zigzag::ZigzagPair::birth_ind   (C++ member), 59
bats::zigzag::ZigzagPair::birth_is_entry (C++ member), 59
bats::zigzag::ZigzagPair::death (C++ member), 59
bats::zigzag::ZigzagPair::death_ind   (C++ member), 59
bats::zigzag::ZigzagPair::death_is_entry (C++ member), 59
bats::zigzag::ZigzagPair::dim(C++ member), 59
bats::zigzag::ZigzagPair::get_birth   (C++ function), 58
bats::zigzag::ZigzagPair::get_birth_ind (C++ function), 58
bats::zigzag::ZigzagPair::get_death   (C++ function), 58
bats::zigzag::ZigzagPair::get_death_ind (C++ function), 58
bats::zigzag::ZigzagPair::get_dim (C++ function), 58
bats::zigzag::ZigzagPair::length (C++ function), 58
bats::zigzag::ZigzagPair::mid(C++ function), 58
bats::zigzag::ZigzagPair::operator!= (C++ function), 58
bats::zigzag::ZigzagPair::operator== (C++ function), 58
bats::zigzag::ZigzagPair::str(C++ function), 58
bats::zigzag::ZigzagPair::ZigzagPair (C++ function), 58
bats::zigzag_levelsets (C++ function), 212
bats::zigzag_toplex (C++ function), 212
block_reduce (C++ function), 212

C

cell_ind (C++ struct), 59
cell_ind::cell_ind (C++ function), 59
cell_ind::dim (C++ member), 59
cell_ind::ind (C++ member), 59
cell_ind::str (C++ function), 59
characteristic_matrix (C++ function), 213
ColumnMatrix (C++ class), 102
ColumnMatrix::add_rows (C++ function), 105
ColumnMatrix::append_column (C++ function), 103
ColumnMatrix::append_row (C++ function), 103, 104
ColumnMatrix::block (C++ function), 104
ColumnMatrix::clear_cols (C++ function), 104
ColumnMatrix::clear_rows (C++ function), 104
ColumnMatrix::col_inv_scale (C++ function), 106
ColumnMatrix::col_type (C++ type), 102
ColumnMatrix::cols (C++ function), 103
ColumnMatrix::ColumnMatrix (C++ function), 102, 103
ColumnMatrix::dump_dense (C++ function), 104
ColumnMatrix::erase_column (C++ function), 104
ColumnMatrix::erase_row (C++ function), 104
ColumnMatrix::erase_row_unsafe (C++ function), 104
ColumnMatrix::gemv (C++ function), 105
ColumnMatrix::getval (C++ function), 103
ColumnMatrix::identity (C++ function), 107
ColumnMatrix::insert_column (C++ function), 103
ColumnMatrix::insert_columns (C++ function), 103
ColumnMatrix::insert_row (C++ function), 104
ColumnMatrix::insert_rows (C++ function), 104
ColumnMatrix::ipermute_cols (C++ function), 105
ColumnMatrix::ipermute_rows (C++ function), 105
ColumnMatrix::is_EL (C++ function), 106
ColumnMatrix::is_ELhat (C++ function), 106
ColumnMatrix::is_EU (C++ function), 106
ColumnMatrix::is_EUhat (C++ function), 106
ColumnMatrix::is_lower (C++ function), 106
ColumnMatrix::is_pivot_matrix (C++ function), 106
ColumnMatrix::is_reduced (C++ function), 106
ColumnMatrix::is_upper (C++ function), 106
ColumnMatrix::is_upper_invert (C++ function), 106
ColumnMatrix::is_zero (C++ function), 106
ColumnMatrix::J_conjugation (C++ function), 106
ColumnMatrix::J_conjugation_inplace (C++ function), 106
ColumnMatrix::J_left (C++ function), 105
ColumnMatrix::J_left_inplace (C++ function), 105
ColumnMatrix::J_right (C++ function), 105
ColumnMatrix::J_right_inplace (C++ function), 105
ColumnMatrix::mix_cols (C++ function), 105
ColumnMatrix::mix_rows (C++ function), 105
ColumnMatrix::ncol (C++ function), 103
ColumnMatrix::nnz (C++ function), 106
ColumnMatrix::nrow (C++ function), 103
ColumnMatrix::operator() (C++ function), 104
ColumnMatrix::operator* (C++ function), 105

```

C
 ColumnMatrix::operator+ (*C++ function*), 105
 ColumnMatrix::operator+= (*C++ function*), 105
 ColumnMatrix::operator== (*C++ function*), 104
 ColumnMatrix::operator- (*C++ function*), 105
 ColumnMatrix::operator[] (*C++ function*), 104
 ColumnMatrix::permute (*C++ function*), 105
 ColumnMatrix::permute_cols (*C++ function*), 105
 ColumnMatrix::permute_rows (*C++ function*), 105
 ColumnMatrix::print (*C++ function*), 106
 ColumnMatrix::print_size (*C++ function*), 106
 ColumnMatrix::random (*C++ function*), 107
 ColumnMatrix::read (*C++ function*), 103
 ColumnMatrix::row_scale (*C++ function*), 106
 ColumnMatrix::save (*C++ function*), 107
 ColumnMatrix::schur_complement (*C++ function*),
 106
 ColumnMatrix::set_block (*C++ function*), 104
 ColumnMatrix::set_nrow (*C++ function*), 103
 ColumnMatrix::str (*C++ function*), 106
 ColumnMatrix::submatrix (*C++ function*), 104
 ColumnMatrix::swap_cols (*C++ function*), 106
 ColumnMatrix::swap_rows (*C++ function*), 104
 ColumnMatrix::T (*C++ function*), 105
 ColumnMatrix::to_row_array (*C++ function*), 104
 ColumnMatrix::transpose (*C++ function*), 105
 ColumnMatrix::val_type (*C++ type*), 102
 ColumnMatrix::write (*C++ function*), 106
 commute (*C++ function*), 213
 complete_pairs (*C++ function*), 213
 CSCMatrix (*C++ class*), 107
 CSCMatrix::CSCMatrix (*C++ function*), 108
 CSCMatrix::get_colptr (*C++ function*), 108
 CSCMatrix::get_rowind (*C++ function*), 108
 CSCMatrix::get_val (*C++ function*), 108
 CSCMatrix::getval (*C++ function*), 108
 CSCMatrix::ncol (*C++ function*), 108
 CSCMatrix::nrow (*C++ function*), 108
 CSCMatrix::operator* (*C++ function*), 108
 CSCMatrix::print (*C++ function*), 108
 CSCMatrix::print_size (*C++ function*), 108
 CSCMatrix::submatrix (*C++ function*), 108
 CU_inplace (*C++ function*), 214

D
 D (*C++ struct*), 60
 delete_pivot (*C++ function*), 214

E
 E (*C++ struct*), 61
 EL (*C++ struct*), 61
 EL_L_commute (*C++ function*), 214
 ELH (*C++ struct*), 61
 EU (*C++ struct*), 62
 EU_U_commute (*C++ function*), 214

EUH (*C++ struct*), 62
 extend_filtration (*C++ function*), 215
 extended_euclidean (*C++ function*), 215
 extract_pairs (*C++ function*), 215
 extract_row_scale (*C++ function*), 215

F
 ff_inv (*C++ function*), 216

G
 gemv (*C++ function*), 216
 generating_basis (*C++ function*), 216
 get_pivots (*C++ function*), 216

I
 IMPL_COUT (*C macro*), 233
 IMPL_FACT (*C macro*), 233
 inv (*C++ function*), 217
 is_UnivariatePolynomial (*C++ struct*), 63
 is_UnivariatePolynomial<UnivariatePolynomial<T>>
 (*C++ struct*), 63
 isprime (*C++ function*), 217

L
 L (*C++ struct*), 64
 L_EL_commute (*C++ function*), 217
 l_inv (*C++ function*), 217
 l_solve (*C++ function*), 218
 LEUP (*C++ function*), 218
 LEUP_Fact (*C++ function*), 218
 LEUP_fact (*C++ function*), 219
 LEUP_inplace (*C++ function*), 219
 lower_star_filtration (*C++ function*), 219, 220
 LQU (*C++ function*), 220
 LQU_inplace (*C++ function*), 220

M
 MAT (*C++ struct*), 64
 matmul (*C++ function*), 220–222
 max_cube_val (*C++ function*), 222
 MM (*C macro*), 234
 ModP (*C++ class*), 109
 ModP::inv (*C++ function*), 110
 ModP::iszero (*C++ function*), 110
 ModP::ModP (*C++ function*), 109
 ModP::operator!= (*C++ function*), 110
 ModP::operator* (*C++ function*), 109
 ModP::operator*= (*C++ function*), 109
 ModP::operator+ (*C++ function*), 109
 ModP::operator+= (*C++ function*), 109
 ModP::operator/ (*C++ function*), 110
 ModP::operator/= (*C++ function*), 110
 ModP::operator== (*C++ function*), 109, 110

ModP::operator- (*C++ function*), 109
ModP::operator-= (*C++ function*), 109
ModP::operator< (*C++ function*), 110
ModP::to_int (*C++ function*), 109
ModP<IntT, 2> (*C++ class*), 110
ModP<IntT, 2>::inv (*C++ function*), 111
ModP<IntT, 2>::iszero (*C++ function*), 111
ModP<IntT, 2>::ModP (*C++ function*), 111
ModP<IntT, 2>::operator!= (*C++ function*), 111
ModP<IntT, 2>::operator* (*C++ function*), 111
ModP<IntT, 2>::operator*= (*C++ function*), 111
ModP<IntT, 2>::operator+ (*C++ function*), 111
ModP<IntT, 2>::operator+= (*C++ function*), 111
ModP<IntT, 2>::operator/ (*C++ function*), 111
ModP<IntT, 2>::operator/= (*C++ function*), 111
ModP<IntT, 2>::operator= (*C++ function*), 111
ModP<IntT, 2>::operator== (*C++ function*), 111
ModP<IntT, 2>::operator- (*C++ function*), 111
ModP<IntT, 2>::operator-= (*C++ function*), 111
ModP<IntT, 2>::operator< (*C++ function*), 111
ModP<IntT, 2>::to_int (*C++ function*), 111
MorsePairing (*C++ class*), 112
MorsePairing::add (*C++ function*), 113
MorsePairing::add_pair (*C++ function*), 113
MorsePairing::boundary_csc (*C++ function*), 113
MorsePairing::clear (*C++ function*), 112
MorsePairing::down_paired (*C++ function*), 112
MorsePairing::faces_begin (*C++ function*), 113
MorsePairing::faces_end (*C++ function*), 113
MorsePairing::is_paired (*C++ function*), 112
MorsePairing::maxdim (*C++ function*), 112
MorsePairing::MorsePairing (*C++ function*), 112
MorsePairing::ncells (*C++ function*), 112
MorsePairing::set_pair (*C++ function*), 112
MorsePairing::set_pair_edge (*C++ function*), 112
MorsePairing::size (*C++ function*), 112
MorsePairing::unpaired (*C++ function*), 113
MorsePairing::up_paired (*C++ function*), 112
MultiGraph (*C++ class*), 113
MultiGraph::add_edge (*C++ function*), 114
MultiGraph::add_node (*C++ function*), 114
MultiGraph::Edge (*C++ struct*), 65, 114
MultiGraph::Edge::data (*C++ member*), 65, 114
MultiGraph::Edge::Edge (*C++ function*), 65, 114
MultiGraph::Edge::get_data (*C++ function*), 65, 114
MultiGraph::Edge::print (*C++ function*), 65, 114
MultiGraph::Edge::src (*C++ member*), 65, 114
MultiGraph::Edge::targ (*C++ member*), 65, 114
MultiGraph::MultiGraph (*C++ function*), 114
MultiGraph::Node (*C++ struct*), 65, 114
MultiGraph::Node::add_input (*C++ function*), 65, 114
MultiGraph::Node::add_output (*C++ function*), 65, 114
MultiGraph::Node::data (*C++ member*), 66, 115
MultiGraph::Node::get_data (*C++ function*), 65, 114
MultiGraph::Node::input (*C++ member*), 66, 115
MultiGraph::Node::Node (*C++ function*), 65, 114
MultiGraph::Node::output (*C++ member*), 66, 115
MultiGraph::Node::print (*C++ function*), 66, 114

N

nzpair (*C++ struct*), 66
nzpair::ind (*C++ member*), 67
nzpair::nzpair (*C++ function*), 66
nzpair::operator!= (*C++ function*), 66
nzpair::operator== (*C++ function*), 66
nzpair::val (*C++ member*), 67

O

operator< (*C++ function*), 222, 223
operator<< (*C++ function*), 223–225

P

P (*C++ struct*), 67
p2c_type (*C macro*), 234
pivot_ind (*C++ function*), 225
PLEU (*C++ function*), 225
PLEU_Fact (*C++ function*), 226
PLEU_fact (*C++ function*), 226
PLEU_inplace (*C++ function*), 226
PUEL (*C++ function*), 226
PUEL_Fact (*C++ function*), 227
PUEL_fact (*C++ function*), 227
PUEL_inplace (*C++ function*), 227

R

Rational (*C++ class*), 115
Rational::inv (*C++ function*), 116
Rational::iszero (*C++ function*), 116
Rational::operator!= (*C++ function*), 116
Rational::operator* (*C++ function*), 115
Rational::operator*= (*C++ function*), 115
Rational::operator+ (*C++ function*), 115
Rational::operator+= (*C++ function*), 115
Rational::operator/ (*C++ function*), 116
Rational::operator/= (*C++ function*), 116
Rational::operator== (*C++ function*), 116
Rational::operator- (*C++ function*), 115
Rational::operator-= (*C++ function*), 115
Rational::operator< (*C++ function*), 116
Rational::Rational (*C++ function*), 115
Rational::to_int (*C++ function*), 115
RCF_basis (*C++ function*), 227

S

schur (*C++ function*), 228
 SetVector (*C++ class*), 116
 SetVector::axpy (*C++ function*), 117
 SetVector::get (*C++ function*), 117
 SetVector::lastnz (*C++ function*), 117
 SetVector::lower_bound (*C++ function*), 117
 SetVector::nnz (*C++ function*), 117
 SetVector::nzbegin (*C++ function*), 117
 SetVector::nzend (*C++ function*), 117
 SetVector::operator== (*C++ function*), 118
 SetVector::permute (*C++ function*), 117
 SetVector::print (*C++ function*), 118
 SetVector::print_row (*C++ function*), 118
 SetVector::replace (*C++ function*), 117
 SetVector::set (*C++ function*), 117
 SetVector::SetVector (*C++ function*), 116, 117
 SetVector::upper_bound (*C++ function*), 117
 sgn (*C++ function*), 228, 229
 SI (*C++ struct*), 67
 smith_factorization (*C++ function*), 229
 smith_normal_form (*C++ function*), 229
 smith_rows (*C++ function*), 229
 SmithFact (*C++ struct*), 67
 SmithFact::C (*C++ member*), 68
 SmithFact::prod (*C++ function*), 68
 SmithFact::R (*C++ member*), 68
 SmithFact::S (*C++ member*), 68
 SparseFact (*C++ struct*), 68
 SparseFact::E (*C++ member*), 68
 SparseFact::L (*C++ member*), 68
 SparseFact::LEUP_prod (*C++ function*), 68
 SparseFact::LQU_prod (*C++ function*), 68
 SparseFact::P (*C++ member*), 68
 SparseFact::PLEU_prod (*C++ function*), 68
 SparseFact::PUEL_prod (*C++ function*), 68
 SparseFact::U (*C++ member*), 68
 SparseFact::UELP_prod (*C++ function*), 68
 SparseFact::UQL_prod (*C++ function*), 68
 SparseVector (*C++ class*), 118
 SparseVector::axpy (*C++ function*), 121, 122
 SparseVector::block (*C++ function*), 120
 SparseVector::clear (*C++ function*), 119
 SparseVector::clear_dealloc (*C++ function*), 119
 SparseVector::clear_inds (*C++ function*), 119
 SparseVector::clear_zeros (*C++ function*), 119
 SparseVector::coeff_intersection (*C++ function*), 121
 SparseVector::emplace_back (*C++ function*), 120
 SparseVector::erase_for_matrix (*C++ function*), 121
 SparseVector::erase_last_row_of_matrix (*C++ function*), 121
 SparseVector::find_last_nz (*C++ function*), 120

SparseVector::firstnz (*C++ function*), 120
 SparseVector::getval (*C++ function*), 120
 SparseVector::insert_rows (*C++ function*), 121
 SparseVector::ipermute (*C++ function*), 120
 SparseVector::J (*C++ function*), 121
 SparseVector::kron (*C++ function*), 122
 SparseVector::lastnz (*C++ function*), 120
 SparseVector::lower_bound (*C++ function*), 120
 SparseVector::mix_rows (*C++ function*), 121
 SparseVector::nnz (*C++ function*), 119
 SparseVector::nnz_intersection (*C++ function*), 121
 SparseVector::nzbegin (*C++ function*), 119
 SparseVector::nzend (*C++ function*), 119
 SparseVector::nzinds (*C++ function*), 119
 SparseVector::nzs (*C++ function*), 120
 SparseVector::nzvals (*C++ function*), 120
 SparseVector::operator!= (*C++ function*), 119
 SparseVector::operator* (*C++ function*), 121
 SparseVector::operator+ (*C++ function*), 121
 SparseVector::operator== (*C++ function*), 119
 SparseVector::operator[] (*C++ function*), 119, 120
 SparseVector::permute (*C++ function*), 120
 SparseVector::print (*C++ function*), 122
 SparseVector::print_row (*C++ function*), 122
 SparseVector::random (*C++ function*), 122
 SparseVector::replace (*C++ function*), 120
 SparseVector::scale (*C++ function*), 122
 SparseVector::scale_inplace (*C++ function*), 121, 122
 SparseVector::set_block (*C++ function*), 121
 SparseVector::shift_inds (*C++ function*), 119
 SparseVector::sort (*C++ function*), 118
 SparseVector::SparseVector (*C++ function*), 118, 119
 SparseVector::str (*C++ function*), 122
 SparseVector::subvector (*C++ function*), 120
 SparseVector::swap_rows (*C++ function*), 121
 SparseVector::tensor (*C++ function*), 122
 SparseVector::tmp_type (*C++ type*), 118
 SparseVector::upper_bound (*C++ function*), 120
 SparseVector::val_type (*C++ type*), 118
 SparseVector::write (*C++ function*), 122
 standard_reduce (*C++ function*), 230

T

T (*C++ struct*), 69

U

U (*C++ struct*), 70
 U_EU_commute (*C++ function*), 230
 u_inv (*C++ function*), 230
 u_solve (*C++ function*), 230, 231
 UELP (*C++ function*), 231

UEL_P_Fact (*C++ function*), 231
UEL_P_fact (*C++ function*), 231
UEL_P_inplace (*C++ function*), 232
UnivariatePolynomial (*C++ class*), 123
UnivariatePolynomial::companion_matrix (*C++ function*), 124
UnivariatePolynomial::degree (*C++ function*), 123
UnivariatePolynomial::dim (*C++ function*), 123
UnivariatePolynomial::divrem (*C++ function*), 124
UnivariatePolynomial::gcd (*C++ function*), 124
UnivariatePolynomial::identity (*C++ function*), 124
UnivariatePolynomial::is_monic (*C++ function*), 124
UnivariatePolynomial::is_zero (*C++ function*), 123
UnivariatePolynomial::leading_coeff (*C++ function*), 123
UnivariatePolynomial::monomial (*C++ function*), 124
UnivariatePolynomial::operator!= (*C++ function*), 124
UnivariatePolynomial::operator() (*C++ function*), 123
UnivariatePolynomial::operator* (*C++ function*), 124
UnivariatePolynomial::operator+ (*C++ function*), 123
UnivariatePolynomial::operator+= (*C++ function*), 123
UnivariatePolynomial::operator/ (*C++ function*), 124
UnivariatePolynomial::operator== (*C++ function*), 124
UnivariatePolynomial::operator- (*C++ function*), 123
UnivariatePolynomial::operator-= (*C++ function*), 123
UnivariatePolynomial::operator[] (*C++ function*), 123
UnivariatePolynomial::print (*C++ function*), 124
UnivariatePolynomial::remainder (*C++ function*), 124
UnivariatePolynomial::size (*C++ function*), 123
UnivariatePolynomial::UnivariatePolynomial (*C++ function*), 123
UnivariatePolynomial::zero (*C++ function*), 124
update_pivot (*C++ function*), 232
UQL (*C++ function*), 232